

SC5000 Series Professional IP Camera Price List

Support Hikvision & Dahua
NVR and CMS Plug & Play

H.265/H.264
1/2/3/4/5/8/12MP

Intelligent
Video

Smart
Streaming

ROI

Sony
Sensor*

WDR
Starlight

Video
Flip

ONVIF2.4
HTTP API

3D/2D
DNR

IPv6

Note:

- Our most prices have Minimum Order Quantity (MOQ) requirement, if your order quantity is less than the MOQ, the unit price will add \$5-20; If the order total value is less than USD5,000, you maybe need to pay additional charges (\$20-30). We could update the price in any time and don't immediately notice you.
- *Intelligent video analytics: support Tampering, Audio Detection, Intrusion detection(Region entrance, Region exiting), Unattended baggage, Virtual Line(Line crossing detection), Motion Detection, Exception Detections(brightness change detection, Defocus detection), some cheap or old model don't support this function;
- * Some cheap models don't use Sony sensor.

Picture	Model	Specifications	Price	Power	Lens	Infrared	Waterproof	Options & Remark
	SC5S21C	2 Megapixel 1080P 25fps Small Indoor IR Plastic Dome IP Camera 2 Megapixel Sony Low light sensor IMX323 + Hi3516CV200 SoC chip, 1920x1080@25fps, Color: 0.1Lux@F1.2; B/W:0.01Lux@F1.2; DWDR,BLC,ROI, Tampering alarm, 2.8mm M12 lens, 3 pcs array LED light, IR distance:20-30m, built-in Smart function, ONVIF; DC12V & PoE, No AC/DC adapter. P2P Mobile Monitoring.		PoE	2.8mm	20-30m	X	1.MOQ: 100pcs 2.Sample price: plus \$15 3.3.6mm lens is optional
	SC5S41A	4 Megapixel 15fps H.265/H.264 WDR Small Indoor IR PoE Plastic Dome IP Camera 4 Megapixel : 2592x1520@15fps, 3 Megapixel: 2048x1520@25fps, OV4689 + Hi3516D SoC chip, WDR 120dB,BLC,ROI, 3D DNR, Tampering alarm, 2.8mm M12 lens, 3 pcs array LED light, IR distance:20-30m, built-in Smart function, ONVIF; DC12V&PoE, No AC/DC adapter. P2P Mobile Monitoring. Support intelligent video analysis.		PoE	2.8mm	20-30m	X	1.MOQ: 50pcs 2.Sample price: plus \$15 3.3.6mm lens is optional
	SC5S51A	5 Megapixel 15fps H.265/H.264 WDR Small Indoor IR PoE Plastic Dome IP Camera 5 Megapixel sensor AR0521 + Hi3516A SoC chip, 5 megapixel(2592*1944)@15fps, 3MP@25/30fps,BLC,ROI, 3D DNR, Tampering alarm, 2.8mm M12 lens, 3 pcs array LED light, IR distance:20-30m, built-in Smart function, ONVIF; DC12V&PoE, No AC/DC adapter. P2P Mobile Monitoring. Support intelligent video analysis.		PoE	2.8mm	20-30m	X	1.MOQ: 20pcs 2.Sample price: plus \$15 3.3.6mm lens is optional
	SC5N21	2 Megapixel 1080P Sony Sensor Small Vandal Proof Dome PoE IP Camera H.264 1920x1080@25fps, Sony 2 Megapixel Low light sensor IMX323 + Hi3516CV200 SoC chip, Color: 0.1Lux@F1.2; B/W:0.01Lux@F1.2; DWDR,BLC,ROI, 3D DNR, Tampering alarm, 3.6mm M12 lens, 24 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IK10, IP66.		PoE	3.6mm	20-30m	IP66	1.MOQ: 10pcs 2. Sample price: plus \$5 3. 2.8mm lens: \$1 4. SD card slot: \$5 5. Audio input/out, reset, alarm input cable: \$10
	SC5N21-MIC	2 Megapixel 1080P Sony Sensor Small Vandal Proof Dome PoE IP Camera H.264 1920x1080@25fps, Sony 2 Megapixel Low light sensor IMX323 + Hi3516C SoC chip, Color: 0.1Lux@F1.2; B/W:0.01Lux@F1.2; DWDR,BLC,ROI, 3D DNR, Tampering alarm, 3.6mm M12 lens, 24 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE, built-in microphone, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome.IK10, IP66.		PoE	3.6mm	20-30m	X	1.MOQ: 10pcs 2. Sample price: plus \$5 3. 2.8mm lens: \$1 4. SD card slot: \$5

	SC5N21B	2 Megapixel 1080P Sony Sensor Small Vandal Proof Smart Dome PoE IP Camera H.265/H.264 1920x1080@25fps, Sony 2 Megapixel Low light sensor IMX323 + Hi3516CV300 SoC chip, Color: 0.1Lux@F1.2; B/W:0.01Lux@F1.2; DWDR,BLC,ROI, 3D DNR, Tampering alarm, 3.6mm M12 lens, 24 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IK10, IP66. Support Audio Detection, Line Crossing Detection, Intrusion Detection, Unattended baggage; Color,brightness,Defocus Exception Detections.		PoE	3.6mm	20-30m	IP66	1.MOQ: 10pcs 2. Sample price: plus \$5 3. 2.8mm lens: \$1 4. SD card slot: \$5 5. Audio input/out, reset, alarm input cable: \$10
	SC5N21B-MIC	2 Megapixel 1080P Sony Sensor Small Vandal Proof Smart Dome PoE IP Camera H.265/H.264 1920x1080@25fps, Sony 2 Megapixel Low light sensor IMX323 + Hi3516CV300 SoC chip, Color: 0.1Lux@F1.2; B/W:0.01Lux@F1.2; DWDR,BLC,ROI, 3D DNR, Tampering alarm, 3.6mm M12 lens, 24 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE, built-in microphone, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome.IK10, IP66. Support Audio Detection, Line Crossing Detection, Intrusion Detection, Unattended baggage; Color,brightness,Defocus Exception Detections.		PoE	3.6mm	20-30m	X	1.MOQ: 20pcs 2. Sample price: plus \$5 3. 2.8mm lens: \$1 4. SD card slot: \$5
	SC5N21S	H.265 2 Megapixel 1080P Sony Starlight Sensor Small Vandal Proof Dome PoE IP Camera 1920x1080@25fps, Sony IMX291 2 Megapixel starlight sensor + Hi3516CV300 SoC chip, Full color: 0.001Lux@F1.2; DWDR,BLC,ROI, 3D DNR, Tampering alarm, 3.6mm M12 lens, 24 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome,IK10, IP66. . Support Audio Detection, Line Crossing Detection, Intrusion Detection, Unattended baggage; Color,brightness,Defocus Exception Detections.		PoE	3.6mm	20-30m	IP66	1.MOQ: 10pcs 2. Sample price: plus \$5 3. 2.8mm lens: \$1 4. SD card slot: \$5 5. Audio input/out, reset, alarm input cable: \$10 6. Intelligent Video Analytics: \$5s
	SC5N21S-MIC	H.265 2 Megapixel 1080P Sony Starlight Sensor Small Vandal Proof Dome PoE IP Camera 1920x1080@25fps, Sony IMX291 2 Megapixel starlight sensor + Hi3516V300 SoC chip, Full color: 0.001Lux@F1.2; DWDR,BLC,ROI, 3D DNR, Tampering alarm, 3.6mm M12 lens, 24 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE, built-in microphone, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome.IK10, IP66. . Support Audio Detection, Line Crossing Detection, Intrusion Detection, Unattended baggage; Color,brightness,Defocus Exception Detections.		PoE	3.6mm	20-30m	X	1.MOQ: 10pcs 2. Sample price: plus \$5 3. 2.8mm lens: \$1 4. SD card slot: \$5 5. Intelligent Video Analytics: \$5

	SC5N21W	H.265 2 Megapixel 1080P Sony Optical WDR Starlight Sensor Small Vandal Proof Dome PoE IP Camera 1920x1080@25fps, Sony IMX290 2 Megapixel starlight sensor + Hi3516CV300 SoC chip, Full color: 0.001Lux@F1.2; Optical WDR>120dB,BLC,ROI, 3D DNR, Tampering alarm, 3.6mm M12 lens, 24 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome,IK10, IP66. Support Audio Detection, Line Crossing Detection, Intrusion Detection, Unattended baggage; Color,brightness,Defocus Exception Detections.		PoE	3.6mm	20-30m	IP66	1.MOQ: 20pcs 2. Sample price: plus \$5 3. 2.8mm lens: \$1 4. SD card slot: \$5 5. Audio input/out, reset, alarm input cable: \$10
	SC5N31B	3 Megapixel Sony Starlight Sensor Small Vandal Proof Smart Dome PoE IP Camera 2048*1536@25fps, Sony 3 Megapixel Low light sensor IMX124+ Hi3516D SoC chip, Full Color: 0.001Lux@F1.2; DWDR,BLC,ROI, 3D DNR, Tampering alarm, 3.6mm M12 lens, 24 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome,IK10, IP66. Support Audio Detection, Line Crossing Detection, Intrusion Detection, Unattended baggage; Color,brightness,Defocus Exception Detections.		PoE	3.6mm	20-30m	IP66	1.MOQ: 10pcs 2. Sample price: plus \$5 3. 2.8mm lens: \$1 4. Built-in microphone:\$5
	SC5N41A	4 Megapixel 15fps H.265/H.264 WDR Small Vandal Proof Dome PoE IP Camera 4 Megapixel : 2592x1520@15fps, 3 Megapixel: 2048x1520@25fps, 4 Megapixel sensor OV4689 + Hi3516D SoC chip, WDR 120dB,BLC,ROI, 3D DNR, Tampering alarm, 3.6mm M12 lens, 24 pcs LED light, built-in Smart function, ONVIF; DC12V,built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IK10, IP66. Support Audio Detection, Line Crossing Detection, Intrusion Detection, Unattended baggage; Color,brightness,Defocus Exception Detections.		PoE	3.6mm	20-30m	IP66	1.MOQ: 10pcs 2. Sample price: plus \$5 3. 2.8mm lens: \$1
	SC5N41A-MIC	4 Megapixel 15fps H.265/H.264 WDR Small Vandal Proof Dome PoE IP Camera with Microphone 4 Megapixel : 2592x1520@15fps, 3 Megapixel: 2048x1520@25fps, 4 Megapixel sensor OV4689 + Hi3516D SoC chip, WDR 120dB,BLC,ROI, 3D DNR, Tampering alarm, 3.6mm M12 lens, 24 pcs LED light, built-in Smart function, ONVIF; DC12V,built-in PoE, built-in Microphone, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IK10, IP66. Support Audio Detection, Line Crossing Detection, Intrusion Detection, Unattended baggage; Color,brightness,Defocus Exception Detections.		PoE	3.6mm	20-30m	X	1.MOQ: 10pcs 2. Sample price: plus \$5 3. 2.8mm lens: \$1

	SC5N51A	5 Megapixel 25/30fps H.265/H.264 WDR Small Vandal Proof Smart Dome PoE IP Camera 5 Megapixel sensor AR0521 + Hi3516A SoC chip, 5 megapixel: 2592*1944, 25/30fps, Color: 0.05Lux@F1.2,B/W: 0.01 Lux@F1.2 DWDR,BLC,ROI, 3D DNR, Tampering alarm, 3.6mm M12 lens, 24 pcs LED light, built-in Smart function, ONVIF; DC12V,built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IK10, IP66. Support Audio Detection, Line Crossing Detection, Intrusion Detection, Unattended baggage; Color,brightness,Defocus Exception Detections.		PoE	3.6mm	20-30m	IP66	1.MOQ: 20pcs 2. Sample price: plus \$5 3. 2.8mm lens: \$1 4. Built-in microphone:\$5
	SC5N81A	8 Megapixel 4K 15fps Small Indoor IR PoE Vandal Proof Dome IP Camera H.265/H.264 , Sony Starlight + Digital Overlap-HDR 1/2.5" CMOS sensor IMX274+ Hisilicon High performance SOC chip Hi3516V200, support 8 Megapixel 4K (3840*2160)15fps extra high definition, Color: 0.01Lux@F1.2; B/W:0.001Lux@F1.2; HDR,BLC,ROI,Tampering alarm, 4mm fixed lens, 24 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IP66, IK10. Support Audio Detection, Line Crossing Detection, Intrusion Detection, Unattended baggage; Color,brightness,Defocus Exception Detections.		PoE	4mm	20-30m	IP66	1.MOQ: 5pcs 2. Sample price: plus \$15 3.2.8/3.6/4/6mm lens is optional 4. Built-in microphone:\$5
	SC5N81	8 Megapixel 4K 25/30fps Small Indoor IR PoE Vandal Proof Dome IP Camera Sony Starlight + Digital Overlap-HDR 1/2.5" CMOS sensor IMX274+ Hisilicon High performance SOC chip Hi3519, support 8 Megapixel 4K (3840*2160) realtime 25/30fps extra high definition, Color: 0.01Lux@F1.2; B/W:0.001Lux@F1.2; HDR,BLC,ROI,Tampering alarm, 4mm fixed lens, 24 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IP66, IK10. Support Audio Detection, Line Crossing Detection, Intrusion Detection, Unattended baggage; Color,brightness,Defocus Exception Detections.		PoE	4mm	20-30m	IP66	1.MOQ: 5pcs 2. Sample price: plus \$15 3.2.8/3.6/4/5/6mm lens is optional 4. Built-in microphone:\$5
	SC5J21	2 Megapixel 1080P Vandal Proof Dome PoE IP Camera 1920x1080@25fps, Sony IMX323 2 Megapixel sensor + Hi3516C SoC chip, 2.8mm M12 lens, 24 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring. IK10, IP66.		PoE	2.8mm	20-30m	IP66	1. 2.8/ 3.6mm option 2. 2.8-12mm varifocal lens: \$3 3. audio input/output: \$5 4. audio, alarm, BNC, RS485 etc. full functions: \$12 5. TF card slot: \$5 6. MOQ: 5pcs
	SC5J21Z	2 Megapixel 1080P Motorized Zoom Vandal Proof Dome PoE IP Camera 1920x1080@25fps, Sony IMX323 2 Megapixel sensor + Hi3516C SoC chip, 2.7-13.5mm motorized zoom varifocal lens, 24 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring. IK10, IP66.		PoE	2.7-13.5mm Motorized Zoom	20-30m	IP66	1. audio, alarm, BNC, RS485 etc. full functions: \$12 2. TF card slot: \$5 3. Update to H.265: \$2 4. MOQ: 5pcs

	SC5J21-T12	2 Megapixel 1080P Vandal Proof Dome PoE IP Camera 1920x1080@25fps, Sony IMX323 2 Megapixel sensor + Hi3516C SoC chip, 2.8-12mm varifocal lens, 24 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring. IK10, IP66.		PoE	2.8-12mm	20-30m	IP66	1. 2.8/ 3.6mm option 2. audio input/output: \$5 3. audio, alarm, BNC, RS485 etc. full functions: \$12 4. TF card slot: \$5 5. MOQ: 5pcs 6. Sample price: plus \$5
	SC5J21B	2 Megapixel 1080P Vandal Proof Dome PoE IP Camera H.265/H.264, 1920x1080@25fps, Sony IMX323 2 Megapixel sensor + Hi3516C SoC chip, 2.8mm M12 lens, 24 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring. IK10, IP66. Support Audio Detection, Line Crossing Detection, Intrusion Detection, Unattended baggage; Color, brightness, Defocus Exception Detections.		PoE	2.8mm	20-30m	IP66	1. 2.8/ 3.6mm option 2. 2.8-12mm varifocal lens: \$3 3. audio input/output: \$5 4. audio, alarm, BNC, RS485 etc. full functions: \$12 5. TF card slot: \$5 6. MOQ: 5pcs 7. Sample price: plus \$5
	SC5J21B-T12	2 Megapixel 1080P Vandal Proof Dome PoE IP Camera H.265/H.264, 1920x1080@25fps, Sony IMX323 2 Megapixel sensor + Hi3516C SoC chip, 2.8-12mm varifocal lens, 24 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring. IK10, IP66. Support Audio Detection, Line Crossing Detection, Intrusion Detection, Unattended baggage; Color, brightness, Defocus Exception Detections.		PoE	2.8-12mm	20-30m	IP66	1. 2.8/ 3.6mm option 2. audio input/output: \$5 3. audio, alarm, BNC, RS485 etc. full functions: \$12 4. TF card slot: \$5 5. MOQ: 5pcs 6. Sample price: plus \$5
	SC5J21W-T12	2 Megapixel 1080P Sony Optical WDR Starlight Sensor Vandal Proof Smart Dome PoE IP Camera H.265/H.264, 1920x1080@25fps, Sony IMX290 2 Megapixel Optical WDR sensor + Hi3516D SoC chip, 2.8-12mm varifocal lens, 24 pcs LED light, built-in Smart function, WDR>120dB, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring. IK10, IP66. Support Audio Detection, Line Crossing Detection, Intrusion Detection, Unattended baggage; Color, brightness, Defocus Exception Detections.		PoE	2.8-12mm	20-30m	IP66	1. 2.8/ 3.6mm option 2. audio input/output: \$5 3. audio, alarm, BNC, RS485 etc. full functions: \$12 4. TF card slot: \$5 5. MOQ: 5pcs 6. Sample price: plus \$5
	SC5J21WZ	2 Megapixel 1080P Sony Optical WDR Starlight Sensor Motorized Zoom Vandal Proof Smart Dome PoE IP Camera H.265/H.264, 1920x1080@25fps, Sony IMX290 2 Megapixel Optical WDR sensor + Hi3516D SoC chip, 0.00ILux, 2.7-13.5mm motorized zoom varifocal lens, 24 pcs LED light, built-in Smart function, WDR>120dB, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring. IK10, IP66. Support Audio Detection, Line Crossing Detection, Intrusion Detection, Unattended baggage; Color, brightness, Defocus Exception Detections.		PoE	2.7-13.5mm Motorized Zoom	20-30m	IP66	1. 2.8/ 3.6mm option 2. audio input/output: \$5 3. audio, alarm, BNC, RS485 etc. full functions: \$12 4. TF card slot: \$5 5. MOQ: 5pcs 6. Sample price: plus \$5

	SC5J21D-T12	2 Megapixel 1080P 50/60fps Sony Starlight Sensor Vandal Proof Smart Dome PoE IP Camera H.265/H.264, 1920x1080@50/60fps, Sony IMX290 2 Megapixel starlight sensor + Hi3516D SoC chip, 2.8-12mm varifocal lens, 24 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring. IK10, IP66. Support Audio Detection, Line Crossing Detection, Intrusion Detection, Unattended baggage; Color, brightness, Defocus Exception Detections.		PoE	2.8-12mm	20-30m	IP66	1. 2.8/ 3.6mm option 2. audio input/output: \$5 3. audio, alarm, BNC, RS485 etc. full functions: \$12 4. TF card slot: \$5 5. MOQ: 5pcs 6. Sample price: plus \$5
	SC5J31B	3 Megapixel 25fps Starlight Vandal Proof Dome PoE IP Camera 2048*1536@25fps, Sony 3 Megapixel Starlight sensor IMX124+ Hi3516D SoC chip, Full Color: 0.001Lux@F1.2; DWDR, BLC, ROI, 3D DNR, Tampering alarm 2.8mm M12 lens, 24 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring. IK10, IP66. Support Audio Detection, Line Crossing Detection, Intrusion Detection, Unattended baggage; Color, brightness, Defocus Exception Detections.		PoE	2.8mm	20-30m	IP66	1. 2.8/ 3.6mm option 2. 2.8-12mm varifocal lens: \$3 3. audio input/output: \$5 4. audio, alarm, BNC, RS485 etc. full functions: \$12 5. TF card slot: \$5 6. 2.7-13.5mm motorized zoom: 7. MOQ: 5pcs 8. Sample price: plus \$10
	SC5J31BZ	3 Megapixel 25fps Starlight Motorized Zoom Vandal Proof Smart Dome PoE IP Camera 2048*1536@25fps, Sony 3 Megapixel Starlight sensor IMX124+ Hi3516D SoC chip, Full Color: 0.001Lux@F1.2; DWDR, BLC, ROI, 3D DNR, Tampering alarm, 2.7-13.5 motorized zoom varifocal lens, 24 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring. IK10, IP66. Support Audio Detection, Line Crossing Detection, Intrusion Detection, Unattended baggage; Color, brightness, Defocus Exception Detections.		PoE	2.7-13.5mm motorized zoom	20-30m	IP66	1. 2.8/ 3.6mm option 2. 2.8-12mm varifocal lens: \$3 3. audio input/output: \$5 4. audio, alarm, BNC, RS485 etc. full functions: \$12 5. TF card slot: \$5 6. Sample price: plus \$10
	SC5J41A	4 Megapixel 15fps, H.265/H.264 Vandal Proof Dome PoE IP Camera 4 Megapixel : 2592x1520@15fps, 3 Megapixel: 2048x1520@25fps, 4 Megapixel sensor OV4689 + Hi3516D SoC chip, 2.8mm M12 lens, 24 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring. IK10, IP66.		PoE	2.8mm	20-30m	IP66	1. 2.8/ 3.6mm option 2. 2.8-12mm varifocal lens: \$3 3. audio input/output: \$5 4. audio, alarm, BNC, RS485 etc. full functions: \$12 5. TF card slot: \$5 6. MOQ: 5pcs 7. Sample price: plus \$5
	SC5J41AZ	4 Megapixel 15fps, H.265/H.264 Vandal Proof Dome PoE IP Camera 4 Megapixel : 2592x1520@15fps, 3 Megapixel: 2048x1520@25fps, 4 Megapixel sensor OV4689 + Hi3516D SoC chip, 2.8-12mm motorized zoom & auto focus lens, 24 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring. IK10, IP66.		PoE	2.8-12mm motorized zoom & autofocus	20-30m	IP66	1. audio input/output: \$5 2. MOQ: 5pcs 3. Sample price: plus \$5
	SC5J41B	4 Megapixel 25fps, H.265/H.264 Vandal Proof Smart Dome PoE IP Camera 4 Megapixel : 2592x1520@25fps, 1080P@50/60fps , 4 Megapixel sensor OV4689 + Hi3516A SoC chip, 2.8mm M12 lens, 24 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring. IK10, IP66.		PoE	2.8mm	20-30m	IP66	1. 2.8/ 3.6mm option 2. 2.8-12mm varifocal lens: \$3 3. audio input/output: \$5 4. MOQ: 5pcs 5. Sample price: plus \$5

	SC5J51A	5 Megapixel 25/30fps, H.265/H.264 Vandal Proof Smart Dome PoE IP Camera 5 Megapixel : 2592*1944@25/30fps, 5 Megapixel sensor OV5658 + Hi3516A SoC chip, DWDR, BLC, ROI, 3D DNR, Tampering alarm, 2.8-12mm CS lens, 2.8mm M12 lens, 24 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring. IK10, IP66.		PoE	2.8mm	20-30m	IP66	1. 2.8/ 3.6mm option 2. 3.3-10.5mm varifocal lens: \$15 3. audio input/output: \$5 4. MOQ: 5pcs 5. Sample price: plus \$5
	SC5J51B	5 Megapixel Sony Super Starlight 25/30fps, H.265/H.264 Vandal Proof Smart Dome PoE IP Camera 5 Megapixel : 2592*1944@25/30fps, Sony 1/1.8" super starlight 5 Megapixel sensor IMX178 + Hi3516A SoC chip, Full color: 0.001Lux@F1.2; DWDR, BLC, ROI, 3D DNR, Tampering alarm, 2.8-12mm CS lens, 2.8mm M12 lens, 24 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring. IK10, IP66.		PoE	2.8mm	20-30m	IP66	1. 2.8/ 3.6mm option 2. 3.3-10.5mm varifocal lens: \$15 3. audio input/output: \$5 4. audio, alarm, BNC, RS485 etc. full functions: \$12 5. TF card slot: \$5 6. MOQ: 5pcs 7. Sample price: plus \$10
Zoom Smart Starlight 	SC5J51BZ	5 Megapixel Sony Super Starlight 25/30fps, H.265/H.264 Vandal Proof Smart Dome PoE IP Camera 5 Megapixel : 2592*1944@25/30fps, Sony 1/1.8" super starlight 5 Megapixel sensor IMX178 + Hi3516A SoC chip, Full color: 0.001Lux@F1.2; DWDR, BLC, ROI, 3D DNR, Tampering alarm, 2.8-12mm CS lens, 2.8mm M12 lens, 24 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring. IK10, IP66.		PoE	3.6-11mm motorized	20-30m	IP66	1. TF card slot: \$5 2. MOQ: 5pcs
Smart Starlight 4K Zoom 	SC5J81AZ	8 Megapixel 4K 15fps Medium IR PoE Vandal Proof Dome IP Camera Sony Starlight + Digital Overlap-HDR 1/2.5" CMOS sensor IMX274+ Hisilicon High performance SOC chip Hi3516V200, support 8 Megapixel 4K (3840*2160) 15fps extra high definition, Color: 0.01Lux@F1.2; B/W: 0.001Lux@F1.2; HDR, BLC, ROI, Tampering alarm, 3.6mm fixed lens, 24 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IP66, IK10.		PoE	3.6-10mm motorized zoom	20-30m	IP66	1. TF card slot: \$5 2. MOQ: 5pcs
Smart Starlight 4K 	SC5J81	8 Megapixel 4K 25/30fps Medium IR PoE Vandal Proof Dome IP Camera Sony Starlight + Digital Overlap-HDR 1/2.5" CMOS sensor IMX274+ Hisilicon High performance SOC chip Hi3519, support 8 Megapixel 4K (3840*2160) realtime 25/30fps extra high definition, Color: 0.01Lux@F1.2; B/W: 0.001Lux@F1.2; HDR, BLC, ROI, Tampering alarm, 3.6mm fixed lens, 24 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IP66, IK10.		PoE	3.6mm	20-30m	IP66	1. TF card slot: \$5 2. MOQ: 5pcs

	SC5J81Z	8 Megapixel 4K 25/30fps Motorized Zoom Medium Starlight IR PoE Vandal Proof Smart Dome IP Camera Sony Starlight + Digital Overlap-HDR 1/2.5" CMOS sensor IMX274+ Hisilicon High performance SOC chip Hi3516AV200, support 8 Megapixel 4K (3840*2160) realtime 25/30fps extra high definiton, Color: 0.01Lux@F1.2; B/W:0.001Lux@F1.2; HDR,BLC,ROI,Tampering alarm, 2.8-12mm varifocal lens, 24 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IP66, IK10.		PoE	3.6-10mm motorized zoom	20-30m	IP66	1. TF card slot: \$5 2. MOQ: 5pcs
	SC5721-L14	2 Megapixel 1080P Fisheye Mini Vandal Proof Dome PoE IP Camera with Mic for Elevator/Lift 1920x1080@25fps, 2 Megapixel sensor SONY323 + Hi3516C SoC chip, 1.4mm M12 fisheye lens, 12 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE, built-in high quality noise reduction circuit & Microphone, No AC/DC adapter. P2P Mobile Monitoring. It is suitable for elevator/lift surveillance.		PoE	1.4mm	10-15m	X	MOQ: 10pcs
	SC5721-MIC	2 Megapixel 1080P Mini Vandal Proof Dome PoE IP Camera with Mic 1920x1080@25fps, 2 Megapixel sensor SONY323 + Hi3516C SoC chip, 2.8mm M12 lens, 12 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE, built-in high quality noise reduction circuit & Microphone , No AC/DC adapter. P2P Mobile Monitoring.		PoE	2.8mm	10-15m	X	MOQ: 10pcs
	SC5741-MIC	4 Megapixel 15fps H.265/H.264 Mini Vandal Proof Dome PoE IP Camera with Mic 4 Megapixel : 2592x1520@15fps, 3 Megapixel: 2048x1520@25fps, 4 Megapixel sensor OV4689 + Hi3516D SoC chip, 12 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE, built-in high quality noise reduction circuit & Microphone , No AC/DC adapter. P2P Mobile Monitoring.		PoE	2.8mm	10-15m	X	MOQ: 10pcs
	SC5U21	H.265/H.264 2 Megapixel Indoor Professional Dome IP Camera 1080P@25/30fps, Sony sensor, 1 channel audio MIC/LINE input, 1 channel audio LINE OUT output; 1ch CVBS analog video output; Reset input; RS485; TF card(Micro SD card) slot, support 128GB, 2ch alarm input / 1ch output, RS485, CVBS analog output, built-in DC 12V(DC9V-16V wide voltage) & AC24V, POE (802.3af). It is suitable for elevator/lift/ bus/vehicles surveillance.		PoE AC24V/DC12V	2.8mm	x	x	1.4mm fisheye lens support MOQ: 10pcs, sample: add 10USD
	SC5D21	2 Megapixel 1080P Sony Sensor IR Bullet IP Camera 1920x1080@25fps, Sony 2 Megapixel Low light sensor IMX323 + Hi3516C SoC chip, Color: 0.1Lux@F1.2; B/W:0.01Lux@F1.2; DWDR,BLC,ROI, 3D DNR, Tampering alarm, 4mm M12 lens, 2x array LED, IR 30m, built-in Smart function, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring. No bracket		PoE	4mm	30m	IP66	1.4/6/8mm lens: free 2. 2.8-12mm lens: \$3 3. TF card slot: \$5 4. audio input / output: \$5 5. MOQ: 10pcs 6. Sample price: \$50

	SC5D21W	2 Megapixel 1080P Sony WDR Sensor IR Bullet IP Camera H.265/H.264, 1920x1080@25fps, Sony 2 Megapixel WDR sensor IMX290 + Hi3516CV300 SoC chip, Color: 0.1Lux@F1.2; B/W:0.01Lux@F1.2; WDR:120db,BLC,ROI, 3D DNR, Tampering alarm, 4mm M12 lens, 2x array LED, IR 30m, built-in Smart function, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring. No bracket		PoE	4mm	30m	IP66	1.4/6/8mm lens: free 2. 2.8-12mm lens: \$3 3. TF card slot: \$5 4. audio input / output: \$5 5. MOQ: 10pcs 6. Sample price: \$75
	SC5D41A	4 Megapixel 15fps H.265/H.264 WDR IR Bullet IP Camera 4 Megapixel : 2592x1520@15fps, 3 Megapixel: 2048x1520@25fps, 4 Megapixel sensor OV4689 + Hi3516D SoC chip, WDR: 120dB,BLC,ROI, 3D DNR, Tampering alarm, 4mm M12 lens, 2x array LED, IR 30m, built-in Smart function, ONVIF; DC12V,built- in PoE, No AC/DC adapter. P2P Mobile Monitoring. No bracket		PoE	4mm	30m	IP66	1.4/6/8mm lens: free 2. 2.8-12mm lens: \$3 3. TF card slot: \$5 4. audio input / output: \$5 5. MOQ: 10pcs 6. Sample price: \$58
	SC5D51A	5 Megapixel 25/30fps H.265/H.264 IR Bullet IP Camera 5 Megapixel : 2592*1944@25/30fps,5 Megapixel sensor OV5658 + Hi3516A SoC chip, DWDR,BLC,ROI, 3D DNR, Tampering alarm, 4mm M12 lens, 2x array LED, IR 30m, built-in Smart function, 1ch audio input/output, 1ch alarm input/ output,ONVIF; DC12V,built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. No bracket		PoE	4mm	30m	IP66	1.4/6/8mm lens: free 2. 3.5-10mm lens: \$7 3. TF card slot: \$5 4. Sample price: plus \$5
	SC5K21A	2 Megapixel 1080P Sony Low Light Sensor IR Bullet IP Camera 1920x1080@25fps, Sony IMX323 2 Megapixel sensor + Hi3516C SoC chip, Color: 0.1Lux@F1.2; B/W:0.01Lux@F1.2; DWDR,BLC,ROI, 8mm CS lens, 4 array LED light, IR distance 50m, built-in Smart function, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring.		PoE	8mm	50m	IP66	1.6/8/12mm lens: free
	SC5K21B	2 Megapixel 1080P Sony Low Light Sensor IR Bullet Smart IP Camera 1920x1080@25fps, Sony IMX323 2 Megapixel sensor + Hi3516C SoC chip, Color: 0.01Lux@F1.2; B/W:0.001Lux@F1.2; DWDR,BLC,ROI, 8mm CS lens, 4 array LED light, IR distance 50m, built-in Smart function, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring. Support Audio Detection, Line Crossing Detection, Intrusion Detection, Unattended baggage; Color,brightness,Defocus Exception Detections.		PoE	8mm	50m	IP66	1.6/8/12mm lens: free
	SC5K21BZ	2 Megapixel 1080P Sony Low Light Zoom Sensor IR Bullet IP Camera H.265/H.264, 1920x1080@25fps, Sony IMX323 2 Megapixel sensor + Hi3516CV300 SoC chip, Color: 0.01Lux@F1.2; B/W:0.001Lux@F1.2; DWDR,BLC,ROI, 2.8-12mm motorized zoom and auto focus lens, 4 array LED light, IR distance 50m, built-in Smart function, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring.		PoE	2.8-12mm motorized zoom & autofocus	50m	IP66	1. 6-22mm motorized zoom & auto focus lens: \$25

	SC5K21S	H.265/H.264 2 Megapixel 1080P Sony StarLight Sensor IR Bullet IP Camera 1920x1080@25fps, Sony IMX291 2 Megapixel starlight sensor + Hi3516D SoC chip, Full color: 0.001Lux@F1.2 ; DWDR,BLC,ROI, 8mm CS lens, 4 array LED light, IR distance 50m, built-in Smart function, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring.		PoE	8mm	50m	IP66	1.6/8/12mm lens: free 2. 2.8-12mm motorized zoom and auto focus lens: \$15
	SC5K21WZ	H.265/H.264 2 Megapixel 1080P 60fps Sony StarLight WDR Motorized Zoom Sensor IR Bullet IP Camera 1920x1080@50/60fps, Sony IMX290 2 Megapixel starlight WDR sensor + Hi3516V300 SoC chip, Full color: 0.001Lux@F1.2; WDR>120dB, BLC,ROI, 2.7-13.5mm motorized zoom lens, 4 array LED light, IR distance 50m, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. Support Audio Detection, Line Crossing Detection, Intrusion Detection, Unattended baggage; Color,brightness,Defocus Exception Detections. SD card slot, audio/alarm I/O, Reset cable.		PoE	2.7-13.5mm motorized zoom	50m	IP66	6-22mm motorized zoom & auto focus lens: \$25
	SC5K41A	4 Megapixel 15fps H.265/H.264 IR Bullet PoE IP Camera 4 Megapixel : 2592x1520@15fps, 3 Megapixel: 2048x1520@25fps, 4 Megapixel sensor OV4689 + Hi3516D SoC chip, 8mm CS lens, 4 array LED light, IR distance 50m, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring.		PoE	8mm	50m	IP66	1.6/8/12mm lens: free 2. 2.8-12mm motorized zoom and auto focus lens: \$15
	SC5K41AZ	4 Megapixel 15fps H.265/H.264 IR Bullet PoE IP Camera 4 Megapixel : 2592x1520@15fps, 3 Megapixel: 2048x1520@25fps, 4 Megapixel sensor OV4689 + Hi3516D SoC chip, 2.8-12mm motorized zoom and auto focus lens, 4 array LED light, IR distance 50m, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring.		PoE	2.8-12mm motorized zoom & autofocus	50m	IP66	1. 6-22mm motorized zoom & auto focus lens: \$25
	SC5K31B	3 Megapixel Sony Starlight 25/30fps H.265/H.264 IR Bullet IP Camera 2048x1520@25fps, 3 Megapixel starlight sensor Sony IMX124+ Hi3516D SoC chip, Full color: 0.001Lux@F1.2 ; DWDR,BLC,ROI, 8mm lens, 4 array LED light, IR distance 50m, built-in Smart function, ONVIF; DC12V,built-in PoE,, No AC/DC adapter. P2P Mobile Monitoring.		PoE	8mm	50m	IP66	1.6/8/12mm lens: free 2. 2.8-12mm motorized zoom and auto focus lens: \$15
	SC5K51A	5 Megapixel 25/30fps H.265/H.264 IR Bullet IP Camera 5 Megapixel : 2592*1944@25/30fps,5 Megapixel sensor OV5658 + Hi3516A SoC chip, DWDR,BLC,ROI, 3D DNR, Tampering alarm, 8mm CS lens, 4 array LED light, IR distance 50m, built-in Smart function, 1ch audio input/output, 1ch alarm input/output,ONVIF; DC12V,built-in PoE, No AC/DC adapter. P2P Mobile Monitoring.		PoE	8mm	50m	IP66	1.6/8/12mm lens: free 2. 2.8-12mm:\$3

	SC5K51AZ	5 Megapixel 25/30fps H.265/H.264 Motorized Zoom IR Bullet IP Camera 5 Megapixel : 2592*1944@25/30fps, 5 Megapixel sensor OV5658 + Hi3516A SoC chip, DWDR, BLC, ROI, 3D DNR, Tampering alarm, 2.8-12mm motorized zoom & auto focus varifocal lens, 4 array LED light, IR distance 50m, built-in Smart function, 1ch audio input/output, 1ch alarm input/output, ONVIF; DC12V, built-in PoE, No AC/DC adapter. P2P Mobile Monitoring.		PoE	2.8-12mm motorized zoom & autofocus	50m	IP66	1. 6-22mm motorized zoom & auto focus lens: \$25
	SC5K51B	5 Megapixel 25fps H.265/H.264 Sony Starlight IR Bullet IP Camera 5 Megapixel : 2592*1944@25/30fps, Sony 1/1.8" super starlight 5 Megapixel sensor IMX178 + Hi3516A SoC chip, Full color: 0.001Lux@F1.2; 8mm CS lens, 4 array LED light, IR distance 50m, built-in Smart function, ONVIF; DC12V, built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. Alarm, audio input/output, RS485, reset cable.		PoE	8mm	50m	IP66	1.6/8/12mm lens: free
	SC5K81Z	8 Megapixel 4K 25/30fps Medium IR Bullet IP Camera Sony Starlight + Digital Overlap-HDR 1/2.5" CMOS sensor IMX274+ Hisilicon High performance SOC chip Hi3519, support 8 Megapixel 4K (3840*2160) realtime 25/30fps extra high definition, Color: 0.01Lux@F1.2; B/W: 0.001Lux@F1.2; HDR, BLC, ROI, Tampering alarm, 2.8-12mm motorized zoom and auto focus lens, 4 array array LED light, IR distance 50m, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring.	DC12V & PoE		2.8-12mm motorized	50m	IP66	1. audio input/output: \$5 2. audio, alarm, BNC, RS485 etc. full functions: \$12 3. TF card slot: \$5 4. 3.6-11mm 4K lens: \$25
	SC5T81	8 Megapixel 4K 25/30fps Medium IR Bullet IP Camera Sony Starlight + Digital Overlap-HDR 1/2.5" CMOS sensor IMX274+ Hisilicon High performance SOC chip Hi3519, support 8 Megapixel 4K (3840*2160) realtime 25/30fps extra high definition, Color: 0.01Lux@F1.2; B/W: 0.001Lux@F1.2; HDR, BLC, ROI, Tampering alarm, 2.8-12mm varifocal CS lens, 30 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. high end metal body, IP66	DC12V & PoE		2.8-12mm	30m	IP66	1. audio input/output: \$5 2. audio, alarm, BNC, RS485 etc. full functions: \$12 3. TF card slot: \$5 4. 1.2/8/3.6/4/5/6mm lens is optional 5. 3.6-11mm 4K lens: \$25 6. MOQ: 20pcs
	SC5A21	2 Megapixel 1080P Sony Low Light Sensor Medium IR Bullet IP Camera 1920x1080@25fps, Sony IMX323 2 Megapixel sensor + Hi3516C SoC chip, Color: 0.1Lux@F1.2; B/W: 0.01Lux@F1.2; DWDR, BLC, ROI, 6mm lens, 2 pcs array LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring. No bracket.		PoE	6mm	30m	IP66	1.4/6/8mm lens: free 2. 2.8-12mm lens: \$3 3. TF card slot: \$5 4. audio input / output: \$5 5. MOQ: 10pcs 6. Sample price: \$60
	SC5A41A	4 Megapixel 15fps H.265/H.264 Medium IR Bullet IP Camera 4 Megapixel : 2592x1520@15fps, 3 Megapixel : 2048x1520@25fps, 4 Megapixel sensor OV4689 + Hi3516D SoC chip, DWDR, BLC, ROI, 6mm lens, 2 pcs array LED light, built-in Smart function, ONVIF; DC12V, built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. No bracket.		PoE	6mm	30m	IP66	1.4/6/8mm lens: free 2. 2.8-12mm lens: \$3 3. TF card slot: \$5 4. audio input / output: \$5 5. MOQ: 50pcs 6. Sample price: plus \$5

	SC5A51A	5 Megapixel 25/30fps H.265/H.264 IR Bullet IP Camera 5 Megapixel : 2592*1944@25/30fps, 5 Megapixel sensor OV5658 + Hi3516A SoC chip, DWDR,BLC,ROI, 3D DNR, Tampering alarm, 4mm M12 lens, 2x array LED, IR 30m, built-in Smart function, 1ch audio input/output, 1ch alarm input/ output, ONVIF; DC12V, built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. No bracket		PoE	6mm	30m	IP66	1.4/6/8mm lens: free 2. 3.5-10mm lens: \$7 3. TF card slot: \$5 4. Sample price: plus \$5
	SC5421B	2 Megapixel 1080P IR Bullet PoE IP Camera 1920x1080@25fps, Sony IMX323 2 Megapixel sensor + Hi3516C SoC chip, Color: 0.1Lux@F1.2; B/W:0.01Lux@F1.2; DWDR,BLC,ROI, 6mm lens, 36 pcs LED light, IR distance 30m, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter, IP66 waterproof, P2P Mobile Monitoring.		PoE	6mm	30m	IP66	1.4/6/8/12mm lens: free 2. 2.8-12mm varifocal lens: 4\$ 3. MOQ: 10pcs 4. audio, alarm, BNC, RS485 etc. full functions: \$12 5. TF card slot: \$5
	SC5421S-T12	H.265/H.264 2 Megapixel 1080P Sony StarLight Sensor IR Bullet IP Camera 1920x1080@25fps, Sony IMX291 2 Megapixel starlight sensor + Hi3516D SoC chip, Full color: 0.001Lux@F1.2; DWDR,BLC,ROI, 2.8-12mm varifocal lens, 36 pcs LED light, IR distance 30m, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter, IP66 waterproof, P2P Mobile Monitoring.		PoE	2.8-12mm	30m	IP66	1.4/6/8/12mm lens: free 2. MOQ: 10pcs 3. audio, alarm, BNC, RS485 etc. full functions: \$12 4. TF card slot: \$5
	SC5441A	4 Megapixel 15fps H.265/H.264 IR Bullet PoE IP Camera 4 Megapixel : 2592x1520@15fps, 3 Megapixel sensor OV4689 + Hi3516D SoC chip, 6mm lens, 36 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring.		PoE	6mm	30m	IP66	1.4/6/8/12mm lens: free 2. 2.8-12mm varifocal lens: 4\$ 3. MOQ: 10pcs
	SC5431B	3 Megapixel Sony Starlight 25/30fps H.265/H.264 IR Bullet IP Camera 2048x1520@25fps, 3 Megapixel starlight sensor Sony IMX124+ Hi3516D SoC chip, Full color: 0.001Lux@F1.2; DWDR,BLC,ROI, 6mm lens, 36 pcs LED light, built-in Smart function, ONVIF; DC12V, built-in PoE, No AC/DC adapter. P2P Mobile Monitoring.		PoE	6mm	30m	IP66	1.4/6/8/12mm lens: free 2. 2.8-12mm varifocal lens: 4\$ 3. 2.8-12mm motorized lens: \$22 4. MOQ: 10pcs
	SC5441B	4 Megapixel 25fps H.265/H.264 IR Bullet PoE IP Camera 4 Megapixel : 2592x1520@25fps, 3 Megapixel sensor OV4689 + Hi3516A SoC chip, 6mm lens, 36 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring.		PoE	6mm	30m	IP66	1.4/6/8/12mm lens: free 2. 3.5-10.5mm varifocal lens: 7\$ 3. MOQ: 10pcs 4. audio, alarm, BNC, RS485 etc. full functions: \$12 5. TF card slot: \$5
	SC5451A	5 Megapixel 25/30fps H.265/H.264 IR Bullet IP Camera 5 Megapixel : 2592*1944@25/30fps, 5 Megapixel sensor OV5658 + Hi3516A SoC chip, DWDR,BLC,ROI, 3D DNR, Tampering alarm, 6mm CS lens, 36pcs IR LED light, IR 30m, built-in Smart function, ONVIF; DC12V, built-in PoE, No AC/DC adapter. P2P Mobile Monitoring.		PoE	6mm	30m	IP66	1.4/6/8/12mm lens: free 2. 3.5-10mm varifocal lens: 7\$ 3. audio, alarm, BNC, RS485 etc. full functions: \$12 4. TF card slot: \$5

	SC5451B	5 Megapixel 25fps H.265/H.264 Sony Starlight IR Bullet IP Camera 2592x1520@25fps, Sony 1/1.8" 5 Megapixel Starlight sensor IMX178+ Hi3516A SoC chip, 6mm lens, 36 pcs LED light, built-in Smart function, ONVIF; DC12V, built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. Alarm, audio input/output, RS485, reset cable.	PoE	6mm	30m	IP66	1.4/6/8/12mm lens: free 2. 3.5-10mm varifocal lens: \$7 3. audio, alarm, BNC, RS485 etc. full functions: \$12 4. TF card slot: \$5
	SC5T21B	2 Megapixel 1080P Sony Low Light Sensor IR Bullet IP Camera 1920x1080@25fps, Sony IMX323 2 Megapixel sensor + Hi3516C SoC chip, Color: 0.1Lux@F1.2; B/W:0.01Lux@F1.2; DWDR,BLC,ROI, 2.8-12mm varifocal CS lens, 30 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. high end metal body, IP66	DC12V & PoE	2.8-12mm	30m	IP66	1. audio input/output: \$5 2. audio, alarm, BNC, RS485 etc. full functions: \$12 3. TF card slot: \$5 4. MOQ: 20pcs
	SC5T21BZ	2 Megapixel 1080P Sony Low Light Sensor IR Bullet IP Camera 1920x1080@25fps, Sony IMX323 2 Megapixel sensor + Hi3516C SoC chip, Color: 0.1Lux@F1.2; B/W:0.01Lux@F1.2; DWDR,BLC,ROI, 2.8-12mm motorized lens, 30 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. high end metal body, IP66	DC12V & PoE	2.8-12mm motorized	30m	IP66	1. audio input/output: \$5 2. audio, alarm, BNC, RS485 etc. full functions: \$12 3. TF card slot: \$5 4. MOQ: 10pcs
	SC5521	2 Megapixel 1080P Sony Low Light Sensor IR Bullet IP Camera 1920x1080@25fps, Sony IMX323 2 Megapixel sensor + Hi3516C SoC chip, Color: 0.1Lux@F1.2; B/W:0.01Lux@F1.2; DWDR,BLC,ROI, 12mm CS lens, 6 array LED light, IR distance 80-100m, built-in Smart function, sunshield, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring. No bracket.	DC12V & PoE	12mm	80-100m	IP66	1. 6/8/12mm lens is optional audio input/output: \$5 2. audio, alarm, BNC, RS485 etc. full functions: \$12 3. TF card slot: \$5 4. 2.8-12mm motorized lens:\$15
	SC5521Z	2 Megapixel 1080P Sony Low Light Sensor IR Bullet IP Camera 1920x1080@25fps, Sony IMX323 2 Megapixel sensor + Hi3516C SoC chip, Color: 0.1Lux@F1.2; B/W:0.01Lux@F1.2; DWDR,BLC,ROI, 12mm CS lens, 6 array LED light, IR distance 80-100m, built-in Smart function, sunshield, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring. No bracket.	DC12V & PoE	12mm	80-100m	IP66	1. 4/6/8/12mm lens is optional audio input/output: \$5 2. audio, alarm, BNC, RS485 etc. full functions: \$12 3. TF card slot: \$5 4. 2.8-12mm motorized lens:\$30
	SC5R21	2 Megapixel 1080P Sony Low Light Sensor IR Bullet IP Camera 1920x1080@25fps, Sony IMX323 2 Megapixel sensor + Hi3516C SoC chip, Color: 0.1Lux@F1.2; B/W:0.01Lux@F1.2; DWDR,BLC,ROI, 12mm CS lens, 6 array LED light, IR distance 80-100m, built-in Smart function, sunshield, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring. No bracket.	DC12V & PoE	12mm	80-100m	IP66	1. 6/8/12mm lens is optional audio input/output: \$5 2. audio, alarm, BNC, RS485 etc. full functions: \$12 3. TF card slot: \$5 4. 2.8-12mm motorized lens:\$15 MOQ: 10pcs, sample: add 10USD
	SC5R21Z	2 Megapixel 1080P Sony Low Light Sensor IR Bullet IP Camera 1920x1080@25fps, Sony IMX323 2 Megapixel sensor + Hi3516C SoC chip, Color: 0.1Lux@F1.2; B/W:0.01Lux@F1.2; DWDR,BLC,ROI, 12mm CS lens, 6 array LED light, IR distance 80-100m, built-in Smart function, sunshield, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring. No bracket.	DC12V & PoE	12mm	80-100m	IP66	1. 4/6/8/12mm lens is optional audio input/output: \$5 2. audio, alarm, BNC, RS485 etc. full functions: \$12 3. TF card slot: \$5 4. 2.8-12mm motorized lens:\$25 5. 6-22mm motorized lens:\$30 MOQ: 10pcs, sample: add 10USD

	SC5021	2 Megapixel 1080P IR Bullet PoE IP Camera 1920x1080@25fps, Sony IMX323 2 Megapixel sensor + Hi3516C SoC chip, 2.8-12mm CS lens, 12 pcs LED light, IR distance 30m, built-in Smart function, ONVIF; DC12V, Built-in PoE , No AC/DC adapter, IP66 waterproof, P2P Mobile Monitoring.		PoE	2.8-12mm	20-30m	IP66	MOQ: 10pcs, sample: add 10USD
	SC5041A	4 Megapixel 15fps H.265/H.264 IR Bullet PoE IP Camera 4 Megapixel : 2592x1520@15fps, 3 Megapixel: 2048x1520@25fps, 4 Megapixel sensor OV4689 + Hi3516D SoC chip, 2.8-12mm lens, 12 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring.		PoE	2.8-12mm	20-30m	IP66	MOQ: 10pcs, sample: add 10USD
	SC5051A	5 Megapixel 25/30fps H.265/H.264 IR Bullet PoE IP Camera 5 Megapixel : 2592*1944@25/30fps, 5 Megapixel sensor OV5658 + Hi3516A SoC chip, DWDR,BLC,ROI, 3D DNR, Tampering alarm, 2.8-12mm CS lens, 4 array LED light, IR distance 50m, built-in Smart function, 1ch audio input/output, 1ch alarm input/output,ONVIF; DC12V,built-in PoE, No AC/DC adapter. P2P Mobile Monitoring.		PoE	2.8-12mm	20-30m	IP66	MOQ: 10pcs, sample: add 10USD
	SC5581-I5	8 Megapixel 4K 25/30fps Big IR Bullet IP Camera Sony Starlight + Digital Overlap-HDR 1/2.5" CMOS sensor IMX274+ Hisilicon High performance SOC chip Hi3519, support 8 Megapixel 4K (3840*2160) realtime 25/30fps extra high definiton, Color: 0.01Lux@F1.2; B/W:0.001Lux@F1.2; HDR,BLC,ROI,Tampering alarm, 8mm fixed CS lens, 4 array array LED light, IR distance up to 50m, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. No bracket.	DC12V & PoE		8mm	50m	IP66	1. 6/8/12mm lens is optional audio input/output: \$5 2. audio, alarm, BNC, RS485 etc. full functions: \$12 3. TF card slot: \$5 4. 2.8-12mm motorized lens:\$30 5. 3.6-11mm 4K lens: \$25 6. 4-40mm 4K lens: \$150
	SC5581-I8	8 Megapixel 4K 25/30fps Big IR Bullet IP Camera Sony Starlight + Digital Overlap-HDR 1/2.5" CMOS sensor IMX274+ Hisilicon High performance SOC chip Hi3519, support 8 Megapixel 4K (3840*2160) realtime 25/30fps extra high definiton, Color: 0.01Lux@F1.2; B/W:0.001Lux@F1.2; HDR,BLC,ROI,Tampering alarm, 12mm fixed CS lens, 6 array array LED light, IR distance 80-100m, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. No bracket.	DC12V & PoE		12mm	80-100m	IP66	1. 8/12/25mm lens is optional audio input/output: \$5 2. audio, alarm, BNC, RS485 etc. full functions: \$12 3. TF card slot: \$5 4. 2.8-12mm motorized lens:\$30 5. 3.6-11mm 4K lens: \$25 6. 4-40mm 4K lens: \$150

	SC5821	2 Megapixel 1080P Sony Sensor Small IR Bullet IP Camera 1920x1080@25fps, Sony 2 Megapixel Low light sensor IMX323 + Hi3516C SoC chip, Color: 0.1Lux@F1.2; B/W:0.01Lux@F1.2; DWDR,BLC,ROI, 3D DNR, Tampering alarm, 3.6mm M12 lens, 24 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring. Built-in bracket		PoE	3.6mm	10-15m	IP66	1.MOQ: 50pcs 2. Sample price: plus \$5
	SC5841A	4 Megapixel 15fps H.265/H.264 WDR Small IR Bullet IP Camera 4 Megapixel : 2592x1520@15fps, 3 Megapixel: 2048x1520@25fps, 4 Megapixel sensor OV4689 + Hi3516D SoC chip, WDR 120dB,BLC,ROI, 3D DNR, Tampering alarm, 3.6mm M12 lens, 24 pcs LED light, built-in Smart function, ONVIF; DC12V,built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. Built-in bracket		PoE	3.6mm	10-15m	IP66	1.MOQ: 50pcs 2. Sample price: plus \$5
	SC5921	2 Megapixel 1080P Indoor IR Plastic Dome IP Camera 1920x1080@25fps,2 Megapixel sensor Sony IMX323 + Hi3516C SoC chip, DWDR,BLC,ROI, 3D DNR, Tampering alarm, 3.6mm M12 lens, 1 pcs Array LED light, built-in Smart function, ONVIF; DC12V, built-in PoE , No AC/DC adapter. P2P Mobile Monitoring.		DC12V	3.6mm	10-15m	X	1.PoE: \$4 2.MOQ: 50pcs 3.Sample price: plus \$5 4.2.8mm lens:1
	SC5941A	4 Megapixel 15fps H.265/H.264 WDR Small Indoor IR PoE Plastic Dome IP Camera 4 Megapixel : 2592x1520@15fps, 3 Megapixel: 2048x1520@25fps, sensor OV4689 + Hi3516D SoC chip, WDR 120dB,BLC,ROI, 3D DNR, Tampering alarm, 3.6mm M12 lens, 1 pcs Array LED light, built-in Smart function, ONVIF; DC12V,built-in PoE, No AC/DC adapter. P2P Mobile Monitoring.		PoE	3.6mm	10-15m	X	1.PoE: \$4 2.MOQ: 50pcs 3.Sample price: plus \$5 4.2.8mm lens:1
	SC5E21Z	2 Megapixel 1080P Sony Sensor Big Vandal Proof Dome PoE IP Camera 1920x1080@25fps,Sony 2 Megapixel Low light sensor IMX323 + Hi3516C SoC chip, Color: 0.1Lux@F1.2; B/W:0.01Lux@F1.2; DWDR,BLC,ROI, 3D DNR, Tampering alarm, 2.8-12mm Motorized lens, 30 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE, built-in TF card slot (max 128GB) No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IP66 & IK10.		PoE	2.8-12mm motorized	30m	IP66	1.MOQ: 20pcs 2.Sample price: plus \$20
	SC5E21BZ	2 Megapixel 1080P Sony Starlight Sensor Big Vandal Proof Dome PoE IP Camera 1920x1080@25fps, Sony IMX291 2 Megapixel starlight sensor + Hi3516D SoC chip, Full color: 0.001Lux@F1.2; DWDR,BLC,ROI, 3D DNR, Tampering alarm, 2.8-12mm Motorized lens, 30 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IP66 & IK10.		PoE	2.8-12mm motorized	30m	IP66	1.MOQ: 20pcs 2.Sample price: plus \$20 3.built-in TF card slot (max 128GB)

	SC5E21W	2 Megapixel 1080P Sony WDR Sensor Big Vandal Proof Dome PoE IP Camera 1920x1080@25fps, Sony 2 Megapixel Super WDR sensor IMX290 + Hi3516D SoC chip, Color: 0.1Lux@F1.2; B/W: 0.01Lux@F1.2; WDR: 130dB , BLC, ROI, 3D DNR, Tampering alarm, 2.8-12mm CS varifocal lens, 30 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IP66 & IK10.		PoE	2.8-12mm	30m	IP66	1.MOQ: 20pcs 2.Sample price: plus \$20
	SC5E21P	2 Megapixel 1080P@50fps Sony Starlight Sensor Big Vandal Proof Dome PoE IP Camera 1920x1080@50fps, Sony IMX291 2 Megapixel starlight sensor + Hi3516A SoC chip, Full color: 0.001Lux@F1.2; DWDR, BLC, ROI, 3D DNR, Tampering alarm, 2.8-12mm Motorized lens, 30 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IP66 & IK10.		PoE	2.8-12mm	30m	IP66	1.MOQ: 20pcs 2.Sample price: plus \$20
	SC5E31B	3 Megapixel Sony Starlight Sensor Big Vandal Proof Dome PoE IP Camera 2048*1536@25fps, Sony 3 Megapixel Low light sensor IMX124+ Hi3516D SoC chip, Full Color: 0.001Lux@F1.2 ; DWDR, BLC, ROI, 3D DNR, Tampering alarm, 2.8-12mm CS varifocal lens, 30 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome,		PoE	2.8-12mm	30m	IP66	1.MOQ: 20pcs 2.Sample price: plus \$20
	SC5E41AZ	4 Megapixel 15fps, H.265/H.264 Vandal Proof Dome PoE IP Camera 4 Megapixel : 2592x1520@15fps, 3 Megapixel: 2048x1520@25fps, 4 Megapixel sensor OV4689 + Hi3516D SoC chip, 2.8-12mm motorized zoom & auto focus lens, 30 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IP66, IK10.		PoE	2.8-12mm motorized	30m	IP66	4MP@25fps: plus \$10
	SC5E51AZ	5 Megapixel 25/30fps, H.265/H.264 Vandal Proof Big Dome PoE IP Camera 5 Megapixel : 2592*1944@25/30fps, 5 Megapixel sensor OV5658 + Hi3516A SoC chip, DWDR, BLC, ROI, 3D DNR, Tampering alarm, 2.8-12mm motorized zoom & auto focus lens, 30 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring.		PoE	2.8-12mm motorized	30m	IP66	1.MOQ: 20pcs 2.Sample price: plus \$20
	SC5E51BZ	5 Megapixel 25/30fps, H.265/H.264 SONY Starlight Vandal Proof Big Dome PoE IP Camera 2592x1520@25fps, Sony 1/1.8" 5 Megapixel Starlight sensor IMX178+ Hi3516A SoC chip, DWDR, BLC, ROI, 3D DNR, Tampering alarm, 3.6-11mm motorized zoom & auto focus lens, 30 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring.		PoE	3.6-11mm motorized	30m	IP66	1.MOQ: 20pcs 2.Sample price: plus \$20

	SC5E81Z	8 Megapixel 4K 25/30fps Big IR PoE Vandal Proof Dome IP Camera Sony Starlight + Digital Overlap-HDR 1/2.5" CMOS sensor IMX274+ Hisilicon High performance SOC chip Hi3519, support 8 Megapixel 4K (3840*2160) realtime 25/30fps extra high definiton, Color: 0.01Lux@F1.2; B/W:0.001Lux@F1.2; HDR,BLC,ROI,Tampering alarm, 2.8-12mm motorized lens, 30 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IP66, IK10.	DC12V & PoE	3.6-11mm motorized	30m	IP66	1. audio input/output: \$5 2. audio, alarm, BNC, RS485 etc. full functions: \$12 3. TF card slot: \$5 4. MOQ: 20pcs
	SC5G21	2 Megapixel 1080P Sony Sensor IR Metal Dome PoE IP Camera 1920x1080@25fps, Sony IMX323 2 Megapixel sensor + Hi3516C SoC chip, Color: 0.01Lux@F1.2, B/W: 0.001Lux@F1.2; DWDR,BLC,ROI, 3D DNR, Tampering alarm, 2.8-12mm varifocal lens,36 pcs LED light, IR distance 30-50m, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. High end metal housing.	PoE	2.8-12mm	30m	IP66	1. 2.8/ 4/6mm option 2.MOQ: 20pcs 3.Sample price: plus \$10
	SC5G41A	4 Megapixel 15fps, H.265/H.264 IR Metal Dome PoE IP Camera 4 Megapixel : 2592x1520@15fps, 3 Megapixel: 2048x1520@25fps, 4 Megapixel sensor OV4689 + Hi3516D SoC chip, 2.8-12mm varifocal lens, 36 pcs LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring.	PoE	2.8-12mm	30m	IP66	1. 2.8/ 4/6mm option 2.MOQ: 20pcs 3.Sample price: plus \$10
	SC5H21-L37	2 Megapixel 1080P 3.7mm Lens PoE Spy Pinhole IP Camera, 1/2.8" Sony 2 Megapixel Low light sensor, Built-in PoE, support audio in / out, alarm in / out, SD card slot. ONVIF support. 3.7mm fixed lens. For ATM or vehicle surveillance.	PoE	3.7mm	x	x	
	SC5H11-L37	1.0 Megapixel 720P 3.7mm Lens PoE Spy Pinhole IP Camera, 1/3" Sony 1. 0 Megapixel Low light sensor, Built-in PoE, support audio in / out, alarm in / out, SD card slot. ONVIF support. 3.7mm fixed lens. For ATM or vehicle surveillance.	PoE	3.7mm	x	x	
	SC5H21A-L37	2 Megapixel 1080P 3.7mm Lens PoE Spy Pinhole IP Camera, 1/2.8" Sony 2 Megapixel Low light sensor, support audio in / out, alarm in / out, SD card slot. ONVIF support. 3.7mm fixed lens. DC12V, NO PoE. For ATM or vehicle surveillance.	PoE	3.7mm	x	x	
	SC5H21A-L37-WDR	2 Megapixel 1080P WDR 3.7mm Lens PoE Spy Pinhole IP Camera, 1/2.8" Optical WDR 2 Megapixel Low light sensor, 120dB optical WDR. support audio in / out, alarm in / out, SD card slot, RS485. ONVIF support. 3.7mm fixed lens. DC12V, NO PoE. For ATM or vehicle surveillance.	PoE	3.7mm	x	x	

	SC5221D	H.265/H.264 2 Megapixel@25fps Starlight WDR Indoor IP Camera 1/2.8" Sony 2 Megapixel Progressive Scan IMX290+ Hi3516D, illumination: 0.005Lux, IR CUT, varifocal lens 2.8 ~ 12mm, no IR light, 140dB TWDR, SD card slot 128GB, alarm input / output, RS485, built-in Microphone, audio input and output, DC 12V & AC24V, POE		PoE	2.8-12mm	x	x	
	SC5221AZ	H.265/H.264 2 Megapixel 50/60fps Starlight WDR Indoor IP Camera 1/2.8" Sony 2 Megapixel Progressive Scan IMX290+ Hi3516A, 1080P 50/60fps,illumination: 0.005Lux, IR CUT, motorized zoom lens 2.8 ~ 12mm,140dB TWDR, SD card slot 128GB, alarm input / output, RS485, built-in Microphone, audio input and output, DC 12V & AC24V, POE		PoE	2.8-12mm motorized zoom & autofocus	x	x	
	SC5221AZR	H.265/H.264 2 Megapixel 50/60fps Starlight WDR Indoor IP Camera 1/2.8" Sony 2 Megapixel Progressive Scan IMX290+ Hi3516A, 1080P 50/60fps,illumination: 0.005Lux, IR CUT, varifocal lens 2.8 ~ 12mm, IR light 15-30m, 140dB TWDR, SD card slot 128GB, alarm input / output, RS485, built-in Microphone, audio input and output, DC 12V & AC24V, POE		PoE	2.8-12mm motorized zoom & autofocus	15-30m	x	
	SC5241ZR	H.265/H.264 4 Megapixel @ 25fps WDR IR Indoor Dome IP Camera 1/3 " 4 Megapixel Progressive Scan CMOS OV4689+Hi3516D, illumination: 0Lux, IR CUT, motorized lens 2.8 ~ 12mm, One Push auto focus, 110dB TWDR, SD card slot 128GB, alarm input, single alarm output, RS485, built-in microphone, audio input and output, DC 12V & AC24V, POE		PoE	2.8-12mm motorized zoom & autofocus	15-30m	x	
	SC5251Z	H.265/H.264 5 Megapixel @25fps Starlight IR Indoor IP Camera 1 / 1.8" Progressive Scan CMOS Sony IMX178, 5 megapixel 25/30fps, 1080P@50/60fps,illumination 0.001lux, IR CUT, motorized lens 3.6 ~ 10mm, One Push auto focus, 120dB TWDR, SD card slot 128GB, alarm input / output, RS485, built-in Microphone, audio input and output, DC 12V & AC24V, POE		PoE	3.6-10mm motorized zoom & autofocus	x	IP66	
	SC5021B-4G	H.265/H.264 2 Megapixel 1080P Sony Low Light Sensor Motorized Zoom IR Bullet 4G Wireless IP Camera H.265/H.264, 1920x1080@25fps, Sony IMX323 2 Megapixel sensor + Hi3516CV300 SoC chip, Color: 0.01Lux@F1.2; B/W:0.001Lux@F1.2; DWDR,BLC,ROI, 2.8-12mm motorized zoom and auto focus lens, 4 array LED light, IR distance 50m, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. Support LTE 4G Support Audio Detection, Line Crossing Detection, Intrusion Detection, Unattended baggage; Color,brightness,Defocus Exception Detections.		PoE	2.8-12mm motorized zoom & autofocus	50m	IP66	MOQ: 10pcs, sample: add 20USD

	SC5C21BZ	H.264/H.265 2 Megapixel 25/30fps Low-light Outdoor Bullet Motorized Zoom HD IP Camera 1920x1080@25fps, Sony IMX323 2 Megapixel sensor + Hi3516CV300 SoC chip, Color: 0.01Lux@F1.2; B/W:0.001Lux@F1.2; DWDR,BLC,ROI,80-100mm IR distance (or white light LED), 6-22mm motorized zoom lens. No bracket. No AC/DC adapter. Support Audio Detection, Line Crossing Detection, Intrusion Detection, Unattended baggage; Color,brightness,Defocus Exception Detections.		PoE	6-22mm motorized zoom	80-100m	IP66	1. 6-50mm motorized zoom lens: \$30 7. MOQ: 5pcs, sample: add \$20
	SC5C21P	2 Megapixel 50/60fps WDR HLC Outdoor Bullet HD IP Camera for Traffic 1/3" 2.1 Megapixels Panasonic MN34229 CMOS sensor,Max 50/60fps@1080P, H.265/H.264 & MJPEG encoding, Optical WDR, HLC, Low illumination: 0.05Lux/F1.4(color),0.01Lux/F1.4 (B/W). 80-100mm IR distance (or white light LED), 12mm fixed lens. No bracket. No AC/DC adapter.		PoE	12mm	80-100m	IP66	1. 4/6/8/12mm lens: free 2. 2.8-12mm varifocal lens: \$9 3. 6-22mm varifocal lens: \$12 4. 2.8-12mm motorized lens: \$22 5. 6-22mm motorized lens:\$25 6. 5-50mm varifocal lens: \$49 7. MOQ: 5pcs, sample: add \$20
	SC5Q21	2 Megapixel 1080P Sony Low light Sensor IR Bullet IP Camera 1920x1080@25fps, Sony 2 Megapixel lowlight sensor IMX323 + Hi3516C SoC chip,Color: 0.1Lux@F1.2; B/W:0.01Lux@F1.2; DWDR,BLC,ROI, Tampering alarm, 2.8-12 motorized zoom & auto focus lens, 4x array LED, IR 50m, built-in Smart function, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring. High quality cast aluminum material,vertical 90° & horizontal 360°rotation bracket, creative single axis control.		PoE	8mm	50m	IP66	1. 6/8/12/16mm is optional MOQ: 5pcs, sample: add \$20
	SC5Q21Z-T28	2 Megapixel 1080P Sony Starlight Sensor IR Bullet IP Camera 1920x1080@25fps, Sony 2 Megapixel starlight sensor IMX291 + Hi3516D SoC chip, Full Color: 0.001Lux@F1.2; DWDR,BLC,ROI, 3D DNR, Tampering alarm, 2.8-12 motorized zoom & auto focus lens, 4x array LED, IR 50m, built-in Smart function, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring. High quality cast aluminum material,vertical 90° & horizontal 360°rotation bracket, creative single axis control.		PoE	2.8-12mm motorized zoom & autofocus	50m	IP66	MOQ: 5pcs, sample: add \$20
	SC5Q21Z-T62	2 Megapixel 1080P Sony Starlight Sensor IR Bullet IP Camera 1920x1080@25fps, Sony 2 Megapixel starlight sensor IMX291 + Hi3516D SoC chip, Full Color: 0.001Lux@F1.2; DWDR,BLC,ROI, 3D DNR, Tampering alarm, 6-22 motorized zoom & auto focus lens, 4x array LED, IR 50m, built-in Smart function, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring. High quality cast aluminum material,vertical 90° & horizontal 360°rotation bracket, creative single axis control,.		PoE	6-22mm motorized zoom & autofocus	50m	IP66	MOQ: 5pcs, sample: add \$20

	SC5Q31B	3 Megapixel 25fps Starlight IR Bullet PoE IP Camera 2048*1536@25fps, Sony 3 Megapixel Low light sensor IMX124+ Hi3516D SoC chip, Full Color: 0.001Lux@F1.2; DWDR,BLC,ROI, 3D DNR, Tampering alarm, 12mm fixed lens, 4x array LED, IR 50m, built-in Smart function, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring. High quality cast aluminum material,vertical 90° & horizontal 360°rotation bracket, creative single axis control.		PoE	12mm	50m	IP66	1. 8/12/25/36mm lens is optional MOQ: 5pcs, sample: add \$20
	SC5Q51B	5 Megapixel Sony Starlight Sensor 25/30fps H.265/H.264 IR Metal Dome IP Camera 5 Megapixel : 2592*1944@25/30fps, Sony 1/1.8" super starlight 5 Megapixel sensor IMX178 + Hi3516A SoC chip,Full color: 0.001Lux@F1.2; DWDR,BLC,ROI, 3D DNR, Tampering alarm, 12mm fixed lens, 4x array LED, IR 50m, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High quality cast aluminum material,vertical 90° & horizontal 360°rotation bracket, creative single axis control.		PoE	12mm	50m	IP66	1. 8/12/25/36mm lens is optional MOQ: 5pcs, sample: add \$20
	SC5Q81B-12M	4K Sony 12 Megapixel Ultra Starlight Sensor 4K 25/30fps H.265/H.264 IR Metal Bullet IP Camera 12 Megapixel : 4000x3000@15fps,8 Megapixel 4Kx2K: 4096*2160 25fps, Sony 1/1.7" super starlight 12 Megapixel sensor IMX226+ Hi3519 SoC chip,Full color: 0.0001Lux@F1.2; DWDR,BLC,ROI, 3D DNR, Tampering alarm, 3.6-10 varifocal 4K lens, 4 pcs array LED light, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High quality cast aluminum material,vertical 90° & horizontal 360°rotation bracket, creative single axis control. PoE/DC12V/AC24V. HDMI output, USB interface.		PoE	3.6-10mm	50m	IP66	1. 6/8/12/25/36/2.8-12/7-22mm lens is optional MOQ: 5pcs, sample: add \$20
	SC5F21Z-T12	WDR H.264 2 Megapixel@25fps WDR Motorized Zoom Box IP Camera 1/2.8 "Progressive Scan WDR & Starlight Sony CMOS + Hi3516D, motorized zoom 2.8 ~ 12mm, One Push auto focus, IR distance: 50m , 2 array LED, 140dB, DC12V /PoE/AC24, with bracket		PoE AC24V/DC24V	2.8-12mm motorized zoom & autofocus	50m	IP66	
	SC5F41Z-T62	WDR H.265 / H.264 4 Megapixel@25fps WDR Motorized Zoom Box IP Camera 1/3 "Progressive Scan CMOS OV4689 + Hi3516D, motorized zoom 6 ~ 22mm, One Push auto focus, IR distance: 50m , 2 array LED, 110dB, DC 12V, with bracket		PoE	6-22mm motorized zoom & autofocus	50m	IP66	
	SC5F41ZB-T12	WDR H.265 / H.264 4 Megapixel@25fps WDR Motorized Zoom Box IP Camera 1/3 "Progressive Scan CMOS OV4689 + Hi3516D, motorized zoom 2.8 ~12mm, One Push auto focus, IR distance: 50m , 2 array LED, 110dB, 2 array LED, 140dB, DC12V /PoE/AC24, with bracket		PoE	2.8-12mm motorized zoom & autofocus	50m	IP66	

	SC5P41Z-T62	H.265 / H.264 4 Megapixel@15fps WDR Motorized Zoom Box IP Camera 1/3 "Progressive Scan CMOS OV4689 + Hi3516D, motorized zoom 6 ~ 22mm, One Push auto focus, IR distance: 100m, 4 array LED, 110dB, DC 12V, with bracket		DC12V	6-22mm motorized zoom & autofocus	100m	IP66	
	SC5251ZR	H.265/H.264 5 Megapixel @25fps Motorized Zoom Starlight IR Indoor IP Camera 1 / 1.8" Progressive Scan CMOS Sony IMX178, 5 megapixel 25/30fps, 1080P@50/60fps, illumination 0lux, IR CUT, IR light:15-30m, motorized lens 3.6 ~ 10mm, One Push auto focus, 120dB TWDR, SD card slot 128GB, alarm input / output, RS485, built-in Microphone, audio input and output, DC 12V & AC24V, POE		PoE AC24V/DC12V	3.6-10mm motorized zoom & autofocus	15-30m	IP66	
	SC5321D	H.265/H.264 2 Megapixel@25fps Starlight WDR IR Vandal Proof IP Camera 1/2.8" Sony 2 Megapixel Progressive Scan IMX290+ Hi3516D, illumination: 0.005Lux, IR CUT, manual lens 2.8 ~ 12mm, IP66 waterproof, IK10 vandal proof, 140dB TWDR, SD card slot 128GB, alarm input / output, RS485, built-in Microphone, audio input and output, DC 12V & AC24V, POE		PoE AC24V/DC12V	2.8-12mm	x	IP66	
	SC5321DZ	H.265/H.264 2 Megapixel@25fps Starlight WDR IR Vandal Proof IP Camera 1/2.8" Sony 2 Megapixel Progressive Scan IMX290+ Hi3516D, illumination: 0.005Lux, IR CUT, motorized zoom lens 2.8 ~ 12mm, IP66 waterproof, IK10 vandal proof, 140dB TWDR, SD card slot 128GB, alarm input / output, RS485, built-in Microphone, audio input and output, DC 12V & AC24V, POE		PoE AC24V/DC12V	2.8-12mm motorized zoom & autofocus	x	IP66	
	SC5321ZR	H.265/H.264 2 Megapixel 50/60fps Starlight Motorized Zoom IR Vandal Proof IP Camera 1 / 2.8" Progressive Scan CMOS Sony IMX290, Hi3616A, 2 Megapixel 1080P 50/60fps, illumination 0lux, motorized lens 2.8 ~ 12mm, One Push auto focus, IP66 water-proof, IK10 vandal proof, IR CUT, 140dB TWDR, SD card slot 128GB, alarm input / output, RS485, built-in Microphone, audio input and output, DC 12V & AC24V, POE		PoE AC24V/DC12V	2.8-12mm motorized zoom & autofocus	15-30m	IP66	
	SC5341ZR	H.265/H.264 4 Megapixel @25fps Motorized Zoom IR Vandal Proof IP Camera 1/3 "4 Megapixel Progressive Scan CMOS OV4689+ Hi3516D, illumination: 0Lux, IR CUT, motorized lens 2.8 ~ 12mm, IP66 waterproof, IK10 vandal proof, One Push auto focus, 110dB TWDR, SD card slot 128GB, alarm input / output, RS485, built-in Microphone, audio input and output, DC 12V & AC24V, POE		PoE AC24V/DC12V	2.8-12mm motorized zoom & autofocus	15-30m	IP66	

	SC5351Z	H.265/H.264 5 Megapixel @25fps Motorized Zoom Starlight IR Vandal Proof IP Camera 1 / 1.8" Progressive Scan CMOS Sony IMX178, 5 megapixel 25/30fps, 1080P@50/60fps, illumination 0.001lux, IR CUT, motorized lens 3.6 ~ 10mm, IP66 waterproof, IK10 vandal proof, One Push auto focus, 120dB TWDR, SD card slot 128GB, alarm input / output, RS485, built-in Microphone, audio input and output, DC 12V & AC24V, POE	PoE AC24V/DC12V	3.6-10mm motorized zoom & autofocus	x	IP66	
	SC5351ZR	H.265/H.264 5 Megapixel @25fps Motorized Zoom Starlight IR Vandal Proof IR IP Camera 1 / 1.8" Progressive Scan CMOS Sony IMX178, 5 megapixel 25/30fps, 1080P@50/60fps, illumination 0lux, IR CUT, IR light: 15-30m, motorized lens 3.6 ~ 10mm, IP66 waterproof, IK10 vandal proof, One Push auto focus, 120dB TWDR, SD card slot 128GB, alarm input / output, RS485, built-in Microphone, audio input and output, DC 12V & AC24V, POE	PoE AC24V/DC12V	3.6-10mm motorized zoom & autofocus	15-30m	IP66	
	SC51B1	H.265 /H.264 12 Megapixel 25/30fps Starlight Ultra HD Box IP Camera 1 / 1.7 " Sony starlight Progressive Scan CMOS IMX236+ Hi3519A, Min. illumination Color: 0.01Lux@F1.2, B/W: 0.0001Lux@F1.2, DWDR,BLC,ROI, 3D DNR, Tampering alarm, Micro SD card slot, 2 alarm input & 1 alarm output, RS485, audio input and output, CVBS, DC 12V & AC 24V & POE. No Lens.	PoE	x	x	x	
	SC5181	H.265 /H.264 8 Megapixel 4x2K 25/30fps Starlight Ultra HD Box IP Camera with HDMI output 1 / 2.5" Sony starlight Progressive Scan CMOS IMX274+ Hi3519A, Min. illumination Color: 0.05Lux@F1.2, B/W: 0.0001Lux@F1.2, DWDR,BLC,ROI, 3D DNR, Tampering alarm, Micro SD card slot, 2 alarm input & 1 alarm output, RS485, audio input and output, HDMI, CVBS, DC 12V & AC 24V & POE	PoE	x	x	x	
	SC5151B	H.265 /H.264 5 Megapixel 25/30fps Sony Starlight Ultra HD Box IP Camera 1 / 1.8 " Sony starlight Progressive Scan CMOS IMX178 + Hi3519A, Min. illumination: Full Color: 0.001Lux@F1.2,DWDR,BLC,ROI, 3D DNR, Tampering alarm, Micro SD card slot, 2 alarm input & 1 alarm output, RS485, audio input and output, HDMI, CVBS, DC 12V & POE. No Lens.	PoE	x	x	x	
	SC5131B	H.265 /H.264 3 Megapixel 25/30fps Sony Starlight HD Box IP Camera with HDMI output 1 / 2.8 " Sony starlight Progressive Scan CMOS IMX124 + Hi3519D, Min. illumination: Full Color: 0.001Lux@F1.2,DWDR,BLC,ROI, 3D DNR, Tampering alarm, Micro SD card slot, 2 alarm input & 1 alarm output, RS485, audio input and output, CVBS, DC 12V & POE. No Lens.	PoE	x	x	x	

	SC5131W	H.265 /H.264 3 Megapixel 25/30fps Sony Back-illuminated WDR HD Box IP Camera with HDMI output 1 / 2.8 " Sony STARVIS DOL-WDR Progressive Scan CMOS IMX123 + Hi3519D, Back-illuminated DOL-WDR:130dB, BLC,ROI, 3D DNR, Tampering alarm , Micro SD card slot, 2 alarm input & 1 alarm output, RS485, audio input and output, HDMI, CVBS, DC 12V & POE. No Lens.		PoE	x	x	x	
	SC5121B	H.265 /H.264 2 Megapixel 25/30fps Sony Starlight HD Box IP Camera with HDMI output 1 / 2.8 " Sony starlight Progressive Scan CMOS IMX291 + Hi3516D, Min. illumination: Full Color: 0.001Lux@F1.2,DWDR,BLC,ROI, 3D DNR, Tampering alarm , Micro SD card slot, 2 alarm input & 1 alarm output, RS485, audio input and output, HDMI, CVBS, DC 12V & POE. No Lens.		PoE	x	x	x	
	SC5620E-C03	2.0 Megapixel 1080P 3x Zoom PTZ Mini Dome IP Camera 1920*1080@25fps, 3x optical zoom camera module, Sony Exmor CMOS, audio in/out, alarm in /out, video output interface, No IR light, waterproof cable box metal housing, IP 66. -30° C to 50° C, AC24V, auto temperature control. Built-in TVS4000V lightning-proof, surge-proof and wave-proof.		AC24V	3-9mm 3x optical zoom	x	IP66	IK10 vandal proof: \$10
	SC5620E-C10	2.0 Megapixel 1080P 10x Zoom PTZ Mini Dome IP Camera 1920*1080@25fps, 10x optical zoom camera module, Sony Exmor CMOS, audio in/out, alarm in /out, video output interface, No IR light, waterproof cable box metal housing, IP 66. -30° C to 50° C, AC24V, auto temperature control. Built-in TVS4000V lightning-proof, surge-proof and wave-proof.		AC24V	5.5-55mm 10x optical zoom	x	IP66	IK10 vandal proof: \$10
	SC5620F-C03	2.0 Megapixel 1080P 3x Zoom PTZ Mini Dome IR IP Camera 1920*1080@25fps, 3x optical zoom camera module, Sony Exmor CMOS, audio in/out, alarm in /out, video output interface, IR light: 50m, waterproof cable box metal housing, IP 66. -30° C to 50° C, AC24V, auto temperature control. Built-in TVS4000V lightning-proof, surge-proof and wave-proof.		AC24V	3-9mm 3x optical zoom	50m	IP66	
	SC5620F-C10	2.0 Megapixel 1080P 10x Zoom PTZ Mini Dome IR IP Camera 1920*1080@25fps, 10x optical zoom camera module, Sony Exmor CMOS, audio in/out, alarm in /out, video output interface, IR light: 50m, waterproof cable box metal housing, IP 66. -30° C to 50° C, AC24V, auto temperature control. Built-in TVS4000V lightning-proof, surge-proof and wave-proof.		AC24V	5.5-55mm 10x optical zoom	50m	IP66	
	SC5620DF-C20	2.0 Megapixel 1080P 20x Zoom High Speed Dome Vandal Proof IP Camera 1920*1080@25fps, 20x optical zoom camera module, CMOS, audio in/out, alarm in /out, video output interface, No IR light, waterproof cable box metal housing, IP 66, IK10. -40° C to 60° C, AC24V, auto temperature control. Built-in TVS4000V lightning-proof, surge-proof and wave-proof.		AC24V	4.7-94mm 20x Optical Zoom	x	√	

	SC5620DF-C36	2.0 Megapixel 1080P 36x Zoom High Speed Dome Vandal Proof IP Camera 1920*1080@25fps, 36x optical zoom camera module, CMOS, audio in/out, alarm in /out, video output interface, No IR light, waterproof cable box metal housing, IP 66, IK10. -40° C to 60° C, AC24V, auto temperature control. Built-in TVS4000V lightning-proof, surge-proof and wave-proof.		AC24V	4.6-165.5mm 36x Optical Zoom	x	√	
	SC5620DF-C18S	2.0 Megapixel 1080P 18x Zoom High Speed Dome Vandal Proof IP Camera 1920*1080@25fps, 18x optical zoom camera module, starlight : color: 0.001Lux, B/W: 0.00001Lux, CMOS, audio in/out, alarm in /out, video output interface, No IR light, waterproof cable box metal housing, IP 66, IK10. -40° C to 60° C, AC24V, auto temperature control. Built-in TVS4000V lightning-proof, surge-proof and wave-proof.		AC24V	4.6-165.5mm 36x Optical Zoom	x	√	
	SC5620DF-S20	2.0 Megapixel 1080P 20x Zoom High Speed Dome Vandal Proof IP Camera 1920*1080@25fps, Sony FCB6300 20x optical zoom camera module, CMOS, audio in/out, alarm in /out, video output interface, No IR light, waterproof cable box metal housing, IP 66, IK10. -40° C to 60° C, AC24V, auto temperature control. Built-in TVS4000V lightning-proof, surge-proof and wave-proof.		AC24V	4.7mm(W) ~94mm (T) 20x Optical Zoom	x	√	
	SC5620DF-S30	2.0 Megapixel 1080P 30x Zoom High Speed Dome Vandal Proof IP Camera 1920*1080@25fps, Sony FCB7500 30x optical zoom camera module, CMOS, audio in/out, alarm in /out, video output interface, No IR light, waterproof cable box metal housing, IP 66, IK10. -40° C to 60° C, AC24V, auto temperature control. Built-in TVS4000V lightning-proof, surge-proof and wave-proof.		AC24V	4.6mm(W) ~138.0mm (T) 30x Optical Zoom	x	√	
	SC5M20-C20	2.0 Megapixel 1080P 20x Zoom High Speed PTZ IR IP Camera 1920*1080@25fps, 20x optical zoom camera module, CMOS, audio in/out, alarm in /out, video output interface, wiper, IR light: 100m, with advantages of impact-resistant, corrosion-proof, and wiper, IP 66. -40° C to 60° C, AC24V, auto temperature control. Built-in TVS4000V lightning-proof, surge-proof and wave-proof.		AC24V	4.7-94mm 20x Optical Zoom	100m	√	Sony 20x zoom module is optional
	SC5M20-C36	2.0 Megapixel 1080P 36x Zoom High Speed PTZ IR IP Camera 1920*1080@25fps, 36x optical zoom camera module, CMOS, audio in/out, alarm in /out, video output interface, wiper, IR light: 100m, with advantages of impact-resistant, corrosion-proof, and wiper, IP 66. -40° C to 60° C, AC24V, auto temperature control. Built-in TVS4000V lightning-proof, surge-proof and wave-proof.		AC24V	4.6-165.5mm 36x Optical Zoom	100m	√	Sony 20x zoom module is optional
	SC5M20L-C20	2.0 Megapixel 1080P 20x Zoom High Speed PTZ Laser IP Camera 1920*1080@25fps, 20x optical zoom camera module, CMOS, audio in/out, alarm in /out, video output interface, wiper, Laser night vision: 300m, with advantages of impact-resistant, corrosion-proof, and wiper, IP 66. -40° C to 60° C, AC24V, auto temperature control. Built-in TVS4000V lightning-proof, surge-proof and wave-proof.		AC24V	4.7-94mm 20x Optical Zoom	300m	√	Sony 20x zoom module is optional

	SC5M20L-C36	2.0 Megapixel 1080P 36x Zoom High Speed PTZ Laser IP Camera 1920*1080@25fps, 36x optical zoom camera module, CMOS, audio in/out, alarm in /out, video output interface, wiper, Laser night vision: 300m, with advantages of impact-resistant, corrosion-proof, and wiper, IP 66. -40° C to 60° C, AC24V, auto temperature control. Built-in TVS4000V lightning-proof, surge-proof and wave-proof.		AC24V	4.6-165.5mm 36x Optical Zoom	300m	√	Sony 20x zoom module is optional
	SC5M20L-C30S	2.0 Megapixel 1080P 30x Zoom Starlight High Speed PTZ Laser IP Camera 1920*1080@25fps, 30x optical zoom camera module, CMOS, starlight night vision: color: 0.001Lux, B/W: 0.000Lux. audio in/out, alarm in /out, video output interface, wiper, Laser night vision: 300m, with advantages of impact-resistant, corrosion-proof, and wiper, IP 66. -40° C to 60° C, AC24V, auto temperature control. Built-in TVS4000V lightning-proof, surge-proof and wave-proof.		AC24V	6-180mm 20x Optical Zoom	300m	√	Sony 20x zoom module is optional
	SC5M20T-C40	2.0 Megapixel 1080P 40x Zoom Color + VGA Thermal Dual Camera High Speed PTZ Camera HD Color camera: 1920*1080@25fps, 40x optical zoom camera module, Sony Exmor CMOS. Thermal camera: resolution: 768*576, Focus: 55mm, work frequency: 8~14um. Vision distance: 130m BNC + IP Dual video output. audio in/out, alarm in /out, video output interface, IP 66. -40° C to 60° C, AC24V, auto temperature control. Built-in TVS4000V lightning-proof, surge-proof and wave-proof.		AC24V	6.8-272mm 40x Optical Zoom	500m	√	Sony 20x zoom module is optional 19mm thermal lens is optional
	SC5620I-C20	2.0 Megapixel 1080P 20x Zoom High Speed Dome IR IP Camera 1920*1080@25fps, 20x optical zoom camera module, Sony Exmor CMOS, audio in/out, alarm in /out, video output interface, IR light: 100m, waterproof cable box metal housing, IP 66. -40° C to 60° C, AC24V, auto temperature control. Built-in TVS4000V lightning-proof, surge-proof and wave-proof.		AC24V	4.7-94mm 20x Optical Zoom	100m	√	
	SC5620I-C36	2.0 Megapixel 1080P 36x Zoom High Speed Dome IR IP Camera 1920*1080@25fps, 36x optical zoom camera module, Sony Exmor CMOS, audio in/out, alarm in /out, video output interface, IR light: 100m, waterproof cable box metal housing, IP 66. -40° C to 60° C, AC24V, auto temperature control. Built-in 4000V lightning-proof, surge-proof and wave-proof.		AC24V	4.6-165.5mm 36x Optical Zoom	100m	√	
	SC5620I-S20	2.0 Megapixel 1080P 20x Zoom High Speed Dome IR IP Camera 1920*1080@25fps, Sony 20x optical zoom camera module FCB6300, audio in/out, alarm in /out, video output interface, IR light: 100m, waterproof cable box metal housing, IP 66. -40° C to 60° C, AC24V, auto temperature control. Built-in TVS4000V lightning-proof, surge-proof and wave-proof.		AC24V	4.7mm(W) ~94mm (T) 20x Optical Zoom	100m	√	



	SC5620IL-C20	2.0 Megapixel 1080P 20x Zoom High Speed Dome Laser 300m IP Camera 1920*1080@25fps, 20x optical zoom camera module, Sony Exmor CMOS, audio in/out, alarm in /out, video output interface, Laser: 300m, waterproof cable box metal housing, IP 66. -40° C to 60° C, AC24V, auto temperature control. Built-in TVS4000V lightning-proof, surge-proof and wave-proof.		AC24V	4.7-94mm 20x Optical Zoom	300m	√	
	SC5620IL-S20	2.0 Megapixel 1080P 20x Zoom High Speed Dome Laser 300m IP Camera 1920*1080@25fps, Sony 20x optical zoom camera module FCB6300, audio in/out, alarm in /out, video output interface, Laser: 300m, waterproof cable box metal housing, IP 66. -40° C to 60° C, AC24V, auto temperature control. Built-in TVS4000V lightning-proof, surge-proof and wave-proof.		AC24V	4.7mm(W) ~94mm (T) 20x Optical Zoom	300m	√	
	SC5620G	2.0 Megapixel 1080P 36x Zoom High Speed PTZ IP Camera 1920*1080@25fps, 36x optical zoom module, audio in/out, alarm in /out, video output CVBS, built-in SD card slot, RS485, IP 66. -40° C to 60° C, AC24V, auto temperature control. Built-in TVS4001V lightning-proof, surge-proof and wave-proof. 1/2.8" Progressive Scan CMOS;		AC24V	4.2~151.2 mm, 36x optical zoom	X	√	
	SC5620GL-40X	2.0 Megapixel 1080P 40x Zoom Laser High Speed PTZ IP Camera 1920*1080@25fps, 40x optical zoom module, audio in/out, alarm in /out, video output CVBS, built-in SD card slot, RS485, IP 66. -40° C to 60° C, AC24V, auto temperature control. Built-in TVS4001V lightning-proof, surge-proof and wave-proof. 1/2.8" Progressive Scan CMOS; Laser night vision.		AC24V	6.8~272.2 mm, 40x optical zoom	X	√	

SC6000 Series Professional IP Camera Price List

Sony Sensor	1/1.3/2/3/4/5 Megapixel	-40℃ - +60℃	3 Years warranty	ONVIF & HTTP CGI	H.265/H.264 High profile	Starlight WDR	2D/3D Noise	Video Flip	SD Card	POE Power
--------------------	--------------------------------	--------------------	-------------------------	-----------------------------	---------------------------------	----------------------	--------------------	-------------------	----------------	------------------

Note:

If your order value is less than USD5,000, you maybe need to pay additional charges (\$20-30) . We could update the price in any time and don't immediately notice you.

Picture	Model	Specifications	Price	POE	Lens	Infrared	Waterproof	Options
Automatic Number-Plate Recognition (ANPR), License Plate Recognition (LPR) IP Camera								
    	SC6121PZ	Automatic Number-Plate Recognition (ANPR), License Plate Recognition (LPR) IP Camera Support Russia,Turkey,UAE, Qatar, Saudi Arabia, France, Indonesia, Singapore, India, Brazil, etc..countries(optional version) license plate recognition. Using Deep Learning AI(Artificial Intelligence) technology to improve the recognition accuracy; Support license plate detection and capture, recognition, support white list control. License plate number OSD, 4 * LED white light, 1920x1080, 1/2.8" Machine Vision CMOS sensor + Hisilicon Hi3516A, H.265 Encode, MP, BP. Multiple Exposure 130dB Super WDR, Star light level Super low light, ,Highlight Compensation (HLC). DC12V/2A, No AC/DC adapter.		√	2.8-12mm Motorized Zoom & Auto focus	white light	√	1.4/6/8/12/16/25mm fixed lens optional
    	SC6B21P	Automatic Number-Plate Recognition (ANPR), License Plate Recognition (LPR) Bullet IP Camera Support Russia,Turkey,UAE, Qatar, Saudi Arabia, France, Indonesia, Singapore, India, Brazil, etc..countries(optional version) license plate recognition. Using Deep Learning AI(Artificial Intelligence) technology to improve the recognition accuracy; Support license plate detection and capture, recognition, support white list control. License plate number OSD, 6 * LED white light, 1920x1080, 1/2.8" Machine Vision CMOS sensor + Hisilicon Hi3516A, H.265 Encode, MP, BP. Multiple Exposure 130dB Super WDR, Star light level Super low light, ,Highlight Compensation (HLC). DC12V/2A, No AC/DC adapter.		√	2.8-12mm Motorized Zoom & Auto focus	white light	√	1.4/6/8/12/16/25mm fixed lens optional
Intelligent Face Recognition Cameras & NVR, H.265 WDR, 50fps! New!								
 	SC6121-FA	Intelligent Face Capture HD IP Camera Professional face detection and analysis FPGA + Hisilicon Hi3516A, support face cache, ISP control, face region enhance, support three intelligent face capture mode: capture after person leave; timely capture; frames capture; Auto adjust face region exposure; Auto find the best quality face and upload to server; Support FTP/SDK/HTTP upload full scene or only face picture to server. It can greatly save face recognition cost 1920x1080, 50/60fps, 1/2.8" Machine Vision CMOS sensor + Hisilicon Hi3516A, H.265 Encode, MP, BP. Multiple Exposure 130dB Super WDR, Star light level Super low light, ,Highlight Compensation (HLC). Built-in PoE, No Lens, No AC/DC adapter.		√	optional	X	X	

	SC6B21-FA	Intelligent Face Capture HD Bullet IP Camera Professional face detection and analysis FPGA + Hisilicon Hi3516A, support face cache, ISP control, face region enhance, support three intelligent face capture mode: capture after person leave; timely capture; frames capture; Auto adjust face region exposure; Auto find the best quality face and upload to server; Support FTP/SDK/HTTP upload full scene or only face picture to server. It can greatly save face recognition cost 1920x1080, 50/60fps, 1/2.8" Machine Vision CMOS sensor + Hisilicon Hi3516A, H.265 Encode, MP, BP. Multiple Exposure 130dB Super WDR, Star light level Super low light, Highlight Compensation (HLC). Built-in PoE, 6 pcs array white LED light, No AC/DC adapter, no bracket.		√	6/8/12/16 mm	6pcs white array LED light	√	
	Face Recognition Software	Intelligent Face recognition Software Linux-based system, support face recognition, search, white / black list alarm. World leading recognition algorithm.B/S system.		-	-	-	-	Don't include Linux software and server hardware
	Face Recognition Server	Intelligent Face recognition Server Industry PC server, Intel Xeon-E5 CPU, 16GB memory, can support 16ch cameras recognition. HDMI output, 1000M Gigabit Ethernet.						Including Linux operation system, don't include display.
	Dongle	U Key for recognition server, one server need one dongle.		-	-	-	-	
Picture	Model	Specifications	Price	POE	Lens	Infrared	Waterproof	Options
H.264 Small IR Bullet IP Camera, fixed lens, IR distance: 10-15m. Promotion!								
	SC6811B	1280*960, Sony Exmor 1/3" CMOS sensor, super low light, Digital WDR, intelligence 3D noise reduction, 2 IR lights, 15m. Micro SD card. Built-in PoE, 3.6mm Fixed M12 Lens, No AC/DC adapter.		√	3.6mm	10-15m	√	1. 2.8mm Lens: free 2. AC/DC Adapter: \$6 3. Audio input & output: \$6 4. MOQ: 50pcs
	SC6820	1920*1080, Sony Exmor 1/2.8" CMOS sensor, super low light, Digital WDR, intelligence 3D noise reduction, 2 IR lights, 20m. Micro SD card. DC12V, 3.6mm Fixed M12 Lens, No AC/DC adapter.		√	3.6mm	10-15m	√	1. 2.8mm Lens: free 2. AC/DC Adapter: \$6 3. Audio input & output: \$6 4. MOQ: 50pcs

 Hot	SC6821	1920*1080, Sony Exmor 1/2.8" CMOS sensor, super low light, Digital WDR, intelligence 3D noise reduction, 2 IR lights, 20m. Micro SD card. Built-in PoE, 3.6mm Fixed M12 Lens, No AC/DC adapter.		√	3.6mm	10-15m	√	1. 2.8mm Lens: free 2. AC/DC Adapter: \$6 3. Audio input & output: \$6 4. MOQ: 50pcs
H.264 Medium IR Bullet IP Camera, fixed / varifocal lens, IR distance: 20-30m								
 Hot	SC6411B	1280*960, Sony Exmor 1/3" CMOS sensor, super low light, Digital WDR, intelligence 3D noise reduction, 3 IR lights, 30m. Micro SD card. Built-in PoE, 6mm Fixed Lens, No AC/DC adapter.		√	6mm	20-30m	√	1. 4/8/12mm Lens: free 2. 2.8-12mm Varifocal Lens: \$3 3. AC/DC Adapter: \$6 4. Audio input & output: \$6
	SC6420	1920*1080, Sony Exmor 1/2.8" CMOS sensor, super low light, Digital WDR, intelligence 3D noise reduction, 3 IR lights, 30m. Micro SD card. No PoE, 6mm Fixed Lens, No AC/DC adapter.		X	6mm	20-30m	√	1. 4/8/12mm Lens: free 2. 2.8-12mm Varifocal Lens: \$5 3. AC/DC Adapter: \$6 4. Audio and alarm: \$6
 Hot	SC6421	1920*1080, Sony Exmor 1/2.8" CMOS sensor, super low light, Digital WDR, intelligence 3D noise reduction, 3 IR lights, 30m. Micro SD card. Built-in PoE, 6mm Fixed Lens, No AC/DC adapter.		√	6mm	20-30m	√	1. 4/8/12mm Lens: free 2. 2.8-12mm Varifocal Lens: \$5 3. AC/DC Adapter: \$6 4. Audio input & output: \$6
 Zoom	SC6421Z	1920*1080, Sony Exmor 1/2.8" CMOS sensor, 4x Zoom , super low light, Digital WDR, intelligence 3D noise reduction, 3 IR lights, 30m. Micro SD card. Built-in PoE, 2.8-12mm remote control Optical Zoom and Focus Lens, No AC/DC adapter.		√	2.8-12mm Motorized Zoom & Auto Focus	20-30m	√	1. AC/DC Adapter: \$6 4. Audio input & output: \$6
H.265/H.264 Medium IR Bullet IP Camera, fixed / varifocal lens, IR distance: 20-30m, IP66 waterproof, audio input/output is optional.								
	SC6441B	4 Megapixel Real Time 25fps H.265 /H.264 Outdoor IR Bullet PoE IP Camera, 2592*1920@25fps, 1/3" WDR CMOS sensor, H.265/H.264/MJPEG Encoding. Optical WDR,intelligence 3D noise reduction. IP66 water proof, 3 IR lights, 30m.Micro SD card. Built-in PoE, 6mm Fixed Lens, No AC/DC adapter.		X	6mm	20-30m	√	1. 6/8/12/16mm Lens: free 2. Audio input & output: \$6 3. AC/DC Adapter: \$6
	SC6441B-T12	4 Megapixel Real Time 25fps H.265 /H.264 Outdoor IR Bullet PoE IP Camera, 2592*1920@25fps, 1/3" WDR CMOS sensor, H.265/H.264/MJPEG Encoding. Optical WDR,intelligence 3D noise reduction. IP66 water proof, 3 IR lights, 30m.Micro SD card. Built-in PoE, 2.8-12mm varifocal lens, No AC/DC adapter.		X	2.8-12mm	20-30m	√	1. 6/8/12/16mm Lens: free 2. Audio input & output: \$6 3. AC/DC Adapter: \$6
	SC6431B	3 Megapixel Real Time 25fps H.265 /H.264 Outdoor IR Bullet PoE IP Camera, 2592*1920@25fps, 1/3" WDR CMOS sensor, H.265/H.264/MJPEG Encoding. Optical WDR,intelligence 3D noise reduction. IP66 water proof, 3 IR lights, 30m.Micro SD card. Built-in PoE, 6mm Fixed Lens, No AC/DC adapter.		X	6mm	20-30m	√	1. 6/8/12/16mm Lens: free 2. Audio input & output: \$6 3. AC/DC Adapter: \$6
	SC6431B-T12	3 Megapixel Real Time 25fps H.265/H.264 Outdoor IR Bullet PoE IP Camera, 2592*1920@25fps, 1/3" WDR CMOS sensor, H.265/H.264/MJPEG Encoding. Optical WDR,intelligence 3D noise reduction. IP66 water proof, 3 IR lights, 30m.Micro SD card. Built-in PoE, 2.8-12mm varifocal lens, No AC/DC adapter.		X	2.8-12mm	20-30m	√	1. 6/8/12/16mm Lens: free 2. Audio input & output: \$6 3. AC/DC Adapter: \$6

	SC6421B-H5W	2 Megapixel 1080P@25fps H.265 / H.264 Super WDR Outdoor IR Bullet PoE IP Camera. 1920*1080@25fps, 1/2.8" Machine Vision CMOS sensor + Hisilicon Hi3516D, H.265/H.264/MJPEG Encoding. Multiple Exposure 130dB Super WDR, Star light level Super low light, Highlight Compensation (HLC), IP66 water proof, 3 IR lights, 30m. Micro SD card. Built-in PoE, 6mm Fixed Lens, No AC/DC adapter.		X	6mm	20-30m	√	1. 6/8/12/16mm Lens: free 2. Audio input & output: \$6 3. AC/DC Adapter: \$6
	SC6421B-H5W-T12	2 Megapixel 1080P@25fps H.265 / H.264 Super WDR Outdoor IR Bullet PoE IP Camera. 1920*1080@25fps, 1/2.8" Machine Vision CMOS sensor + Hisilicon Hi3516D, H.265/H.264/MJPEG Encoding. Multiple Exposure 130dB Super WDR, Star light level Super low light, Highlight Compensation (HLC), IP66 water proof, 3 IR lights, 30m. Micro SD card. Built-in PoE, 2.8-12mm Fixed Lens, No AC/DC adapter.		X	2.8-12mm	20-30m	√	1. 6/8/12/16mm Lens: free 2. Audio input & output: \$6 3. AC/DC Adapter: \$6
	SC6421B-H5	2 Megapixel 1080P@25fps H.265 / H.264 Low Light Outdoor IR Bullet PoE IP Camera. 1920*1080@25fps, 1/2.8" CMOS sensor + Hisilicon Hi3516D, H.265/H.264/MJPEG Encoding. Super low light, digital WDR. IP66 water proof, 3 IR lights, 30m. Micro SD card. Built-in PoE, 6mm Fixed Lens, No AC/DC adapter.		X	6mm	20-30m	√	1. 6/8/12/16mm Lens: free 2. Audio input & output: \$6 3. AC/DC Adapter: \$6
	SC6421B-H5-T12	2 Megapixel 1080P@25fps H.265 / H.264 Low Light Outdoor IR Bullet PoE IP Camera. 1920*1080@25fps, 1/2.8" CMOS sensor + Hisilicon Hi3516D, H.265/H.264/MJPEG Encoding. Super low light, digital WDR. IP66 water proof, 3 IR lights, 30m. Micro SD card. Built-in PoE, 2.8-12mm varifocal Lens, No AC/DC adapter.		X	2.8-12mm	20-30m	√	1. 6/8/12/16mm Lens: free 2. Audio input & output: \$6 3. AC/DC Adapter: \$6
Big IR Bullet IP Camera (IR distance 80-100m, IR can be removed, 100/1000M Ethernet, -40 °C ~ 60°C, IP66, PoE is optional, no installation bracket)								
	SC6B11B-L12	1.3 Megapixel H.264 IR Bullet IP Camera. 1280*960@25fps, Sony Exmor 1/2.8" CMOS sensor, H.264 HP, MP, BP, super low light, Digital WDR, intelligence 3D noise reduction, 6 IR led lights, Max 100m, Micro SD card slot, audio & alarm input/output, RS485. Built-in PoE, 12mm fixed Lens, No AC/DC adapter.		√	12mm	80-100m	√	1. 6/8/12/16mm Lens: free 2. 3G: \$79 3. 4G: \$139 4. AC/DC Adapter: \$7 5. Wall installation bracket: \$6
	SC6B11B-T12	1.3 Megapixel H.264 IR Bullet IP Camera. 1280*960@25fps, Sony Exmor 1/2.8" CMOS sensor, H.264 HP, MP, BP, super low light, Digital WDR, intelligence 3D noise reduction, 6 IR led lights, Max 100m, Micro SD card slot, audio & alarm input/output, RS485. Built-in PoE, 2.8-12mm varifocal Lens, No AC/DC adapter.		√	2.8-12mm	80-100m	√	1. 7-22mm: \$25 2. 3G: \$79 3. 4G: \$139 4. AC/DC Adapter: \$7 5. Wall installation bracket: \$6
	SC6B20-L12	2 Megapixel 1080P H.264 IR Bullet IP Camera. 1920*1080@25fps, Sony Exmor 1/2.8" CMOS sensor, H.264 HP, MP, BP, super low light, Digital WDR, intelligence 3D noise reduction, 6 IR led lights, Max 100m, Micro SD card slot, audio & alarm input/output, RS485. No PoE, 12mm fixed Lens, No AC/DC adapter.		X	12mm	80-100m	√	1. 6/8/12/16mm Lens: free 2. 3G: \$79 3. 4G: \$139 4. AC/DC Adapter: \$7 5. Wall installation bracket: \$6

	SC6B21-L12	2 Megapixel 1080P H.264 IR Bullet IP Camera. 1920*1080@25fps, Sony Exmor 1/2.8" CMOS sensor, H.264 HP, MP, BP, super low light, Digital WDR, intelligence 3D noise reduction, 6 IR led lights, Max 100m, Micro SD card slot, audio & alarm input/output, RS485. Built-in PoE, 12mm fixed Lens, No AC/DC adapter.		√	12mm	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket: \$6
	SC6B21-T12	2 Megapixel 1080P H.264 IR Bullet IP Camera. 1920*1080@25fps, Sony Exmor 1/2.8" CMOS sensor, H.264 HP, MP, BP, super low light, Digital WDR, intelligence 3D noise reduction, 6 IR led lights, Max 100m, Micro SD card slot, audio & alarm input/output, RS485. Built-in PoE, 2.8-12mm varifocal Lens, No AC/DC adapter.		√	2.8-12mm	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket: \$6
	SC6B21Z	2 Megapixel 1080P H.264 IR Bullet IP Camera. 1920*1080@25fps, 1/2.8" Sony Exmor CMOS sensor, H.264 Encode, MP, BP. Super low light, digital WDR. Micro SD card (max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 100M RJ45. Built-in PoE, 2.8-12mm motorized zoom lens, No AC/DC adapter. IP66.		√	2.8-12mm Motorized Zoom	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket: \$6
	SC6B21-T72	2 Megapixel 1080P H.264 IR Bullet IP Camera. 1920*1080@25fps, 1/2.8" Sony Exmor CMOS sensor, H.264 Encode, MP, BP. Super low light, digital WDR. Micro SD card (max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 100M RJ45. Built-in PoE, 7-22mm varifocal lens, No AC/DC adapter. IP66.		√	7-22mm	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket: \$6
	SC6B21Z-T72	2 Megapixel 1080P H.264 IR Bullet IP Camera. 1920*1080@25fps, 1/2.8" Sony Exmor CMOS sensor, H.264 Encode, MP, BP. Super low light, digital WDR. Micro SD card (max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 100M RJ45. Built-in PoE, 7-22mm motorized zoom lens, No AC/DC adapter. IP66.		√	7-22mm Motorized Zoom	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket: \$6
	SC6B21-H5	H.265 2 Megapixel 1080P@25fps IR Bullet IP Camera. 1920*1080@25fps, 1/2.8" Sony Exmor CMOS sensor + Hisilicon Hi3516D, H.265 Encode, MP, BP. Super low light, digital WDR. Micro SD card (max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 100M RJ45. Built-in PoE, 12mm fixed lens, No AC/DC adapter. IP66		√	12mm	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket: \$6
	SC6B21-H5-T12	H.265 2 Megapixel 1080P@25fps IR Bullet IP Camera. 1920*1080@25fps, 1/2.8" Sony Exmor CMOS sensor + Hisilicon Hi3516D, H.265 Encode, MP, BP. Super low light, digital WDR. Micro SD card (max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 100M RJ45. Built-in PoE, 2.8-12mm varifocal lens, No AC/DC adapter. IP66		√	2.8-12mm	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket: \$6

	SC6B21Z-H5	H.265 2 Megapixel 1080P@25fps IR Bullet IP Camera. 1920*1080@25fps, 1/2.8" CMOS sensor + Hisilicon Hi3516D, H.265 Encode, MP, BP. Super low light,digital WDR. Micro SD card(max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 100M RJ45. Built-in PoE, 2.8-12mm motorized zoom lens, No AC/DC adapter. IP66	√	2.8-12mm Motorized Zoom	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6 5. SFP fiber port: \$40 6. SFP module: optional
	SC6B21-H5-T72	H.265 2 Megapixel 1080P@25fps IR Bullet IP Camera. 1920*1080@25fps, 1/2.8" Sony Exmor CMOS sensor + Hisilicon Hi3516D, H.265 Encode, MP, BP. Super low light,digital WDR. Micro SD card(max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 100M RJ45. Built-in PoE, No PoE, 7-22mm varifocal lens, No AC/DC adapter. IP66	X	7-22mm	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6 5. SFP fiber port: \$40 6. SFP module: optional
	SC6B21Z-H5-T72	H.265 2 Megapixel 1080P@25fps IR Bullet IP Camera. 1920*1080@25fps, 1/2.8" Sony Exmor CMOS sensor + Hisilicon Hi3516D, H.265 Encode, MP, BP. Super low light,digital WDR. Micro SD card(max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 100M RJ45. Built-in PoE, 7-22mm motorized zoom lens, No AC/DC adapter. IP66	√	7-22mm Motorized Zoom	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6 5. SFP fiber port: \$40 6. SFP module: optional
	SC6B21I-L12	2 Megapixel 1080P H.264 Intelligent Bullet IP Camera. 1920*1080@25fps,Sony Exmor 1/2.8" CMOS sensor, support Perimeter intrusion, tripwire,etc intelligent analysis. H.264 HP, MP, BP,super low light, Digital WDR, intelligence 3D noise reduction, Micro SD card slot, audio & alarm input/output, RS485. No IR light, Built-in PoE, 12mm fixed Lens, No AC/DC adapter.	√	12mm	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6
	SC6B21-H5W	2 Megapixel 1080P@25fps H.265 Super WDR IR Bullet IP Camera. 1920*1080@25fps, 1/2.8" Machine Vision CMOS sensor + Hisilicon Hi3516D, H.265 Encode, MP, BP. Multiple Exposure 130dB Super WDR, Star light level Super low light, ,Highlight Compensation (HLC). Micro SD card(max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 1000M Gigabit RJ45. Built-in PoE, 12mm fixed lens, No AC/DC adapter. IP66	√	12mm	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6
	SC6B21-H5W-T12	2 Megapixel 1080P@25fps H.265 Super WDR IR Bullet IP Camera. 1920*1080@25fps, 1/2.8" Machine Vision CMOS sensor + Hisilicon Hi3516D, H.265 Encode, MP, BP. Multiple Exposure 130dB Super WDR, Star light level Super low light, ,Highlight Compensation (HLC). Micro SD card(max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 1000M Gigabit RJ45. Built-in PoE, 2.8-12mm varifocal lens, No AC/DC adapter. IP66	√	2.8-12mm	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6

	SC6B21Z-H5WV	2 Megapixel 1080P@25fps H.265 Super WDR IR Bullet IP Camera. 1920*1080@25fps, 1/2.8" Machine Vision CMOS sensor + Hisilicon Hi3516D, H.265 Encode, MP, BP. Multiple Exposure 130dB Super WDR, Star light level Super low light, ,Highlight Compensation (HLC). Micro SD card(max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 1000M Gigabit RJ45. Built-in PoE, 2.8-12mm motorized zoom lens, No AC/DC adapter. IP66	√	2.8-12mm Motorized Zoom	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6
	SC6B21-H5W-T72	2 Megapixel 1080P@25fps H.265 Super WDR IR Bullet IP Camera. 1920*1080@25fps, 1/2.8" Machine Vision CMOS sensor + Hisilicon Hi3516D, H.265 Encode, MP, BP. Multiple Exposure 130dB Super WDR, Star light level Super low light, ,Highlight Compensation (HLC). Micro SD card(max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 1000M Gigabit RJ45. Built-in PoE, 7-22mm varifocal lens, No AC/DC adapter. IP66	√	7-22mm	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6 5. SFP fiber port: \$40 6. SFP module: optional
	SC6B21Z-H5W-T72	2 Megapixel 1080P@25fps H.265 Super WDR IR Bullet IP Camera. 1920*1080@25fps, 1/2.8" Machine Vision CMOS sensor + Hisilicon Hi3516D, H.265 Encode, MP, BP. Multiple Exposure 130dB Super WDR, Star light level Super low light, ,Highlight Compensation (HLC). Micro SD card(max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 1000M Gigabit RJ45. Built-in PoE, 7-22mm motorized zoom lens, No AC/DC adapter. IP66	√	7-22mm Motorized Zoom	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6 5. SFP fiber port: \$40 6. SFP module: optional
	SC6B21-H5D-T12	2 Megapixel 1080P@25fps H.265 Super Low Light Outdoor IR Bullet IP Camera, 1920*1280@25fps, Sony Exmor R 1/1.8" CMOS sensor IMX178LQJ+Hisilicon Hi3516A, H.265 Encode, MP, BP. Starlight level super low light, Digital WDR,intelligence 3D noise reduction.Micro SD card(max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 1000M Gigabit RJ45. Built-in PoE, 3-12mm varifocal lens, No AC/DC adapter. IP66	√	3-12mm	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6 5. SFP fiber port: \$40 6. SFP module: optional
	SC6B21Z-H5D	2 Megapixel 1080P@25fps H.265 Super Low Light Outdoor IR Bullet IP Camera, 1920*1280@25fps, Sony Exmor R 1/1.8" CMOS sensor IMX178LQJ+Hisilicon Hi3516A, H.265 Encode, MP, BP. Starlight level super low light, Digital WDR,intelligence 3D noise reduction.Micro SD card(max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 1000M Gigabit RJ45. Built-in PoE, 3-12mm motorized zoom lens, No AC/DC adapter. IP66	√	3-12mm Motorized Zoom	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6 5. SFP fiber port: \$40 6. SFP module: optional
	SC6B31	3 Megapixel Real Time 25fps H.265 WDR Outdoor IR Bullet IP Camera, 2048*1520@25fps,1/3" WDR CMOS sensor, H.265 Encode, MP, BP. Optical WDR, intelligence 3D noise reduction.Micro SD card(max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 1000M Gigabit RJ45. Built-in PoE, 12mm fixed lens, No AC/DC adapter. IP66	√	12mm	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6

 H.265 WD 3MP@25fps	SC6B31-T12	3 Megapixel Real Time 25fps H.265 WDR Outdoor IR Bullet IP Camera , 2048*1520@25fps, 1/3" WDR CMOS sensor, H.265 Encode, MP, BP. Optical WDR, intelligence 3D noise reduction. Micro SD card(max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 1000M Gigabit RJ45. Built-in PoE, 3-12mm varifocal lens, No AC/DC adapter. IP66		√	3-12mm	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6
 H.265 WD 4MP@25fps	SC6B41	4 Megapixel Real Time 25fps H.265 Outdoor IR Bullet IP Camera , 2592*1920@25fps, 1/3" WDR CMOS sensor, H.265 Encode, MP, BP. Optical WDR, intelligence 3D noise reduction. Micro SD card(max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 1000M Gigabit RJ45. Built-in PoE, 12mm fixed lens, No AC/DC adapter. IP66		√	12mm	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6
 H.265 4MP@25fps	SC6B41-T12	4 Megapixel Real Time 25fps H.265 Outdoor IR Bullet IP Camera , 2592*1920@25fps, 1/3" WDR CMOS sensor, H.265 Encode, MP, BP. Optical WDR, intelligence 3D noise reduction. Micro SD card(max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 1000M Gigabit RJ45. Built-in PoE, 3-12mm varifocal lens, No AC/DC adapter. IP66		√	3-12mm	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6
 H.265 4MP@25fps	SC6B41Z	4 Megapixel Real Time 25fps H.265 Outdoor IR Bullet IP Camera , 2592*1920@25fps, 1/3" WDR CMOS sensor, H.265 Encode, MP, BP. Optical WDR, intelligence 3D noise reduction. Micro SD card(max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 1000M Gigabit RJ45. Built-in PoE, 2.8-12mm motorized zoom & auto focus lens, No AC/DC adapter. IP66		√	2.8-12mm Motorized Zoom	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6
 H.265 5MP@25fps	SC6B51-H5-T12	5 Megapixel Real Time 25fps H.265 Super Low Light Outdoor IR Bullet IP Camera , 2592*1920@25fps, Sony Exmor R 1/1.8" CMOS sensor IMX178LQJ+Hisilicon Hi3516A, H.265 Encode, MP, BP. Super low light, Digital WDR, intelligence 3D noise reduction. Micro SD card(max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 1000M Gigabit RJ45. Built-in PoE, 3-12mm varifocal lens, No AC/DC adapter. IP66		√	3-12mm	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6
 H.265 5MP@25fps Zoom	SC6B50Z-H5	5 Megapixel Real Time 25fps H.265 Super Low Light Outdoor IR Bullet IP Camera , 2592*1920@25fps, Sony Exmor R 1/1.8" CMOS sensor IMX178LQJ+Hisilicon Hi3516A, H.265 Encode, MP, BP. Super low light, Digital WDR, intelligence 3D noise reduction. Micro SD card(max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 1000M Gigabit RJ45. No PoE, 3-12mm motorized zoom lens, No AC/DC adapter. IP66		X	3-12mm Motorized Zoom	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6

	SC6B51Z-H5	5 Megapixel Real Time 25fps H.265 Super Low Light Outdoor IR Bullet IP Camera 2592*1920@25fps, Sony Exmor R 1/1.8" CMOS sensor IMX178LQJ+Hisilicon Hi3516A, H.265 Encode, MP, BP. Super low light, Digital WDR,intelligence 3D noise reduction.Micro SD card(max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 1000M Gigabit RJ45. Built-in PoE, 3-12mm motorized zoom lens, No AC/DC adapter. IP66		√	3-12mm Motorized Zoom	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6
---	------------	--	--	---	-----------------------	---------	---	--

Vandal Proof IK10 Big IR Bullet IP Camera (IR distance 80-100m, IR can be removed, 100/1000M Ethernet, -40 °C ~ 60°C, IP66. PoE is optional)

	SC6B11BF-L12	1.3 Megapixel H.264 Vandal Proof IR Bullet IP Camera. 1280*960@25fps,Sony Exmor 1/2.8" CMOS sensor, H.264 HP, MP, BP,super low light, Digital WDR, intelligence 3D noise reduction, 6 IR led lights,Max 100m, Dual Micro SD card slot, audio & alarm input/output, RS485. Built-in PoE, 12mm fixed Lens, No AC/DC adapter.	√	12mm	80-100m	√	1. 6/8/12/16mm Lens: free 2.3G: \$79 3.4G: \$139 4. AC/DC Adapter: \$7 5. Wall installation bracket:\$6
	SC6B11BF-T12	1.3 Megapixel H.264 Vandal Proof IR Bullet IP Camera. 1280*960@25fps,Sony Exmor 1/2.8" CMOS sensor, H.264 HP, MP, BP,super low light, Digital WDR, intelligence 3D noise reduction, 6 IR led lights,Max 100m,Dual Micro SD card slot, audio & alarm input/output, RS485. Built-in PoE, 2.8-12mm varifocal Lens, No AC/DC adapter.	√	2.8-12mm	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6
	SC6B11BFZ	1.3 Megapixel H.264 Vandal Proof IR Bullet IP Camera. 1280*960@25fps, 1/2.8" Sony Exmor CMOS sensor, H.264 Encode, MP, BP. Super low light,digital WDR. Micro SD card(max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 100M RJ45. Built-in PoE, 2.8-12mm motorized motorized zoom & auto focus lens, No AC/DC adapter. IP66.	√	2.8-12mm Motorized Zoom	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6
	SC6B11BF-T72	1.3 Megapixel H.264 Vandal Proof IR Bullet IP Camera. 1280*960@25fps, 1/2.8" Sony Exmor CMOS sensor, H.264 Encode, MP, BP. Super low light,digital WDR. Micro SD card(max 64G). 6 IR led lights, Max 80-100m,Dual Micro SD card slot, audio & alarm input/output, RS485, 100M RJ45. Built-in PoE, 7-22mm varifocal lens, No AC/DC adapter. IP66.	√	7-22mm	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6
	SC6B11BFZ-T72	1.3 Megapixel H.264 Vandal Proof IR Bullet IP Camera. 1280*960@25fps, 1/2.8" Sony Exmor CMOS sensor, H.264 Encode, MP, BP. Super low light,digital WDR. Micro SD card(max 64G). 6 IR led lights, Max 80-100m,Dual Micro SD card slot, audio & alarm input/output, RS485, 100M RJ45. Built-in PoE, 7-22mm motorized zoom & auto focus lens, No AC/DC adapter. IP66.	√	7-22mm Motorized Zoom	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6
	SC6B21F-L12	2 Megapixel 1080P H.264 Vandal Proof IR Bullet IP Camera. 1920*1080@25fps,Sony Exmor 1/2.8" CMOS sensor, H.264 HP, MP, BP,super low light, Digital WDR, intelligence 3D noise reduction, 6 IR led lights,Max 100m, Dual Micro SD card slot, audio & alarm input/output, RS485. Built-in PoE, 12mm fixed Lens, No AC/DC adapter.	√	12mm	80-100m	√	1. 6/8/12/16mm Lens: free 2.3G: \$79 3.4G: \$139 4. AC/DC Adapter: \$7 5. Wall installation bracket:\$6
	SC6B21F-T12	2 Megapixel 1080P H.264 IK10 Vandal Proof IR Bullet IP Camera. 1920*1080@25fps,Sony Exmor 1/2.8" CMOS sensor, H.264 HP, MP, BP,super low light, Digital WDR, intelligence 3D noise reduction, 6 IR led lights,Max 100m, Dual Micro SD card slot, audio & alarm input/output, RS485. Built-in PoE, 2.8-12mm varifocal Lens, IK10 Vandal Proof. No AC/DC adapter.	√	2.8-12mm	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6

	SC6B21FZ	2 Megapixel 1080P Vandal Proof IR Bullet IP Camera. 1920*1080@25fps, 1/2.8" Sony Exmor CMOS sensor , H.264 Encode, MP, BP. Super low light,digital WDR. Micro SD card(max 64G). 6 IR led lights, Max 80-100m, Dual Micro SD card slot, audio & alarm input/output, RS485, 100M RJ45. Built-in PoE, 2.8-12mm motorized zoom lens, No AC/DC adapter. IP66.		√	2.8-12mm Motorized Zoom	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6
	SC6B21F-T72	2 Megapixel 1080P H.264 Vandal Proof IR Bullet IP Camera. 1920*1080@25fps, 1/2.8" Sony Exmor CMOS sensor , H.264 Encode, MP, BP. Super low light,digital WDR. Dual Micro SD card(max 64G). 6 IR led lights, Max 80-100m, Dual Micro SD card slot, audio & alarm input/output, RS485, 100M RJ45. Built-in PoE, 7-22mm varifocal lens, No AC/DC adapter. IP66.		√	7-22mm	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6
	SC6B21FZ-T72	2 Megapixel 1080P H.264 Vandal Proof IR Bullet IP Camera. 1920*1080@25fps, 1/2.8" Sony Exmor CMOS sensor , H.264 Encode, MP, BP. Super low light,digital WDR. Micro SD card(max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 100M RJ45. Built-in PoE, 7-22mm motorized zoom lens, No AC/DC adapter. IP66.		√	7-22mm Motorized Zoom	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6
	SC6B21F-H5-L12	2 Megapixel 1080P@25fps H.265 Vandal Proof IR Bullet IP Camera. 1920*1080@25fps, 1/2.8" Sony Exmor CMOS sensor + Hisilicon Hi3516D, H.265 Encode, MP, BP. Super low light,digital WDR. Dual Micro SD card(max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 100M RJ45. Built-in PoE, 12mm fixed lens, No AC/DC adapter. IP66		√	12mm	80-100m	√	1. 6/8/12/16mm Lens: free 2.3G: \$79 3.4G: \$139 4. AC/DC Adapter: \$7 5. Wall installation bracket:\$6
	SC6B21F-H5-T12	2 Megapixel 1080P@25fps H.265 Vandal Proof IR Bullet IP Camera. 1920*1080@25fps, 1/2.8" Sony Exmor CMOS sensor + Hisilicon Hi3516D, H.265 Encode, MP, BP. Super low light,digital WDR. Dual Micro SD card(max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 100M RJ45. Built-in PoE, 2.8-12mm varifocal lens, No AC/DC adapter. IP66		√	2.8-12mm	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6
	SC6B21FZ-H5	2 Megapixel 1080P@25fps H.265 Vandal Proof IR Bullet IP Camera. 1920*1080@25fps, 1/2.8" Sony Exmor CMOS sensor + Hisilicon Hi3516D, H.265 Encode, MP, BP. Super low light,digital WDR. Micro SD card(max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 100M RJ45. Built-in PoE, 2.8-12mm motorized zoom lens, No AC/DC adapter. IP66		√	2.8-12mm Motorized Zoom	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6
	SC6B21F-H5-T72	2 Megapixel 1080P@25fps H.265 Vandal Proof IR Bullet IP Camera. 1920*1080@25fps, 1/2.8" Sony Exmor CMOS sensor + Hisilicon Hi3516D, H.265 Encode, MP, BP. Super low light,digital WDR. Micro SD card(max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 100M RJ45. Built-in PoE, 7-22mm varifocal lens, No AC/DC adapter. IP66		√	7-22mm	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6

	SC6B21FZ-H5-T72	2 Megapixel 1080P@25fps H.265 Vandal Proof IR Bullet IP Camera. 1920*1080@25fps, 1/2.8" Sony Exmor CMOS sensor + Hisilicon Hi3516D, H.265 Encode, MP, BP. Super low light,digital WDR. Dual Micro SD card(max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 100M RJ45. Built-in PoE, 7-22mm motorized zoom lens, No AC/DC adapter. IP66	√	7-22mm Motorized Zoom	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6
	SC6B21FZ-H5W	2 Megapixel 1080P@25fps H.265 Super WDR Vandal Proof IR Bullet IP Camera. 1920*1080@25fps, 1/2.8" Machine Vision CMOS sensor + Hisilicon Hi3516D, H.265 Encode, MP, BP. Multiple Exposure 130dB Super WDR, Star light level Super low light, ,Highlight Compensation (HLC). Micro SD card(max 64G). 6 IR led lights, Max 80-100m, Dual Micro SD card slot, audio & alarm input/output, RS485, 1000M Gigabit RJ45. Built-in PoE, 2.8-12mm motorized zoom lens, No AC/DC adapter. IP66	√	3-12mm Motorized Zoom	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6
	SC6B21FZ-H5W-T72	2 Megapixel 1080P@25fps H.265 Super WDR Vandal Proof IK10 IR Bullet IP Camera. 1920*1080@25fps, 1/2.8" Machine Vision CMOS sensor + Hisilicon Hi3516D, H.265 Encode, MP, BP. Multiple Exposure 130dB Super WDR, Star light level Super low light, ,Highlight Compensation (HLC). Micro SD card(max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 1000M Gigabit RJ45. Built-in PoE, 7-22mm motorized zoom lens, No AC/DC adapter. IP66	√	7-22mm Motorized Zoom	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6
	SC6B21F-H5D-T12	2 Megapixel 1080P@25fps H.265 Super Low Light Vandal Proof Outdoor IR Bullet IP Camera, 1920*1280@25fps, Sony Exmor R 1/1.8" CMOS sensor IMX178LQJ+Hisilicon Hi3516A, H.265 Encode, MP, BP. Starlight Super low light, Digital WDR,intelligence 3D noise reduction.Dual Micro SD card(max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 1000M Gigabit RJ45. Built-in PoE, 3-12mm varifocal lens, No AC/DC adapter. IP66	√	3-12mm	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6
	SC6B21FZ-H5D	2 Megapixel 1080P@25fps H.265 Super Low Light Vandal Proof Outdoor IR Bullet IP Camera, 1920*1280@25fps, Sony Exmor R 1/1.8" CMOS sensor IMX178LQJ+Hisilicon Hi3516A, H.265 Encode, MP, BP. Starlight Super low light, Digital WDR,intelligence 3D noise reduction.Micro SD card(max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 1000M Gigabit RJ45. Built-in PoE, 3-12mm motorized zoom lens, No AC/DC adapter. IP66	√	3-12mm Motorized Zoom	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6
	SC6B21F-H5W-T72	2 Megapixel 1080P@25fps H.265 Super WDR Vandal Proof IR Bullet IP Camera. 1920*1080@25fps, 1/2.8" Machine Vision CMOS sensor + Hisilicon Hi3516D, H.265 Encode, MP, BP. Multiple Exposure 130dB Super WDR, Star light level Super low light, ,Highlight Compensation (HLC). Dual Micro SD card(max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 1000M Gigabit RJ45. Built-in PoE, 7-22mm varifocal lens, No AC/DC adapter. IP66	√	7-22mm	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket:\$6

	SC6B21FI-L12	2 Megapixel 1080P H.264 Vandal Proof Intelligent Bullet IP Camera without IR. 1920*1080@25fps, Sony Exmor 1/2.8" CMOS sensor, support Perimeter intrusion, tripwire, etc intelligent analysis. H.264 HP, MP, BP, super low light, Digital WDR, intelligence 3D noise reduction. Dual Micro SD card slot, audio & alarm input/output, RS485. Built-in PoE, No IR light, 12mm fixed Lens, No AC/DC adapter.	√	12mm	X	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket: \$6
	SC6B31F	3 Megapixel Real Time 25fps H.265 Vandal Proof Outdoor IR Bullet IP Camera, 2048*1520@25fps, 1/3" WDR CMOS sensor, H.265 Encode, MP, BP. Optical WDR, intelligence 3D noise reduction. Dual Micro SD card (max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 1000M Gigabit RJ45. Built-in PoE, fixed 12mm fixed lens, No AC/DC adapter. IP66	√	12mm	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket: \$6
	SC6B41F	4 Megapixel Real Time 25fps H.265 Vandal Proof Outdoor IR Bullet IP Camera, 2592*1920@25fps, 1/3" WDR CMOS sensor, H.265 Encode, MP, BP. Optical WDR, intelligence 3D noise reduction. Micro SD card (max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 1000M Gigabit RJ45. Built-in PoE, fixed 12mm fixed lens, No AC/DC adapter. IP66	√	12mm	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket: \$6
	SC6B51F-H5-T12	5 Megapixel Real Time 25fps H.265 Super Low Light Vandal Proof Outdoor IR Bullet IP Camera, 2592*1920@25fps, Sony Exmor R 1/1.8" CMOS sensor IMX178LQJ+Hisilicon Hi3516A, H.265 Encode, MP, BP. Super low light, Digital WDR, intelligence 3D noise reduction. Dual Micro SD card (max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 1000M Gigabit RJ45. Built-in PoE, 3-12mm varifocal lens, No AC/DC adapter. IP66	√	3-12mm	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket: \$6
	SC6B51FZ-H5	5 Megapixel Real Time 25fps H.265 Super Low Light Vandal Proof IK10 Outdoor IR Bullet IP Camera, 2592*1920@25fps, Sony Exmor R 1/1.8" CMOS sensor IMX178LQJ+Hisilicon Hi3516A, H.265 Encode, MP, BP. Super low light, Digital WDR, intelligence 3D noise reduction. Dual Micro SD card (max 64G). 6 IR led lights, Max 80-100m, Micro SD card slot, audio & alarm input/output, RS485, 1000M Gigabit RJ45, Built-in PoE, 3-12mm motorized zoom lens, No AC/DC adapter. IP66	√	3-12mm Motorized Zoom	80-100m	√	1. 3G: \$79 2. 4G: \$139 3. AC/DC Adapter: \$7 4. Wall installation bracket: \$6
H.264 Indoor Dome Metal IP Camera, fixed lens, IR distance: 20-30m, PoE & Audio is optional, if don't need PoE, it can support alarm & audio							
	SC6911	1.3 Megapixel 960P@25fps H.264 Indoor IR PoE Metal Fixed Dome IP Camera. 1280*960, Sony Exmor 1/3" CMOS sensor, super low light, Digital WDR, intelligence 3D noise reduction. Built-in PoE, 2 IR Light, No AC/DC Adapter, 3.6mm Fixed Lens. Metal Housing.	√	3.6mm	20-30m	X	1. 2.8/3.6/6mm Lens: free 2. AC/DC Adapter: \$6 3. Audio Interface Board: \$6

	SC6920	2 Megapixel 1080P@25fps H.264 Indoor IR PoE Metal Fixed Dome IP Camera. 1920x1080, Sony Exmor 1/2.8" CMOS sensor, super low light, Digital WDR, intelligence 3D noise reduction. 2 IR Light, No PoE, No AC/DC Adapter, 3.6mm Fixed Lens. Metal Housing.		X	3.6mm	20-30m	X	1. 2.8/3.6/6mm Lens: free 2. AC/DC Adapter: \$6 3. Audio,Alarm Input/Output: \$6
 	SC6921	2 Megapixel 1080P@25fps H.264 Indoor IR PoE Metal Fixed Dome IP Camera. 1920*1080, Sony Exmor 1/2.8" CMOS sensor, super low light, Digital WDR, intelligence 3D noise reduction. Built-in PoE, 2 IR Light, No AC/DC Adapter, 3.6mm Fixed Lens. Metal Housing.		√	3.6mm	20-30m	X	1. 2.8/3.6/6mm Lens: free 2. AC/DC Adapter: \$6 3. Audio Interface Board: \$6
H.265/H.264 Indoor Dome Metal IP Camera, fixed lens, IR distanc: 20-30m, PoE & Audio is optional, if don't need PoE, it can support alarm & audio								
	SC6941	4 Megapixel Real Time 25fps H.265 /H.264 Indoor IR Metal Fixed Dome PoE IP Camera, 2592*1920@25fps, 1/3" WDR CMOS sensor, H.265/H.264/MJPEG Encoding. Optical WDR,intelligence 3D noise reduction. Built-in PoE, 2 IR Light, No AC/DC Adapter, 3.6mm Fixed Lens. Metal Housing.		√	3.6mm	20-30m	X	1. 2.8/3.6/6mm Lens: free 2. AC/DC Adapter: \$6 3. Audio Interface Board: \$6
	SC6931	3 Megapixel Real Time 25fps H.265/H.264 Indoor IR Metal Fixed Dome PoE IP Camera, 2048*1520@25fps, 1/3" WDR CMOS sensor, H.265/H.264/MJPEG Encoding. Optical WDR,intelligence 3D noise reduction. Built-in PoE, 2 IR Light, No AC/DC Adapter, 3.6mm Fixed Lens. Metal Housing.		√	3.6mm	20-30m	X	1. 2.8/3.6/6mm Lens: free 2. AC/DC Adapter: \$6 3. Audio Interface Board: \$6
	SC6921-H5	2 Megapixel 25fps H.265/H.264 Super Low light Indoor IR Metal Fixed Dome PoE IP Camera, 1920*1080@25fps, Sony Exmor 1/2.8" CMOS sensor, CPU 900MHZ, H.264 HP, MP, BP.super low light, Digital WDR, intelligence 3D noise reduction. Built-in PoE, 2 IR Light, No AC/DC Adapter, 3.6mm Fixed Lens. Metal Housing.		√	3.6mm	20-30m	X	1. 2.8/3.6/6mm Lens: free 2. AC/DC Adapter: \$6 3. Audio Interface Board: \$6
	SC6921-H5W	2 Megapixel 25fps H.265/H.264 Super WDR Indoor IR Metal Fixed Dome PoE IP Camera, 1920*1080@25fps, 1/2.8" Machine Vision CMOS sensor + Hisilicon Hi3516D, H.265/H.264/MJPEG Encoding. Multiple Exposure 130dB Super WDR, Star light level Super low light,Highlight Compensation (HLC). Built-in PoE, 2 IR Light, No AC/DC Adapter, 3.6mm Fixed Lens. Metal Housing.		√	3.6mm	20-30m	X	1. 2.8/3.6/6mm Lens: free 2. AC/DC Adapter: \$6 3. Audio Interface Board: \$6
H.265/H.264 Indoor/Outdoor Vandal Proof Waterproof Metal Dome IP Camera, varifocal lens, IR distanc: 20-30m								
	SC6J21-H5	H.265/H.264 2 Megapixel 1080P Vandal Proof Dome PoE IP Camera H.265/H.264, 1920x1080@25fps, Sony IMX322 2 Megapixel sensor + Hi3516D SoC chip, 2.8-12mm varifocal lens, 24 pcs LED light, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. IP66 waterproof, IK10 vandal proof.		√	2.8-12mm	20-30m	IP66	1. AC/DC Adapter: \$6 2. Audio input/output: \$5 3.Audio,Alarm Input/Output: \$7

 Super WDR Starlight	SC6J21-H5W	H.265/H.264 2 Megapixel 1080P Super WDR Vandal Proof Dome PoE IP Camera H.265/H.264 , 1920x1080@25fps, 1/2.8" Machine Vision CMOS sensor + Hisilicon Hi3516D, H.265 Encode, MP, BP. Multiple Exposure 130dB Super WDR , Star light level Super low light, Highlight Compensation (HLC). 2.8-12mm varifocal lens, 24 pcs LED light, ONVIF; DC12V, Built-in PoE , No AC/DC adapter. IP66 waterproof, IK10 vandal proof.	√	2.8-12mm	20-30m	IP66	1. AC/DC Adapter: \$6 2. Audio input/output: \$5 3. Audio, Alarm Input/Output: \$7
 H.265 4MP@25fps WDR	SC6J41	4 Megapixel 25fps H.265 / H.264 Vandal Proof Indoor / Outdoor Dome IR PoE IP Camera. 2592*1520@25fps, 1/3" WDR CMOS sensor, H.265 Encode, Optical WDR, IP66 Waterproof, IK10 Vandal Proof Dome, Built-in PoE, SD card, 24 pcs LED IR Light, IR 20-30m, No AC/DC Adapter. 2.8-12mm Varifocal Lens.	√	2.8-12mm	20-30m	IP66	1. AC/DC Adapter: \$6 2. Audio input/output: \$5 3. Audio, Alarm Input/Output: \$7
 H.265 3MP@25fps WDR	SC6J31	3 Megapixel 25fps H.265 / H.264 Vandal Proof Indoor / Outdoor Dome IR PoE IP Camera. 2048*1520@25fps, 1/3" WDR CMOS sensor, H.265 Encode, Optical WDR, IP66 Waterproof, IK10 Vandal Proof Dome, Built-in PoE, SD card, 24 pcs LED IR Light, IR 20-30m, No AC/DC Adapter. 2.8-12mm Varifocal Lens.	√	2.8-12mm	20-30m	IP66	1. AC/DC Adapter: \$6 2. Audio input/output: \$5 3. Audio, Alarm Input/Output: \$7
Indoor Dome Plastic IP Camera, fixed/varifocal lens, built-in alarm & audio input/output, RS232. IR-light is optional							
 Hot	SC6211B	1.3 Megapixel 960P@25fps H.264 Indoor IR PoE Dome IP Camera. 1280*960, Sony Exmor 1/3" CMOS sensor, super low light, Digital WDR, intelligence 3D noise reduction. Built-in PoE, IR Light, No AC/DC Adapter. 2.8-12mm Varifocal Lens. Alarm, audio input/output, RS232.	√	2.8-12mm	√	X	1. AC/DC Adapter: \$6
 Hot	SC6221A	2 Megapixel 1080P@25fps H.264 Indoor Dome IP Camera. 1920*1080, Sony Exmor 1/2.8" CMOS sensor, CPU 500MHZ, H.264 MP, BP. super low light, Digital WDR, intelligence 3D noise reduction. SD card, Built-in PoE, IR Light, No AC/DC Adapter. 2.8-12mm Varifocal Lens. Alarm, audio input/output, RS232.	√	2.8-12mm	√	X	1. AC/DC Adapter: \$6
 H. 265	SC6220A-H5	2 Megapixel 1080P@25fps H.265 / H.264 Indoor Dome IP Camera. 1920*1080@25fps, Sony Exmor 1/2.8" CMOS sensor, CPU 900MHZ, H.264 HP, MP, BP. super low light, Digital WDR, intelligence 3D noise reduction. SD card, No IR Light, No PoE, No AC/DC Adapter. 4mm Fixed Lens. alarm, audio input/output, RS232.	X	4mm	X	X	1. 2.8/4/6/8/12mm Lens: free 2. AC/DC Adapter: \$6 3. PoE: \$7 4. IR: \$6
 H. 265	SC6221-H5	2 Megapixel 1080P@25fps H.265 / H.264 Indoor Dome IP Camera. 1920*1080@25fps, Sony Exmor 1/2.8" CMOS sensor, CPU 900MHZ, H.264 HP, MP, BP. super low light, Digital WDR, intelligence 3D noise reduction. SD card, IR Light, Built-in PoE, No AC/DC Adapter. 2.8-12mm Varifocal Lens. alarm, audio input/output, RS232.	√	2.8-12mm	√	X	1. 2.8/4/6/8/12mm Lens: free 2. AC/DC Adapter: \$6

 Hot	SC6711B	1.3 Megapixel 960P Indoor/Outdoor Vandal Proof Metal Mini Dome PoE IP Camera 1280*960, Sony Exmor 1/3" CMOS sensor, super low light, Digital WDR, intelligence 3D noise reduction, SD card. Mini Vandal Proof Dome, Built-in PoE, Fixed 3.6mm M12 Lens, No AC/DC adapter.		√	3.6mm	X	√	1. 2.8mm M12 Lens: free 2. AC/DC Adapter: \$4
 Hot	SC6721	2.0 Megapixel 1080P Indoor/Outdoor Vandal Proof Metal Mini Dome PoE IP Camera 1920*1080, Sony Exmor 1/2.8" CMOS sensor, super low light, Digital WDR, intelligence 3D noise reduction, SD card. Mini Vandal Proof Dome, Built-in PoE, Fixed 2.8mm M12 Lens, No AC/DC adapter.		√	3.6mm	X	√	1. 2.8mm M12 Lens: free 2. AC/DC Adapter: \$4
 Hot	SC6711B-IR	1.3 Megapixel 960P Indoor/Outdoor Vandal Proof Metal Mini IR Dome PoE IP Camera 1280*960, Sony Exmor 1/3" CMOS sensor, super low light, Digital WDR, intelligence 3D noise reduction, SD card. Mini Vandal Proof Dome, Built-in PoE, Built in IR Fixed 3.6mm M12 Lens, No AC/DC adapter.		X	3.6mm	5-10m	√	1. 2.8mm M12 Lens: free 2. AC/DC Adapter: \$4 3. Audio: \$4 4. Audio & Alarm: \$7
 Hot	SC6721-IR	2.0 Megapixel 1080P Indoor/Outdoor Vandal Proof Metal Mini IR Dome PoE IP Camera 1920*1080, Sony Exmor 1/2.8" CMOS sensor, super low light, Digital WDR, intelligence 3D noise reduction, SD card. Mini Vandal Proof Dome, Built-in PoE, Built -in IR .Fixed 2.8mm M12 Lens, No AC/DC adapter.		√	3.6mm	5-10m	√	1. 2.8mm M12 Lens: free 2. AC/DC Adapter: \$4 3. Audio: \$4 4. Audio & Alarm: \$7
Indoor/Outdoor Vandal Proof Metal Dome IP Camera, fixed/varifocal lens, IR distanc: 20-30m, audio & alarm is optional								
 Hot	SC6311	1.3 Megapixel 960P@25fps H.264 Vandal Proof Indoor / Outdoor Dome IP Camera. 1280*960, Sony Exmor 1/3" CMOS sensor, CPU 500MHZ, H.264 MP, BP.super low light, Digital WDR, intelligence 3D noise reduction. SD card, audio, alarm,RS232. Vandal Proof Dome, Built-in PoE, IR Light, No AC/DC Adapter. 2.8-12mm Varifocal Lens. IP66 Waterproof, IK10 Vandal Proof.		√	2.8-12mm	√	√	1. AC/DC Adapter: \$6
	SC6321A	2 Megapixel 1080P@25fps H.265 / H.264 Vandal Proof Indoor Dome IP Camera. 1920*1080, Sony Exmor 1/2.8" CMOS sensor, CPU 500MHZ, H.264 HP, MP, BP.super low light, Digital WDR, intelligence 3D noise reduction.SD card, audio, alarm, RS232. Vandal Proof Dome, Built-in PoE, No IR Light, No AC/DC Adapter.2.8mm Fixed Lens. IP66 Waterproof, IK10 Vandal Proof.		√	2.8mm	X	√	1. AC/DC Adapter: \$6
 H. 265	SC6321A-H5	2 Megapixel 1080P@25fps H.265 / H.264 Vandal Proof Indoor Dome IP Camera. 1920*1080, Sony Exmor 1/2.8" CMOS sensor, H.265 HP, MP, BP.super low light, Digital WDR, intelligence 3D noise reduction.SD card, audio, alarm. RS232 Vandal Proof Dome, Built-in PoE, No IR Light, No AC/DC Adapter. 4mm Fixed Lens. Vandal Proof, Alarm, audio input/output, RS232.		√	4mm	X	X	1. 6/8/12mm fixed lens: free 2. 2.8-12mm varifocal lens: \$3 3. IR-light: \$5 4. AC/DC Adapter: \$6

 H.265	SC6321-H5	2 Megapixel 1080P@25fps H.265 / H.264 Vandal Proof Indoor / Outdoor Dome IP Camera. 1920*1080, Sony Exmor 1/2.8" CMOS sensor, H.265 HP, MP, BP.super low light, Digital WDR, intelligence 3D noise reduction.SD card, audio, alarm. RS232 Vandal Proof Dome, Built-in PoE, IR Light, No AC/DC Adapter.2.8-12mm Varifocal Lens. IP66 Waterproof, IK10 Vandal Proof.		√	2.8-12mm	√	√	1. 4/6/8mm Lens: free 2. AC/DC Adapter: \$6
	SC6321	2 Megapixel 1080P@25fps H.265 / H.264 Vandal Proof Indoor / Outdoor Dome IP Camera. 1920*1080, Sony Exmor 1/2.8" CMOS sensor, CPU 900MHZ , H.264 HP, MP, BP.super low light, Digital WDR, intelligence 3D noise reduction.SD card, audio, alarm, RS232. Vandal Proof Dome, Built-in PoE, IR Light, No AC/DC Adapter.2.8-12mm Varifocal Lens. IP66 Waterproof, IK10 Vandal Proof.		√	2.8-12mm	√	√	1. AC/DC Adapter: \$6
 Zoom	SC6321A-ZF	2 Megapixel 1080P@25fps H.265 / H.264 Vandal Proof Indoor / Outdoor Dome IP Camera. 1920*1080, 4X Optical Zoom , Sony Exmor 1/2.8" CMOS sensor, CPU 500MHZ, H.264 HP, MP, BP.super low light, Digital WDR, intelligence 3D noise reduction.SD card, audio, alarm, RS232. Vandal Proof Dome, Built-in PoE, IR Light, No AC/DC Adapter.2.8-12mm Motorized Zoom & Auto Focus Lens. IP66 Waterproof, IK10 Vandal Proof.		√	2.8-12mm Motorized Zoom & Auto Focus	√	√	1. AC/DC Adapter: \$6
 H.265 3MP@25fps WDR	SC6331A	3 Megapixel 25fps H.265 / H.264 Indoor Dome IP Camera. 2048*1520@25fps, 1/3" WDR CMOS sensor, H.265 Encode, Optical WDR, IK10 Vandal Proof Dome, Built-in PoE, SD card, No IR Light, No AC/DC Adapter. 4mm Fixed Lens. Alarm, audio input/output, RS232.		√	4mm	X	X	1. 4/6/8mm Lens: free 2. AC/DC Adapter: \$6 3. IR light: \$6
 H.265 3MP@25fps WDR	SC6331B	3 Megapixel 25fps H.265 / H.264 Indoor/Outdoor Dome IP Camera. 2048*1520@25fps, 1/3" WDR CMOS sensor, H.265 Encode, Optical WDR, IK10 Vandal Proof Dome, Built-in PoE, SD card, 2 array LED IR Light, No AC/DC Adapter.2.8-12mm Varifocal Lens. IP66 Waterproof, Alarm, audio input/output, RS232.		√	2.8-12mm	20-30m	√	1. 4/6/8mm Lens: free 2. AC/DC Adapter: \$6
 H.265 4MP@25fps WDR	SC6341A	4 Megapixel 25fps H.265 / H.264 Vandal Proof Indoor Dome IP Camera. 2592*1520@25fps, 1/3" WDR CMOS sensor, H.265 Encode, Optical WDR, IK10 Vandal Proof Dome, Built-in PoE, SD card, No IR Light, No AC/DC Adapter. 4mm Fixed Lens. Alarm, audio input/output, RS232.		√	4mm	X	X	1. 4/6/8mm Lens: free 2. AC/DC Adapter: \$6 3. IR light: \$6
 H.265 4MP@25fps WDR	SC6341B	4 Megapixel 25fps H.265 / H.264 Vandal Proof Indoor / Outdoor Dome IP Camera. 2592*1520@25fps, 1/3" WDR CMOS sensor, H.265 Encode, Optical WDR, IP66 Waterproof, IK10 Vandal Proof.Dome, Built-in PoE, SD card, 2 array LED IR Light, No AC/DC Adapter.2.8-12mm Varifocal Lens. Alarm, audio input/output, RS232.		√	2.8-12mm	20-30m	√	1. 4/6/8mm Lens: free 2. AC/DC Adapter: \$6

	SC6321A-H5W	2 Megapixel 1080P@25fps H.265 / H.264 Super WDR Vandal Proof Dome IP Camera. 1920*1080@25fps, 1/2.8" Machine Vision CMOS sensor + Hisilicon Hi3516D, H.265 Encode, MP, BP. Multiple Exposure 130dB Super WDR, Star light level Super low light, Highlight Compensation (HLC). SD card, audio, alarm. Vandal Proof Dome, Built-in PoE, No IR Light, No AC/DC Adapter. 4mm Varifocal Lens. Alarm, audio input/output, RS232.		√	4mm	X	X	1. 4/6/8mm Lens: free 2. AC/DC Adapter: \$6 3. 2.8-12mm: \$3 4. IR light: \$6
	SC6321-H5W	2 Megapixel 1080P@25fps H.265 Super WDR Vandal Proof Dome IP Camera. 1920*1080@25fps, 1/2.8" Machine Vision CMOS sensor + Hisilicon Hi3516D, H.265 Encode, MP, BP. Multiple Exposure 130dB Super WDR, Star light level Super low light, Highlight Compensation (HLC). SD card, audio, alarm. Vandal Proof Dome, Built-in PoE, IR Light, No AC/DC Adapter. 2.8-12mm Varifocal Lens. Waterproof, Alarm, audio input/output, RS232.		√	2.8-12mm	20-30m	√	1. 4/6/8mm Lens: free 2. AC/DC Adapter: \$6
	SC6321Z-H5W	2 Megapixel 1080P@25fps H.265 / H.264 Super WDR Vandal Proof Dome IP Camera. 1920*1080@25fps, 1/2.8" Machine Vision CMOS sensor + Hisilicon Hi3516D, H.265 Encode, MP, BP. Multiple Exposure 130dB Super WDR, Star light level Super low light, Highlight Compensation (HLC). SD card, audio, alarm. Vandal Proof Dome, Built-in PoE, IR Light, No AC/DC Adapter. 2.8-12mm Motorized Zoom & Auto focus Lens. Waterproof, Alarm, audio input/output, RS232.		√	2.8-12mm Motorized Zoom & Auto focus	20-30m	√	1. 4/6/8mm Lens: free 2. AC/DC Adapter: \$6
Traffic Road Application High Speed IP Camera (the car speed <=50km/h)								
	SC6B20-G21H	H.265/H.264 1/1.8" 2 Megapixel Starlight Super Lux LED Bullet IP Camera for Traffic Road Plate License Recognition application. 1920*1080@25fps, 1/1.8" CMOS sensor Super low light, digital WDR. 6 LED white lights, Max 80-100m, Micro SD card slot (64G), audio & alarm input/output, RS485, 1000M RJ45. 25mm Fixed lens, Built-in Chinese Plate License Recognition, No AC/DC adapter, No PoE. IP66 water proof		X	25mm	80m	IP66	
	SC6B20-G21C	H.265/H.264 1/2.8" 2 Megapixel High Speed Sensor LED White Light Bullet IP Camera for Parking Lot Plate License Recognition application. 1920*1080@25fps, 1/2.8" High Speed CMOS sensor Super low light, digital WDR. 6 LED white lights, Max 80-100m, Micro SD card slot (64G), audio & alarm input/output, RS485, 1000M RJ45. 6mm Fixed lens, Built-in Chinese Plate License Recognition, No AC/DC adapter, No PoE. IP66 water proof		X	6mm	80m	IP66	1. 6/8/12/16mm
	SC6120-G21H	H.265/H.264 1/1.8" 2 Megapixel Starlight Super Lux Box IP Camera for Traffic Road Plate License Recognition application. 1920*1080@25fps, 1/1.8" CMOS sensor Super low light, digital WDR. It can drive LED white lights, Micro SD card slot (64G), audio & alarm input/output, RS485, BNC video output, 100M RJ45. Built-in Chinese Plate License Recognition, Built-in PoE, No AC/DC adapter, No Lens.		X	25mm	80m	IP66	

	SC6120-G21C	H.265/H.264 1/2.8" 2 Megapixel High Speed Sensor Sensor Box IP Camera for Parking Lot Plate License Recognition application. 1920*1080@25fps, 1/2.8" High Speed CMOS sensor Super low light,digital WDR.It can drive LED white lights, Max 80-100m, Micro SD card slot (64G), audio & alarm input/output, RS485, BNC video output, 100M RJ45. Built-in Chinese Plate License Recognition, Built-in PoE, No AC/DC adapter, No Lens.		X	6mm	80m	IP66	1. 6/8/12/16mm
Indoor Box IP Camera. Lens, 3G, 4G, audio, alarm, outdoor housing are optional								
	SC6120A	1920*1080, Sony Exmor 1/2.8" CMOS sensor, CPU 500MHZ, H.264 MP, BP. Super low light, Digital WDR, intelligence 3D noise reduction.Micro SD card. No PoE, No Lens, No AC/DC adapter.		X	X	X	X	1. CS Lens 2. IR-Cut: \$4 3. Audio,Alarm,Video Output: \$6 4. AC/DC Adapter: \$4
	SC6121A	1920*1080, Sony Exmor 1/2.8" CMOS sensor, CPU 500MHZ, H.264 MP, BP. Super low light, Digital WDR, intelligence 3D noise reduction.Micro SD card. Built-in PoE, No Lens, No AC/DC adapter.		√	X	X	X	1. CS Lens 2. IR-Cut: \$4 3. Audio,Alarm,Video Output: \$6 4. AC/DC Adapter: \$4
	SC6121H-H5	2 Megapixel 1080P H.265 Indoor Box IP Camera. 1920*1080@25fps, Sony Exmor 1/2.8" CMOS sensor,H.264 HP, MP, BP.super low light, Digital WDR, intelligence 3D noise reduction.Micro SD card. Built-in PoE, No Lens, No AC/DC adapter.		√	X	X	X	1. CS Lens 2. IR-Cut: \$4 3. Audio,Alarm,Video Output: Free 4. AC/DC Adapter: \$4 5. 3G WCDMA module: \$79 6. 4G LTE module: \$139
	SC6121H-H5W	2 Megapixel 1080P@25fps H.265 Super WDR Indoor Box IP Camera. 1920*1080@25fps, 1/2.8" Machine Vision CMOS sensor + Hisilicon Hi3516D, H.265 Encode, MP, BP. Multiple Exposure 130dB Super WDR, Star light level Super low light, ,Highlight Compensation (HLC), intelligence 3D noise reduction. Micro SD card (max 2TB). Built-in PoE, IR-Cut, Audio, 1000M Gigabit RJ45, Alarm ,RS485, No Lens, No AC/DC adapter. It is for traffice.		√	X	X	X	1. CS Lens 2. IR-Cut: Free 3. Audio,Alarm,Video Output: Free 4. AC/DC Adapter: \$4 5. 3G WCDMA module: \$79 6. 4G LTE module: \$139
	SC6121H-H5D	2 Megapixel 1080P@25fps H.265 Super Low Light Indoor Box IP Camera, 1920*1080@25fps, Sony Exmor R 1/1.8" CMOS sensor IMX178LQJ+ Hisilicon Hi3516D, H.265 Encode, MP, BP. Star Level Super low light, ,Highlight Compensation (HLC), Digital WDR, intelligence 3D noise reduction.Micro SD card(max 128G). 1000M Gigabit RJ45, Built-in PoE, IR-Cut, Audio ,Alarm ,RS485, No Lens, No AC/DC adapter.		√	X	X	X	1. CS Lens 2. IR-Cut: Free 3. Audio,Alarm,Video Output: Free 4. AC/DC Adapter: \$4 5. 3G WCDMA module: \$79 6. 4G LTE module: \$139
	SC5620GL-40X	2.0 Megapixel 1080P 40x Zoom Laser High Speed PTZ IP Camera 1920*1080@25fps, 40x optical zoom module, audio in/out, alarm in /out, video output CVBS, built-in SD card slot, RS485, IP 66. -40° C to 60° C, AC24V, auto temperature control. Built-in TVS4001V lightning-proof, surge-proof and wave-proof. 1/2.8" Progressive Scan CMOS; Laser night		√	6.8~272.2 mm, 40x optical zoom	X	X	1. IR-Cut: Free 2. Audio,Alarm,Video Output: Free 3. AC/DC Adapter: \$4 4. IP66 outdoor housing 5. 3G WCDMA module: \$79 6. 4G LTE module: \$139
	SC6121BS	1920*1080, Sony Exmor 1/2.8" CMOS sensor, CPU 900MHZ, H.264 HP, MP, BP.super low light, Digital WDR, intelligence 3D noise reduction.Micro SD card. Support intelligent analysis (perimeter intrusion, tripwire, double tripwire, etc.) Built-in PoE, No Lens, No AC/DC adapter.		√	X	X	X	1. CS Lens 2. Audio,Alarm,Video Output: \$6 4. AC/DC Adapter: \$4

 H.265 5MP@25fp 1080P@50fp	SC6151G-H5	5 Megapixel Real Time 25fps H.265 Super Low Light Indoor Box IP Camera , 2592*1920@25fps, Sony Exmor R 1/1.8" CMOS sensor IMX178LQJ+Hisilicon Hi3516A, H.265 Encode, MP, BP. Super low light , Digital WDR,intelligence 3D noise reduction.Micro SD card(max 128G). 1000M Gigabit RJ45 ,Built-in PoE, IR-Cut, Audio, Alarm, RS485, No Lens, No AC/DC adapter .	√	X	X	X	1. CS Lens 2. IR-Cut: Free 3. Audio,Alarm,Video Output: Free 4. AC/DC Adapter: \$4 5. 3G WCDMA module: \$79 6. 4G LTE module: \$139
 H.265 4MP@25fp	SC6141A	4 Megapixel Real Time 25fps H.265 Indoor Box IP Camera , 2592*1920@25fps, 1/3" WDR CMOS sensor, H.265 Encode, Optical WDR, intelligence 3D noise reduction.Micro SD card(max 128G). Built-in PoE, No Lens, No AC/DC adapter .	√	X	X	X	1. CS Lens 2. IR-Cut: \$4 3. Audio,Alarm,Video Output: no 4. AC/DC Adapter: \$4 5. 3G WCDMA module: \$79 6. 4G LTE module: \$139
 H.265 4MP@25fp	SC6141B	4 Megapixel Real Time 25fps H.265 Indoor Box IP Camera , 2592*1920@25fps, 1/3" WDR CMOS sensor, H.265 Encode, Optical WDR, intelligence 3D noise reduction.Micro SD card(max 128G). Built-in PoE, IR-Cut, Audio, Alarm, RS485, BNC output, No Lens, No AC/DC adapter .	√	X	X	X	1. CS Lens 2. IR-Cut: Free 3. Audio,Alarm,Video Output: Free 4. AC/DC Adapter: \$4 5. 3G WCDMA module: \$79 6. 4G LTE module: \$139
 H.265 3MP@25fp	SC6131A	3 Megapixel Real Time 25fps H.265 Indoor Box IP Camera , 2048*1520@25fps, 1/3" WDR CMOS sensor, H.265 Encode, Optical WDR, intelligence 3D noise reduction.Micro SD card(max 128G). Built-in PoE, No Lens, No AC/DC adapter .	√	X	X	X	1. CS Lens 2. IR-Cut: \$4 3. Audio,Alarm,Video Output: no 4. AC/DC Adapter: \$4 5. 3G WCDMA module: \$79 6. 4G LTE module: \$139
 H.265 3MP@25fp	SC6131B	3 Megapixel Real Time 25fps H.265 Indoor Box IP Camera , 2048*1520@25fps, 1/3" WDR CMOS sensor, H.265 Encode, Optical WDR, intelligence 3D noise reduction.Micro SD card(max 128G). Built-in PoE, IR-Cut, Audio, Alarm, RS485, BNC output, No Lens, No AC/DC adapter .	√	X	X	X	1. CS Lens 2. IR-Cut: Free 3. Audio,Alarm,Video Output: Free 4. AC/DC Adapter: \$4 5. 3G WCDMA module: \$79 6. 4G LTE module: \$139
PTZ High Speed Dome IP Camera							
	SC6620B-K20	1920*1080, Made In Korea camera module, CMOS, 20X optical Zoom, auto people tracking,audio in/out, alarm in/out, Wiper,analog video output, waterproof cable box metal housing. No IR light.	X	4.7mm(W) ~94mm (T) 20x Optical Zoom	X	√	
	SC6620B-S20	1920*1080, SONY FCB6300 camera module, CMOS, 20X Optical Zoom, auto people tracking,audio in/out, alarm in/out, Wiper,analog video output, waterproof cable box metal housing. No IR light.	X	4.7mm(W) ~94mm (T) 20x Optical Zoom	X	√	
	SC6620-S20	1920*1080, SONY FCB6300 camera module, CMOS, 20X Optical Zoom, , auto people tracking,audio in/out, alarm in/out, analog video output, Wiper,IR distance 180m, waterproof cable box metal housing	X	4.7mm(W) ~94mm (T) 20x Optical Zoom	180m	√	

	SC6620-S30	1920*1080, SONY FCB-EH7500 camera module, CMOS, 30X Optical Zoom, , auto people tracking,audio in/out, alarm in/out, analog video output,Wiper,IR distance 180m, waterproof cable box metal housing		X	4.6mm(W) ~138.0mm (T) 30x Optical Zoom	180m	√	
--	------------	--	--	---	---	------	---	--

SC8000 Series Professional IP Camera Price List

Triple Stream	IPv4/IPv6	ONVIF 2.6	Shutter: 1/5~1/50000S	H.265/H.264	Sony Sensor	WDR Starlight	-40℃ - +60℃	128G TF Card	3D/2D DNR
---------------	-----------	-----------	-----------------------	-------------	-------------	---------------	-------------	--------------	-----------

Multiple Languages: English,Русский,Español,ภาษาไทย,Czech, Français,Deutsch,PolSKI,Türkçe,Italiano,한국어,Tiếng Việt, 繁體中文.

Multiple Protocols: HTTPS, NAS, SNMP, 802.1X, QoS, IPv6, Bonjour, IP/Mac Address Filter, RTSP/RTP/RTCP, RTMP, ONVIF2.6, CGI(HTTP API), FTP, SSH, UPnP, IGMP, Multicast, Auto Reboot.

Note:

The following prices have Minimum Order Quantity (MOQ) requirement, if your order quantity is less than the MOQ, the unit price will add \$10-30;

Picture	Model	Specifications	Price	Power Supply	Lens	Infrared	Protection	Options & Remark
	SC8N21	2 Megapixel 1080P Sony Sensor Small Vandal Proof Dome PoE IP Camera 1920x1080@25fps, Sony 2 Megapixel Low light sensor IMX323 + Hi3516C SoC chip, Color: 0.1Lux@F1.2; B/W:0.01Lux@F1.2; DWDR,BLC,ROI, 3D DNR, triple streaming, 2.8mm M12 lens, 24 pcs LED light, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IP66, IK10. IP/MAC address filter.		PoE	2.8mm	30m	IP66,IK10	1.MOQ: 10pcs 2. Sample price: plus \$15 3. 3.6mm is optional
	SC8N21-Mic	2 Megapixel 1080P Sony Sensor Small Vandal Proof Dome PoE IP Camera 1920x1080@25fps, Sony 2 Megapixel Low light sensor IMX323 + Hi3516C SoC chip, Color: 0.1Lux@F1.2; B/W:0.01Lux@F1.2; DWDR,BLC,ROI, 3D DNR, triple streaming, 2.8mm M12 lens, 24 pcs LED light, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IP66, IK10. IP/MAC address filter. Built-in Microphone		PoE	2.8mm	30m	X	1.MOQ: 10pcs 2. Sample price: plus \$15 3. 3.6mm is optional
	SC8N21S	2 Megapixel 1080P Sony Starlight WDR Sensor Small Vandal Proof Dome PoE IP Camera 1920x1080@25fps, Sony IMX291 2 Megapixel starlight sensor + Hi3516D SoC chip, Full color: 0.02Lux@F1.2, B/W:0.002Lux; WDR:120dB,BLC,ROI, 3D DNR, triple streaming, 2.8mm M12 lens, 24 pcs LED light, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IP66, IK10. IP/MAC address filter.		PoE	2.8mm	20-30m	IP66,IK10	1.MOQ: 10pcs 2. Sample price: plus \$15 3. 3.6mm is optional
	SC8N21S-MIC	2 Megapixel 1080P Sony Starlight WDR Sensor Small Vandal Proof Dome PoE IP Camera 1920x1080@25fps, Sony IMX291 2 Megapixel starlight sensor + Hi3516D SoC chip, Full color: 0.02Lux@F1.2, B/W:0.002Lux; WDR:120dB,BLC,ROI, 3D DNR, triple streaming, 2.8mm M12 lens, 24 pcs LED light, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IP66, IK10. IP/MAC address filter.		PoE	2.8mm	20-30m	IK10	1.MOQ: 10pcs 2. Sample price: plus \$15 3. 3.6mm is optional
	SC8N21C	2 Megapixel Sony Super Starlight WDR Sensor Small Vandal Proof Dome PoE IP Camera 1080P@60fps, Sony 2 Megapixel Low light sensor IMX291+ Hi3516A SoC chip, Full Color: 0.001Lux@F1.2; WDR:130dB,BLC,ROI, 3D DNR, triple streaming, 2.8mm M12 lens, 24 pcs LED light, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IP66, IK10. IP/MAC address filter.		PoE	2.8mm	20-30m	IP66,IK10	1.MOQ: 10pcs 2. Sample price: plus \$15 3. 3.6mm is optional 4. Built-in Mic: \$5

	SC8N31B	3 Megapixel Sony Starlight Sensor Small Vandal Proof Dome PoE IP Camera 2048*1536@25fps, Sony 2 Megapixel Low light sensor IMX123+ Hi3516D SoC chip, Full Color: 0.001Lux@F1.2 ; WDR:130dB,BLC,ROI, 3D DNR, triple streaming, 2.8mm M12 lens, 24 pcs LED light, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IP66, IK10. IP/MAC address filter.		PoE	2.8mm	20-30m	IP66,IK10	1.MOQ: 10pcs 2. Sample price: plus \$15 3. 3.6mm is optional
	SC8N41A	4 /3 Megapixel 20fps H.265/H.264 WDR Small Vandal Proof Dome PoE IP Camera 4 Megapixel : 2592x1520@20fps, 3 Megapixel: 2048x1520@25fps, 4 Megapixel sensor OV4689 + Hi3516D SoC chip, WDR 80dB,BLC,ROI, 3D DNR, triple streaming, 2.8mm M12 lens, 24 pcs LED light, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IP66, IK10. IP/MAC address filter.		PoE	2.8mm	20-30m	IP66,IK10	1.MOQ: 10pcs 2. Sample price: plus \$15 3. 3.6mm is optional 4.Built-in Mic: \$5
	SC8N51B	5 Megapixel 25/30fps H.265/H.264 Super Starlight & WDR Small Vandal Proof Dome PoE IP Camera 5 Megapixel Sony sensor IMX178 + Hi3516A SoC chip, 5 megapixel: 2592*1944, 25/30fps, Color: 0.03Lux@F1.2,B/W: 0.001 Lux@F1.2 WDR: 100dB,BLC,ROI, 3D DNR, 3D DNR, triple streaming, 2.8mm M12 lens, 24 pcs LED light, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IP66, IK10. IP/MAC address filter.		PoE	2.8mm	20-30m	IP66,IK10	1.MOQ: 10pcs 2. Sample price: plus \$15 3. 3.6mm is optional 4. Built-in Mic: \$5
	SC8J21	2 Megapixel 1080P Sony Sensor Vandal Proof Dome PoE IP Camera 1920x1080@25fps, Sony 2 Megapixel Low light sensor IMX323 + Hi3516C SoC chip, Color: 0.1Lux@F1.2; B/W:0.01Lux@F1.2; DWDR,BLC,ROI, 3D DNR, triple streaming, 2.8-12mm varifocal lens, 24 pcs LED light, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IP66, IK10. IP/MAC address filter.		PoE	2.8-12mm	20-30m	IP66,IK10	1.MOQ: 10pcs 2. Sample price: plus \$15 3. 2.8/3.6mm is optional 4. audio input/output: \$5
	SC8J21S	2 Megapixel 1080P Sony Starlight WDR Sensor Vandal Proof Dome PoE IP Camera 1920x1080@25fps, Sony IMX291 2 Megapixel starlight sensor + Hi3516D SoC chip, Full color: 0.02Lux@F1.2, B/W:0.002Lux; WDR:120dB,BLC,ROI, 3D DNR, triple streaming, 2.8-12mm varifocal lens,24 pcs LED light, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IP66, IK10. IP/MAC address filter.		PoE	2.8-12mm	20-30m	IP66,IK10	1.MOQ: 10pcs 2. Sample price: plus \$15 3. 2.8/3.6mm is optional 4. audio input/output: \$5
	SC8J21C	2 Megapixel Sony Super Starlight WDR Sensor Small Vandal Proof Dome PoE IP Camera 1080P@60fps, Sony 2 Megapixel Low light sensor IMX291+ Hi3516A SoC chip, Full Color: 0.001Lux@F1.2 ; WDR:130dB,BLC,ROI, 3D DNR, triple streaming, 2.8-12mm varifocal lens, 24 pcs LED light, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IP66, IK10. IP/MAC address filter.		PoE	2.8-12mm	20-30m	IP66,IK10	1.MOQ: 10pcs 2. Sample price: plus \$15 3. 2.8/3.6mm is optional 4. audio input/output: \$5

 	SC8J31B	3 Megapixel Sony Starlight Sensor Vandal Proof Dome PoE IP Camera 2048*1536@25fps, Sony 3 Megapixel Low light sensor IMX123+ Hi3516D SoC chip, Full Color: 0.001Lux@F1.2; WDR:130dB,BLC,ROI, 3D DNR, triple streaming, 2.8-12mm varifocal lens, 24 pcs LED light, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IP66, IK10. IP/MAC address filter.		PoE	2.8-12mm	20-30m	IP66,IK10	1.MOQ: 10pcs 2. Sample price: plus \$15 3. 2.8/3.6mm is optional 4. audio input/output: \$5
	SC8J41A	4 /3 Megapixel 20fps H.265/H.264 WDR Small Vandal Proof Dome PoE IP Camera 4 Megapixel : 2592x1520@20fps, 3 Megapixel: 2048x1520@25fps, 4 Megapixel sensor OV4689 + Hi3516D SoC chip, WDR:130dB,BLC,ROI, 3D DNR, triple streaming, 2.8-12mm varifocal lens, 24 pcs LED light, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IP66, IK10. IP/MAC address filter.		PoE	2.8-12mm	20-30m	IP66,IK10	1.MOQ: 10pcs 2. Sample price: plus \$15 3. 2.8/3.6mm is optional 4. audio input/output: \$5
	SC8J51B	5 Megapixel Sony Super Starlight 25/30fps, H.265/H.264 Vandal Proof Dome PoE IP Camera 5 Megapixel : 2592*1944@25/30fps, Sony 1/1.8" super starlight 5 Megapixel sensor IMX178 + Hi3516A SoC chip, Full color: 0.001Lux@F1.2; WDR:100db,BLC,ROI, 3D DNR, 3.6-11mm varifocal lens, 24 pcs LED light, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IP66, IK10. IP/MAC address filter.		PoE	3.6-11mm	20-30m	IP66,IK10	1.MOQ: 10pcs 2. Sample price: plus \$15 3. 2.8/3.6mm is optional 4. audio input/output: \$5
	SC8E21Z	2 Megapixel 1080P Sony Sensor 2.8-12mm Motorized Zoom & Auto Focus Big Vandal Proof Dome PoE IP Camera 1920x1080@25fps, Sony IMX323 2 Megapixel low light sensor + Hi3516C SoC chip, Full color: 0.1Lux@F1.2, B/W:0.001Lux; WDR:80dB,BLC,ROI, 3D DNR, triple streaming, 2.8-12mm motorized zoom auto focus, auto IRIS lens, IR light:30-50m, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IP66, IK10. IP/MAC address filter. Alarm, audio input/output, RS485,BNC output. Built-in Mini SD card slot, max support 128GB.		PoE	2.8-12mm motorized zoom & autofocus, DC Auto IRIS		IP66,IK10	1.MOQ: 20pcs 2. Sample price: plus \$15
	SC8E21SZ	2 Megapixel 1080P Sony Starlight WDR Sensor 2.8-12mm Motorized Zoom & Auto Focus Big Vandal Proof Dome PoE IP Camera 1920x1080@25fps, Sony IMX291 2 Megapixel starlight sensor + Hi3516D SoC chip, Full color: 0.02Lux@F1.2, B/W:0.002Lux; WDR:120dB,BLC,ROI, 3D DNR, triple streaming, 2.8-12mm motorized zoom auto focus, auto IRIS lens, IR light:30-50m, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IP66, IK10. IP/MAC address filter. Alarm, audio input/output, RS485,BNC output. Built-in Mini SD card slot, max support 128GB.		PoE	2.8-12mm motorized zoom & autofocus, DC Auto IRIS		IP66,IK10	1.MOQ: 20pcs 2. Sample price: plus \$15

	SC8E21BSZ	2 Megapixel 1080P 60fps Sony Starlight WDR Sensor 2.8-12mm Motorized Zoom & Auto Focus Big Vandal Proof Dome PoE IP Camera 1920x1080@25fps, Sony IMX291 2 Megapixel starlight sensor + Hi351AD SoC chip, Full color: 0.02Lux@F1.2, B/W:0.002Lux; WDR:120dB,BLC,ROI, 3D DNR, triple streaming, 2.8-12mm motorized zoom auto focus, auto IRIS lens, IR light:30-50m, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IP66, IK10. IP/MAC address filter. Alarm, audio input/output, RS485, reset cable. Built-in Mini SD card slot, max support 128GB.		PoE	2.8-12mm motorized zoom & autofocus, DC Auto IRIS		IP66,IK10	1.MOQ: 20pcs 2. Sample price: plus \$15
	SC8E31Z	3 Megapixel Sony Starlight Sensor 2.8-12mm Motorized Zoom & Auto Focus Big Vandal Proof Dome PoE IP Camera 2048*1536@25fps, Sony 3 Megapixel Low light sensor IMX123+ Hi3516D SoC chip, Full Color: 0.001Lux@F1.2; WDR:130dB,BLC,ROI, 3D DNR, triple streaming, 2.8-12mm motorized zoom auto focus, auto IRIS lens, IR light:30-50m, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IP66, IK10. IP/MAC address filter. Alarm, audio input/output, RS485, BNC output. Built-in Mini SD card slot, max support 128GB.		PoE	2.8-12mm motorized zoom & autofocus, DC Auto IRIS		IP66,IK10	1.MOQ: 20pcs 2. Sample price: plus \$15
	SC8E41AZ	4 /3 Megapixel 20fps H.265/H.264 WDR Small Vandal Proof Dome PoE IP Camera 4 Megapixel : 2592x1520@20fps, 3 Megapixel: 2048x1520@25fps, 4 Megapixel sensor OV4689 + Hi3516D SoC chip, WDR:130dB,BLC,ROI, 3D DNR, triple streaming, 2.8-12mm motorized zoom auto focus, auto IRIS lens, IR light:30-50m, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IP66, IK10. IP/MAC address filter. Alarm, audio input/output, RS485, BNC output. Built-in Mini SD card slot, max support 128GB.		PoE	2-12mm motorized zoom & autofocus, DC Auto IRIS		IP66,IK10	1.MOQ: 20pcs 2. Sample price: plus \$15
	SC8E51Z	5 Megapixel Sony Starlight Sensor 2.8-12mm Motorized Zoom & Auto Focus Big Vandal Proof Dome PoE IP Camera 2048*1536@25fps, Sony 3 Megapixel Low light sensor IMX123+ Hi3516D SoC chip, Full Color: 0.001Lux@F1.2; WDR:130dB,BLC,ROI, 3D DNR, triple streaming, 3.6-11mm motorized zoom auto focus, auto IRIS lens, IR light:30-50m, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. High end metal dome, IP66, IK10. IP/MAC address filter. Alarm, audio input/output, RS485, BNC output. Built-in Mini SD card slot, max support 128GB.		PoE	3.6-11mm motorized zoom & autofocus, DC Auto IRIS		IP66,IK10	1.MOQ: 20pcs 2. Sample price: plus \$15
	SC8K21B	2 Megapixel 1080P Sony Low Light Sensor IR Bullet IP Camera 1920x1080@25fps, Sony IMX323 2 Megapixel sensor + Hi3516C SoC chip, Color: 0.1Lux@F1.2; B/W:0.01Lux@F1.2; DWDR,BLC,ROI, triple streaming, 8mm CS lens, 4 array LED light, IR distance 50m, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring.		PoE	8mm	50m	IP66	1. 6/8/12mm lens: free 2. MOQ: 10pcs 3. Sample price: plus \$15

	SC8K21BZ	2 Megapixel 1080P Sony Low Light Zoom Sensor IR Bullet IP Camera 1920x1080@25fps, Sony IMX323 2 Megapixel sensor + Hi3516C SoC chip, Color: 0.1Lux@F1.2; B/W:0.01Lux@F1.2; DWDR,BLC,ROI, triple streaming, 2.8-12mm motorized zoom and auto focus lens, 4 array LED light, IR distance 50m, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring.		PoE	2.8-12mm motorized zoom & autofocus	50m	IP66	1. MOQ: 10pcs 2. Sample price: plus \$15
	SC8K21S	H.265/H.264 2 Megapixel 1080P Sony StarLight Sensor IR Bullet IP Camera 1920x1080@25fps, Sony IMX291 2 Megapixel starlight sensor + Hi3516D SoC chip, Full color: 0.001Lux@F1.2; DWDR,BLC,ROI, triple streaming, 8mm CS lens, 4 array LED light, IR distance 50m,ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring. No bracket.		PoE	8mm	50m	IP66	1.6/8/12mm lens: free 2. 2.8-12mm motorized zoom and auto focus lens: \$15
	SC8K41A	4 Megapixel 15fps H.265/H.264 IR Bullet PoE IP Camera 4 Megapixel : 2592x1520@15fps, 3 Megapixel: 2048x1520@25fps, 4 Megapixel sensor OV4689 + Hi3516D SoC chip, 8mm CS lens,DWDR,BLC,ROI, triple streaming, 8mm CS lens, 4 array LED light, IR distance 50m, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring.		PoE	8mm	50m	IP66	1.6/8/12mm lens: free 2. 2.8-12mm motorized zoom and auto focus lens: \$15
	SC8K41AZ	4 Megapixel 15fps H.265/H.264 IR Bullet PoE IP Camera 4 Megapixel : 2592x1520@15fps, 3 Megapixel: 2048x1520@25fps, 4 Megapixel sensor OV4689 + Hi3516D SoC chip, 2.8-12mm motorized zoom and auto focus lens, 4 array LED light, IR distance 50m, built-in Smart function, ONVIF; DC12V, Built-in PoE, No AC/DC adapter. P2P Mobile Monitoring.		PoE	2.8-12mm motorized zoom & autofocus	50m	IP66	1.MOQ: 10pcs 2. Sample price: plus \$15
	SC8K31B	3 Megapixel Sony Starlight 25/30fps H.265/H.264 IR Bullet IP Camera 2048x1520@25fps, 3 Megapixel starlight sensor Sony IMX124+ Hi3516D SoC chip, Full color: 0.001Lux@F1.2; DWDR,BLC,ROI, 8mm lens, 4 array LED light, IR distance 50m, built-in Smart function, ONVIF; DC12V,built-in PoE,, No AC/DC adapter. P2P Mobile Monitoring.		PoE	8mm	50m	IP66	1.6/8/12mm lens: free 2. 2.8-12mm motorized zoom and auto focus lens: \$15
	SC8K51B	5 Megapixel 25fps H.265/H.264 Sony Starlight IR Bullet IP Camera 5 Megapixel : 2592*1944@25/30fps, Sony 1/1.8" super starlight 5 Megapixel sensor IMX178 + Hi3516A SoC chip,Full color: 0.001Lux@F1.2; 8mm CS lens, 4 array LED light, IR distance 50m, built-in Smart function, ONVIF; DC12V,built-in PoE, No AC/DC adapter. P2P Mobile Monitoring. Alarm, audio input/output, RS485, reset cable.		PoE	8mm	50m	IP66	1.6/8/12mm lens: free 2.MOQ: 20pcs 3. Sample price: plus \$15

	SC8R21S-T62	H.265/H.264 2 Megapixel 1080P Sony StarLight Sensor IR Bullet IP Camera 1920x1080@25fps, Sony IMX291 2 Megapixel starlight sensor + Hi3516D SoC chip, Full color: 0.001Lux@F1.2 ; DWDR,BLC,ROI, triple streaming, 6-22mm varifocal lens, 6 array LED light, IR distance 80100m,ONVIF; DC12V, Built-in PoE , No AC/DC adapter. P2P Mobile Monitoring. SunShield, No bracket.		PoE	6-22mm	80-100m	IP66	1.6/8/12/16mm lens: free 2. 2.8-12mm lens: free 3.MOQ: 20pcs 4. Sample price: plus \$15
	SC8C21P	2 Megapixel 50/60fps WDR HLC Outdoor Bullet HD IP Camera for Traffic 1080P@60fps, Sony 2 Megapixel Low light sensor IMX291+ Hi3516A SoC chip, Full Color: 0.001Lux@F1.2; WDR:130dB,BLC,ROI, 3D DNR, triple streaming, H.265/H.264 & MJPEG encoding, 0.05Lux/F1.4(color),0.01Lux/F1.4 (B/W). 80-100mm IR distance (or white light LED), 12mm fixed lens. No bracket. No AC/DC adapter.		PoE	12mm	80-100m	IP66	1. 4/6/8/12mm lens: free 2. 2.8-12mm varifocal lens: \$9 3. 6-22mm varifocal lens: \$12 4. 2.8-12mm motorized lens: \$26 5. 5-50mm varifocal lens: \$49 6. MOQ: 5pcs 7. Sample price: plus \$20

SC4000 Series Cheap IP Camera Price List

Notes:

1. Minimum Order Quantity(MOQ) is 50 pieces;
2. Small order(5pcs < Quantity < 50pcs): the unit price add \$1-2;
3. Sample order(Quantity <= 5pcs), the unit price add \$10;
4. All cameras don't include AC/DC adapter, built-in PoE: add USD4;
5. If the order total value < USD5,000, you need to pay additional charges (\$20-30).
6. We could update the price in any time and don't immediately notice you. Product picture is for reference only.

IR Bullet IP Camera

	MODEL	Chip Solution	Pixels	Resolution	Frames	ONVIF	Power	PoE	Housing	Water Proof	Size	Lens	IR Distance
	SC4A10A	XM510A + H42	1.0MP	1280*720	25fps	yes	DC 12V	Optional	Plastic	IP66	75#	6mm	20-30m
	SC4A10B	XM510A + AR013	1.3MP	1280*960	25fps	yes	DC 12V	Optional	Plastic	IP66	75#	6mm	20-30m
	SC4A10C	3518C+0130	1.3MP	1280*960	25fps	yes	DC 12V	Optional	Plastic	IP66	75#	6mm	20-30m
	SC4A20A	3516C+2035	2.0MP	1920*1080	25fps	yes	DC 12V	Optional	Plastic	IP66	75#	6mm	20-30m
	SC4A20B	3516C+SONY322	2.0MP	1920*1080	25fps	yes	DC 12V	Optional	Plastic	IP66	75#	6mm	20-30m

	MODEL	Chip Solution	Pixels	Resolution	Frames	ONVIF	Power	PoE	Housing	Water Proof	Size	Lens	IR Distance
	SC4810A	3518E+9712	1.0MP	1280*720	25fps	yes	DC 12V	Optional	Metal	IP66	60#	3.6mm	15-20m
	SC4810B	3518E+1035	1.3MP	1280*960	25fps	yes	DC 12V	Optional	Metal	IP66	60#	3.6mm	15-20m
	SC4810C	3518C+0130	1.3MP	1280*960	25fps	yes	DC 12V	Optional	Metal	IP66	60#	3.6mm	15-20m
	SC4820A	3516C+2035	2.0MP	1920*1080	25fps	yes	DC 12V	Optional	Metal	IP66	60#	3.6mm	15-20m
	SC4820B	3516C+SONY322	2.0MP	1920*1080	25fps	yes	DC 12V	Optional	Metal	IP66	60#	3.6mm	15-20m

	Model	Chip Solution	Pixels	Resolution	Frames	ONVIF	Power	PoE	Housing	Water Proof	Size	Lens	IR Distance
	SC4B10A	3518E+9712	1.0MP	1280*720	25fps	yes	DC 12V	Optional	Metal	IP66	60#	3.6mm	15-20m
	SC4B10B	3518E+1035	1.3MP	1280*960	25fps	yes	DC 12V	Optional	Metal	IP66	60#	3.6mm	15-20m
	SC4B10C	3518C+0130	1.3MP	1280*960	25fps	yes	DC 12V	Optional	Metal	IP66	60#	3.6mm	15-20m
	SC4B20A	3516C+2035	2.0MP	1920*1080	25fps	yes	DC 12V	Optional	Metal	IP66	60#	3.6mm	15-20m
	SC4B20B	3516C+SONY322	2.0MP	1920*1080	25fps	yes	DC 12V	Optional	Metal	IP66	60#	3.6mm	15-20m

	Model	Chip Solution	Pixels	Resolution	Frames	ONVIF	Power	PoE	Housing	Water Proof	Size	Lens	IR Distance
	SC4410A	3518E+9712	1.0MP	1280*720	25fps	yes	DC 12V	Optional	Metal	IP66	60#	2.8-12mm	30-35m
	SC4410B	3518E+1035	1.3MP	1280*960	25fps	yes	DC 12V	Optional	Metal	IP66	60#	2.8-12mm	30-35m
	SC4410C	3518C+0130	1.3MP	1280*960	25fps	yes	DC 12V	Optional	Metal	IP66	60#	2.8-12mm	30-35m
	SC4420A	3516C+2035	2.0MP	1920*1080	25fps	yes	DC 12V	Optional	Metal	IP66	60#	2.8-12mm	30-35m
	SC4420B	3516C+SONY322	2.0MP	1920*1080	25fps	yes	DC 12V	Optional	Metal	IP66	60#	2.8-12mm	30-35m

	Model	Chip Solution	Pixels	Resolution	Frames	ONVIF	Power	PoE	Housing	Water Proof	Size	Lens	IR Distance
	SC4010A	3518E+9712	1.0MP	1280*720	25fps	yes	DC 12V	Optional	Metal	IP66	60#	2.8-12mm	30-35m
	SC4010B	3518E+1035	1.3MP	1280*960	25fps	yes	DC 12V	Optional	Metal	IP66	60#	2.8-12mm	30-35m
	SC4010C	3518C+0130	1.3MP	1280*960	25fps	yes	DC 12V	Optional	Metal	IP66	60#	2.8-12mm	30-35m
	SC4020A	3516C+2035	2.0MP	1920*1080	25fps	yes	DC 12V	Optional	Metal	IP66	60#	2.8-12mm	30-35m
	SC4020B	3516C+SONY322	2.0MP	1920*1080	25fps	yes	DC 12V	Optional	Metal	IP66	60#	2.8-12mm	30-35m

IR Dome IP Camera

	Model	Chip Solution	Pixels	Resolution	Frames	ONVIF	Power	PoE	Housing	Water Proof	Size	Lens	IR Distance
	SC4910A	3518E+9712	1.0MP	1280*720	25fps	yes	DC 12V	Optional	Plastic	no	60#	3.6mm	15-20m
	SC4910B	3518E+1035	1.3MP	1280*960	25fps	yes	DC 12V	Optional	Plastic	no	60#	3.6mm	15-20m
	SC4910C	3518C+0130	1.3MP	1280*960	25fps	yes	DC 12V	Optional	Plastic	no	60#	3.6mm	15-20m
	SC4920A	3516C+2035	2.0MP	1920*1080	25fps	yes	DC 12V	Optional	Plastic	no	60#	3.6mm	15-20m
	SC4920B	3516C+SONY322	2.0MP	1920*1080	25fps	yes	DC 12V	Optional	Plastic	no	60#	3.6mm	15-20m

	Model	Chip Solution	Pixels	Resolution	Frames	ONVIF	Power	PoE	Housing	Water Proof	Size	Lens	IR Distance
	SC4G10A	3518E+9712	1.0MP	1280*720	25fps	yes	DC 12V	Optional	Metal	IP66	60#	3.6mm	15-20m
	SC4G10B	3518E+1035	1.3MP	1280*960	25fps	yes	DC 12V	Optional	Metal	IP66	60#	3.6mm	15-20m
	SC4G10C	3518C+0130	1.3MP	1280*960	25fps	yes	DC 12V	Optional	Metal	IP66	60#	3.6mm	15-20m
	SC4G20A	3516C+2035	2.0MP	1920*1080	25fps	yes	DC 12V	Optional	Metal	IP66	60#	3.6mm	15-20m
	SC4G20B	3516C+SONY322	2.0MP	1920*1080	25fps	yes	DC 12V	Optional	Metal	IP66	60#	3.6mm	15-20m
	Model	Chip Solution	Pixels	Resolution	Frames	ONVIF	Power	PoE	Housing	Water Proof	Size	Lens	IR Distance
	SC4E10A	3518E+9712	1.0MP	1280*720	25fps	yes	DC 12V	Optional	Metal	IP66	60#	3.6mm	15-20m
	SC4E10B	3518E+1035	1.3MP	1280*960	25fps	yes	DC 12V	Optional	Metal	IP66	60#	3.6mm	15-20m
	SC4E10C	3518C+0130	1.3MP	1280*960	25fps	yes	DC 12V	Optional	Metal	IP66	60#	3.6mm	15-20m
	SC4E20A	3516C+2035	2.0MP	1920*1080	25fps	yes	DC 12V	Optional	Metal	IP66	60#	3.6mm	15-20m
	SC4E20B	3516C+SONY322	2.0MP	1920*1080	25fps	yes	DC 12V	Optional	Metal	IP66	60#	3.6mm	15-20m
	Model	Chip Solution	Pixels	Resolution	Frames	ONVIF	Power	PoE	Housing	Water Proof	Size	Lens	IR Distance
	SC4J10A	3518E+9712	1.0MP	1280*720	25fps	yes	DC 12V	Optional	Vandal Proof	IP66	3.5"	2.8-12mm	15-20m
	SC4J10B	3518E+1035	1.3MP	1280*960	25fps	yes	DC 12V	Optional	Vandal Proof	IP66	3.5"	2.8-12mm	15-20m
	SC4J10C	3518C+0130	1.3MP	1280*960	25fps	yes	DC 12V	Optional	Vandal Proof	IP66	3.5"	2.8-12mm	15-20m
	SC4J20A	3516C+2035	2.0MP	1920*1080	25fps	yes	DC 12V	Optional	Vandal Proof	IP66	3.5"	2.8-12mm	15-20m
	SC4J20B	3516C+SONY322	2.0MP	1920*1080	25fps	yes	DC 12V	Optional	Vandal Proof	IP66	3.5"	2.8-12mm	15-20m

Special Products Price List

Note:

Some of the following product prices have Minimum Order Quantity (MOQ) requirement, if your order quantity is less than the MOQ, we will use sample price;

Picture	Model	Specifications	Options
	4Kx3K SC91K1-4K	12 Megapixel 15fps H.264 Super WDR Indoor Box IP Camera. 1/1.8" 12 Megapixel Progressive Scan SONY CMOS, Ambarella SOC; Color: 0.2 Lux @ 30IRE, F1.4 Black/White: 0.1 Lux @ 30IRE, F1.4, IR-cut, Resolution: 4000*3000@15fps, 4096*2160@24fps; IR-cut, Highlight Compensation (HLC), SD card, Built-in PoE, DC12V/AC24V, BNC, USB, HDMI, alarm, audio input/output, 100M/1000M RJ45 Ethernet, Triple stream: 1080p+Full D1+CIF, RS485, P-IRIS, working temperature: -20--60°C. No AC/DC Adapter, No IR Light, No Lens.	
	6MP SC9161	6 Megapixel 25/30fps H.264 Indoor Box IP Camera. 1/1.8" 6.3 Megapixel Progressive Scan SONY CMOS, Ambarella SOC; supports H.264 HP compression; color 0.05 Lux @ 30IRE, F1.4 black and white 0.005Lux @ 30IRE, F1.4, infrared sensors, 3072 x 2048 @ 25 / 30fps; Tri-streaming: 3072 * 2048 + D1 + Cvbs / HDMI, 3DNR, digital wide dynamic; auto iris, HDMI, BNC, USB, audio input and output, alarm input and output, SD card storage, 100 / 1000M RJ45 Ethernet, support DC12V / AC24V / POE optional power supply, RS485 output, precise back focus adjust, operating temperature: -20--60 °C. No AC/DC Adapter, No IR Light, No Lens.	
	Thermal SC8100T-L100	Thermal IP Network Camera Uncooled IRFPA Microbolometer Temperature detection Effective resolution 396x264 Sensitivity 50mK 100mm fixed lens (other lens is optional) Infrared detection wavelength 8-14um Support 8 area temperature Detection H.264/MJPEG, 100M RJ45, built-in SD card slot, audio input/output, alarm input/output. IPv4/v6, ONVIF	Optional lens: 8 / 15 / 25 / 35 / 50 / 75 / 100mm fixed lens, 75 / 100 / 150mm motorized zoom lens
	PoE SC8621-H20	20x Zoom 2MP 1080P PTZ Speed Dome PoE IP Camera Specification Built-in Hikvision 18x zoom 2 megapixel 1080P network HD module, built-in PoE. No IR light. HLC, 3DNR, 360° horizontal free rotating, 180° vertical rotating H 0.1~240° /s & V 0.1~240°/S Variable high speed rotating. Preset point: 255. working temperature: -20--60 °C. AC48V, PoE.	MOQ: 5PCS Sample: plus \$20

	SC8621-C33	33x Zoom 2MP 1080P Starlight IR PTZ Speed Dome PoE IP Camera 33x zoom 2 megapixel 1080P network HD module, Sony starlight sensor, built-in PoE. IR light: 300m . HLC, 3DNR, 360°horizontal free rotating, 180°vertical rotating H 0.1~240° /s & V 0.1~240°/S Variable high speed rotating. Preset point: 255. working temperature: -20--60 °C. DC12V, PoE.	MOQ:5PCS Sample: plus \$20
	SCH630-Z30	30x Zoom 3MP 25fps Starlight IR Bullet Outdoor IP Camera 30x zoom 3 megapixel 25fps realtime network HD module, Sony starlight sensor, IR light: 100m . HLC, 3DNR, working temperature: -35--60 °C. DC12V, no PoE. Built-in SD card slot, audio, alarm. ONVIFI. Wiper is optional.	MOQ:5PCS Sample: plus \$20
	SCH521-Z10	2 Megapixel 1080P 10x Zoom PTZ all-in-one Bullet IR IP Camera. IR-distance:50-80m, f=5.1-51mm, auto Iris, F1.6-F22, horizontal range: 0°~260°, vertical range: -5°~60°, speed: 12°/s. Built-in PoE, NO AC/DC adapter, NO alarm / audio (optional)	MOQ: 50PCS Sample: plus \$10
	SCH521-Z03	2 Megapixel 1080P 3x Zoom PTZ all-in-one Bullet IR IP Camera. IR-distance:50-80m, f=3-9mm, auto Iris, F1.6~F22, horizontal range: 0°~260°, vertical range: -5°~60°, speed: 12°/s. Built-in PoE, NO AC/DC adapter, NO alarm / audio (optional)	MOQ: 50PCS Sample: plus \$10
	SC8731-FE	3MP Fisheye Panoramic IP Camera: 2048*1536@20fps, 1080P@25fps, 23 IR lights, 10-15m. 1.56mm Ultra-wide angle Lens, Micro TF card. Built-in PoE, Ceilling Mount or Wall Mount;P2P plug and play function; No AC/DC adapter.No Wifi	MOQ:20PCS Sample: plus \$10
	SC9F61-FE	6 Megapixel 25/30fps 360° Fisheye Panorama Lens IR IP Dome Camera 1/1.8 " 6.3MP progressive scan SONY CMOS, Ambarella SOC; fish-eye panorama, ePTZ control, image split, image rectification, color 0.05 Lux @ 30IRE, F1.4 black and white 0.005Lux @ 30IRE, F1.4, infrared, 3072 x 2048 @ 25 / 30fps; multi-stream output, USB, 3D filtering, audio, alarm input and output, SD card storage, 100 / 1000M Ethernet , support DC12V power supply, RS485 output, precise back focus, operating temperature: -20--60 °C.	MOQ:5PCS Sample: plus \$20

	60fps SC9121B	2 Megapixel 1080P@60fps H.264 Super WDR Indoor Box IP Camera. 1920*1080@60fps, 1/1.8" Progressive CMOS sensor + Ambarella chip, H.264 Encoding, MP, BP. Super low light: color:0.005 Lux @ 30IRE, F1.2 B/W:0.0005Lux @ 30IRE, F1.2, IR-cut, Highlight Compensation (HLC), SD card, Built-in PoE, DC12V/AC24V, BNC, USB, HDMI, alarm, audio input/output, 100M/1000M RJ45 Ethernet, Triple stream:1080p+Full D1+CIF, RS485, P-IRIS, working temperature:-20--60℃. No AC/DC Adapter, No IR Light, No Lens.	
3MP 	SC9630A-C22	3 Megapixel 25/30fps 22x Zoom PTZ High Speed Dome IP Camera, Ambarella SoC, 1 / 2.8" 3.2MP progressive scan Sony CMOS, supports H.264 / H.265 compression; 22x optical zoom: f4.3-94.6 mm, color: 0.1Lux @ 30IRE, F1.6; black and white: 0.05Lux @ 30IRE, F1.6; 3.1MP (2048x1536), dual-stream: 3.1MP + D1 / 25fps. No IR light. HLC, 3DNR, ROI, defog, intrusion detection, and other smart dynamic tracking recognition; working temperature: -20--60 ℃.	IK10 is optional
3MP 30fps 	SC9630AR-C22	3 Megapixel 25/30fps 22x Zoom PTZ High Speed Dome IP Camera, Ambarella SoC, 1 / 2.8" 3.2MP progressive scan Sony CMOS, supports H.264 / H.265 compression; 22x optical zoom: f4.3-94.6 mm, color: 0.1Lux @ 30IRE, F1.6; black and white: 0.05Lux @ 30IRE, F1.6; 3.1MP (2048x1536), dual-stream: 3.1MP + D1 / 25fps. IR light: 150m. HLC, 3DNR, ROI, defog, intrusion detection, and other smart dynamic tracking recognition; working temperature: -20--60 ℃.	Sample: plus \$30
	SC8P30-4S	Panoramic 4 Sensors 180° 12 Megapixel 25/30fps Realtime Extra HD Camera, 180° vision, H.265/H.265 encoding, 12 Megapixel: 4*1/2.8"3.0 MP Pixel progressive scan CMOS, 4*4mm fixed-focus, multiple video merge, support ePTZ, support WEB and CMS view, 128G Micro SD slot. IP66, IK10. -30℃ ~ 60℃. It's suitable for airport, highway, railway station, port, square, etc. big area place.	
	SC8P30-5S	Panoramic 5 Sensors 360° 15 Megapixel Extra HD Camera, 360° vision, H.265/H.265 encoding, 15 Megapixel: 5*1/2.8"3.0 MP Pixel progressive scan CMOS, 5*4mm fixed-focus, multiple video merge, support ePTZ, support WEB and CMS view, 128G Micro SD slot. IP66, IK10. -30℃ ~ 60℃. It's suitable for airport, highway, railway station, port, square, etc. big area place.	

	SC8P30-5S	Panoramic 8 Sensors 360° 24 Megapixel 25/30fps Realtime Extra HD Camera, 360° vision, H.265/H.265 encoding, 24 Megapixel: 8*1/2.8"3.0 MP Pixel progressive scan CMOS, 8*4mm fixed-focus, multiple video merge, support ePTZ, support WEB and CMS view, 128G Micro SD slot. IP66, IK10. -30℃ ~ 60℃. It's suitable for airport, highway, railway station, port, square, etc. big area place.	
	SN5424S	24CH Intelligent NVR Support H.265/H.264 24ch 4K / 24ch 5MP / 16ch 1080P recording, 4ch 4K/ 4ch 5MP / 16ch 1080P playback; Support 4 x 4TB SATA hard disk, support SC5000 series intelligent IP cameras video analysis alarm (Audio Detection, Line Crossing Detection, Intrusion Detection, Unattended baggage; Color,brightness,Defocus Exception Detections.) 1.5U Size;	
	SN5832S	32CH Intelligent NVR Support H.265/H.264 32ch 4MP / 24ch 4K / 24ch 5MP / 16ch 1080P recording, 9ch 4MP / 4ch 4K/ 4ch 5MP / 16ch 1080P playback; Support 8 x 4TB SATA hard disk, support SC5000 series intelligent IP cameras video analysis alarm (Audio Detection, Line Crossing Detection, Intrusion Detection, Unattended baggage; Color,brightness,Defocus Exception Detections.) 2U Size	